



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SA性能 45mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.4	24.0	76.2	24.0	77.9	22.6	79.6	20.5	80.6	19.4
20.0	72.6	24.0	74.1	23.5	75.9	21.1	77.3	19.3	78.2	18.5
22.0	70.5	22.2	72.0	21.3	73.8	19.7	75.0	18.2	75.8	17.6
24.0	68.4	19.8	69.8	19.5	71.7	18.2	72.7	17.3	73.4	16.8
26.0	66.2	17.8	67.6	17.7	69.4	16.8	70.4	16.2	71.0	16.0
28.0	63.9	16.1	65.3	16.0	67.0	15.5	68.1	15.0	68.4	14.9
30.0	61.6	14.6	62.9	14.5	64.6	14.4	65.6	14.0	65.8	14.0
32.0	59.2	13.1	60.4	13.2	62.1	13.3	63.1	13.1		
34.0	56.6	12.0	57.9	12.0	59.4	12.1	60.4	12.1		
36.0	54.0	10.8	55.3	11.0	56.7	11.0	57.5	11.0		
38.0	51.2	9.1	52.6	9.7	53.9	9.9	54.4	10.0		
40.0	48.3	7.6	49.7	8.0	50.9	8.5	51.2	8.7		
42.0	45.3	6.2	46.7	6.6	47.8	7.0				
44.0	42.0	4.9	43.4	5.2	44.2	5.6				
46.0	38.5	3.7	39.8	4.0	40.3	4.3				
48.0	34.6	2.7	35.9	2.9	36.0	3.1				
危険角度 (°)		31		32		32		48		63
標準フック		24t		24t		24t		24t		24t
フック質量 (t)		0.88		0.88		0.88		0.88		0.88
巻掛本数		2		2		2		2		2

SA性能 45mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	12.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.9	12.0	70.0	12.0	72.7	12.0	74.7	12.0	76.0	12.0
28.0	65.0	12.0	68.1	12.0	70.8	12.0	72.6	12.0	73.7	12.0
30.0	63.1	12.0	66.1	12.0	68.7	12.0	70.4	12.0	71.3	12.0
32.0	61.1	12.0	64.1	12.0	66.6	12.0	68.2	12.0	68.7	11.8
34.0	59.1	12.0	62.1	12.0	64.3	11.5	65.8	11.2	66.1	11.1
36.0	56.8	11.0	59.8	11.2	61.9	10.8	63.3	10.5		
38.0	54.4	10.0	57.4	10.2	59.5	10.1	60.7	9.9		
40.0	52.0	8.8	54.9	9.4	56.9	9.4	58.0	9.3		
42.0	49.4	7.4	52.4	8.4	54.2	8.7	55.0	8.7		
44.0	46.8	6.2	49.5	7.0	51.3	7.7	51.8	7.8		
46.0	43.8	5.0	46.5	5.8	48.2	6.3				
48.0	40.7	4.0	43.3	4.6	44.8	5.1				
50.0	37.4	3.0	39.9	3.6	41.1	3.9				
52.0	33.8	2.1	36.2	2.6	36.9	2.8				
危険角度 (°)		32		33		33		48.5		63.5
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SA性能 45mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0	83.4	11.3		
24.0	70.7	12.0	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	69.0	12.0	73.2	12.0	76.7	11.9	79.5	10.7	81.4	9.9
28.0	67.3	12.0	71.5	12.0	74.9	11.2	77.6	10.4	79.3	9.7
30.0	65.5	12.0	69.8	12.0	73.0	10.8	75.6	10.2	77.1	9.6
32.0	63.7	12.0	67.8	11.2	71.1	10.4	73.5	9.9	74.9	9.5
34.0	61.9	11.4	65.9	10.6	69.1	10.1	71.4	9.5	72.5	9.1
36.0	60.0	10.7	63.8	10.2	67.1	9.7	69.1	9.1	70.0	8.9
38.0	58.1	10.1	61.8	9.7	64.9	9.2	66.8	8.6	67.4	8.5
40.0	56.2	9.4	59.7	9.1	62.7	8.6	64.5	8.3	64.7	8.2
42.0	54.1	8.4	57.5	8.5	60.3	8.1	61.9	7.9		
44.0	51.7	7.4	55.1	7.9	57.9	7.6	59.2	7.4		
46.0	49.2	6.3	52.6	7.1	55.3	7.1	56.4	7.0		
48.0	46.5	5.2	50.0	6.2	52.5	6.7	53.3	6.6		
50.0	43.8	4.3	47.2	5.2	49.6	5.8	50.1	6.1		
52.0	40.8	3.4	44.3	4.2	46.4	4.7				
54.0	37.6	2.5	41.1	3.3	42.9	3.7				
56.0	34.2	1.8	37.6	2.4	39.0	2.7				
58.0			33.8	1.6	34.7	1.8				
危険角度 (°)		32		33		33		48.5		63.5
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SA性能 45mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.1	12.0	79.0	12.0	83.4	10.3				
24.0	72.6	12.0	77.4	11.4	81.7	9.8				
26.0	71.1	12.0	75.8	10.7	80.0	9.4	83.5	8.4		
28.0	69.5	11.8	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
30.0	67.9	10.9	72.5	9.6	76.5	8.7	79.8	8.0	82.2	7.2
32.0	66.2	10.2	70.8	9.1	74.8	8.3	77.9	7.8	80.2	7.1
34.0	64.5	9.5	69.0	8.7	72.9	8.0	75.9	7.6	78.1	7.1
36.0	62.8	8.9	67.2	8.3	71.1	7.8	73.9	7.4	75.9	7.0
38.0	61.0	8.3	65.4	7.9	69.2	7.5	71.8	7.3	73.7	7.0
40.0	59.2	7.8	63.5	7.5	67.2	7.3	69.7	7.1	71.2	6.8
42.0	57.3	7.3	61.6	7.2	65.2	7.1	67.6	6.8	68.7	6.7
44.0	55.2	6.9	59.6	6.9	63.0	6.9	65.4	6.5	66.0	6.5
46.0	53.2	6.5	57.5	6.6	60.9	6.6	63.1	6.2		
48.0	51.0	6.2	55.4	6.4	58.6	6.2	60.7	6.1		
50.0	48.8	5.3	53.2	6.1	56.2	5.9	57.9	5.8		
52.0	46.5	4.4	50.8	5.5	53.8	5.5	54.9	5.5		
54.0	43.9	3.6	48.2	4.6	50.8	5.2	51.7	5.2		
56.0	41.2	2.9	45.4	3.8	47.8	4.5				
58.0	38.4	2.1	42.5	3.0	44.5	3.5				
60.0	35.3	1.5	39.3	2.2	40.8	2.7				
62.0			35.8	1.5	36.8	1.8				
危険角度 (°)		33		33		33		48.5		63.5
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42				



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SC性能 45mブーム + 2m + 10.85mSLジブ

オフセット 作業半径 (m)	5'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.4	24.0	76.2	24.0	77.9	22.6	79.6	20.5	80.6	19.4
20.0	72.6	24.0	74.1	23.5	75.9	21.1	77.3	19.3	78.2	18.5
22.0	70.5	22.2	72.0	21.3	73.8	19.7	75.0	18.2	75.8	17.6
24.0	68.4	19.8	69.8	19.5	71.7	18.2	72.7	17.3	73.4	16.8
26.0	66.2	17.8	67.6	17.7	69.4	16.8	70.4	16.2	71.0	16.0
28.0	63.9	16.0	65.3	16.0	67.0	15.5	68.1	15.0	68.4	14.9
30.0	61.4	13.4	62.8	14.2	64.6	14.4	65.6	14.0	65.8	14.0
32.0	59.0	11.2	60.3	11.9	62.0	12.8	63.1	13.1		
34.0	56.3	9.2	57.7	9.9	59.3	10.6	60.3	11.1		
36.0	53.6	7.5	55.0	8.1	56.5	8.7	57.3	9.1		
38.0	50.9	5.9	52.3	6.4	53.6	7.0	54.2	7.3		
40.0	48.0	4.5	49.4	5.0	50.6	5.5	50.9	5.7		
42.0	45.0	3.3	46.4	3.7	47.4	4.1				
44.0					43.8	2.8				
危険角度 (°)	42		43.5		43.5		48		63	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SC性能 45mブーム + 2m + 15mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	12.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.9	12.0	70.0	12.0	72.7	12.0	74.7	12.0	76.0	12.0
28.0	65.0	12.0	68.1	12.0	70.8	12.0	72.6	12.0	73.7	12.0
30.0	63.1	12.0	66.1	12.0	68.7	12.0	70.4	12.0	71.3	12.0
32.0	61.1	12.0	64.1	12.0	66.6	12.0	68.2	12.0	68.7	11.8
34.0	58.9	10.4	62.0	11.8	64.3	11.5	65.8	11.2	66.1	11.1
36.0	56.5	8.7	59.6	10.0	61.9	10.8	63.3	10.5		
38.0	54.0	7.1	57.1	8.3	59.4	9.3	60.7	9.9		
40.0	51.5	5.8	54.6	6.8	56.7	7.7	57.9	8.2		
42.0	49.0	4.5	51.9	5.5	53.9	6.2	54.7	6.6		
44.0	46.2	3.4	49.1	4.3	50.9	4.9	51.5	5.2		
46.0	43.3	2.4	46.1	3.1	47.8	3.7				
48.0					44.4	2.5				
危険角度 (°)	42		44		44		48.5		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SC性能 45mブーム + 2m + 20mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0	83.4	11.3		
24.0	70.7	12.0	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	69.0	12.0	73.2	12.0	76.7	11.9	79.5	10.7	81.4	9.9
28.0	67.3	12.0	71.5	12.0	74.9	11.2	77.6	10.4	79.3	9.7
30.0	65.5	12.0	69.8	12.0	73.0	10.8	75.6	10.2	77.1	9.6
32.0	63.7	12.0	67.8	11.2	71.1	10.4	73.5	9.9	74.9	9.5
34.0	61.9	11.4	65.9	10.6	69.1	10.1	71.4	9.5	72.5	9.1
36.0	59.9	10.0	63.8	10.2	67.1	9.7	69.1	9.1	70.0	8.9
38.0	57.8	8.4	61.8	9.7	64.9	9.2	66.8	8.6	67.4	8.5
40.0	55.7	7.0	59.6	8.5	62.7	8.6	64.5	8.3	64.7	8.2
42.0	53.5	5.8	57.3	7.2	60.3	8.1	61.9	7.9		
44.0	51.1	4.7	54.8	5.9	57.8	6.9	59.2	7.4		
46.0	48.6	3.6	52.3	4.8	55.1	5.6	56.3	6.2		
48.0	46.0	2.7	49.6	3.7	52.2	4.5	53.1	4.9		
50.0	43.3	1.8	46.9	2.7	49.2	3.4	49.8	3.7		
52.0					46.0	2.4				
危険角度 (°)	42		44		44		48.5		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SC性能 45mブーム + 2m + 25mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.1	12.0	79.0	12.0	83.4	10.3				
24.0	72.6	12.0	77.4	11.4	81.7	9.8				
26.0	71.1	12.0	75.8	10.7	80.0	9.4	83.5	8.4		
28.0	69.5	11.8	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
30.0	67.9	10.9	72.5	9.6	76.5	8.7	79.8	8.0	82.2	7.2
32.0	66.2	10.2	70.8	9.1	74.8	8.3	77.9	7.8	80.2	7.1
34.0	64.5	9.5	69.0	8.7	72.9	8.0	75.9	7.6	78.1	7.1
36.0	62.8	8.9	67.2	8.3	71.1	7.8	73.9	7.4	75.9	7.0
38.0	61.0	8.3	65.4	7.9	69.2	7.5	71.8	7.3	73.7	7.0
40.0	59.2	7.8	63.5	7.5	67.2	7.3	69.7	7.1	71.2	6.8
42.0	57.2	6.9	61.6	7.2	65.2	7.1	67.6	6.8	68.7	6.7
44.0	55.0	5.8	59.6	6.9	63.0	6.9	65.4	6.5	66.0	6.5
46.0	52.8	4.7	57.4	6.2	60.9	6.6	63.1	6.2		
48.0	50.5	3.8	55.1	5.1	58.6	6.2	60.7	6.1		
50.0	48.2	2.9	52.7	4.1	56.1	5.1	57.9	5.8		
52.0	45.8	2.1	50.2	3.2	53.4	4.1	54.7	4.6		
54.0	43.2	1.4	47.6	2.4	50.4	3.2	51.4	3.6		
56.0			44.8	1.6	47.3	2.3				
危険角度 (°)	42		44		44.5		48.5		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SC性能 45mブーム + 2m + 30mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SD性能 45mブーム + 2m + 10.85mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.4	24.0	76.2	24.0	77.9	22.6	79.6	20.5	80.6	19.4
20.0	72.6	24.0	74.1	23.5	75.9	21.1	77.3	19.3	78.2	18.5
22.0	70.5	22.2	72.0	21.3	73.8	19.7	75.0	18.2	75.8	17.6
24.0	68.4	19.8	69.8	19.5	71.7	18.2	72.7	17.3	73.4	16.8
26.0	66.0	16.5	67.6	17.6	69.4	16.8	70.4	16.2	71.0	16.0
28.0	63.6	13.8	65.2	14.7	67.0	15.5	68.1	15.0	68.4	14.9
30.0	61.2	11.4	62.6	12.2	64.4	13.2	65.6	13.8	65.8	14.0
32.0	58.8	9.3	60.1	10.0	61.8	10.9	63.0	11.4		
34.0	56.2	7.4	57.5	8.1	59.1	8.8	60.1	9.3		
36.0	53.5	5.8	54.9	6.4	56.4	7.0	57.2	7.4		
38.0	50.7	4.3	52.1	4.8	53.5	5.4	54.1	5.7		
40.0	47.8	3.0	49.2	3.5	50.4	4.0	50.8	4.1		
危険角度 (°)	45		47		48		48		63	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SD性能 45mブーム + 2m + 15mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	12.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.9	12.0	70.0	12.0	72.7	12.0	74.7	12.0	76.0	12.0
28.0	65.0	12.0	68.1	12.0	70.8	12.0	72.6	12.0	73.7	12.0
30.0	63.1	12.0	66.1	12.0	68.7	12.0	70.4	12.0	71.3	12.0
32.0	60.9	10.4	64.1	12.0	66.6	12.0	68.2	12.0	68.7	11.8
34.0	58.6	8.6	61.8	10.0	64.3	11.2	65.8	11.2	66.1	11.1
36.0	56.2	7.0	59.4	8.3	61.8	9.4	63.2	10.1		
38.0	53.8	5.5	56.9	6.7	59.2	7.7	60.5	8.3		
40.0	51.3	4.2	54.4	5.3	56.5	6.1	57.6	6.6		
42.0	48.7	3.1	51.7	4.0	53.7	4.8	54.5	5.1		
44.0	46.0	2.0	48.9	2.9	50.8	3.5	51.4	3.8		
危険角度 (°)	45		47		48		48.5		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SD性能 45mブーム + 2m + 20mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0				
24.0	70.7	12.0	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	69.0	12.0	73.2	12.0	76.7	11.9	79.5	10.7	81.4	9.9
28.0	67.3	12.0	71.5	12.0	74.9	11.2	77.6	10.4	79.3	9.7
30.0	65.5	12.0	69.8	12.0	73.0	10.8	75.6	10.2	77.1	9.6
32.0	63.7	11.7	67.8	11.2	71.1	10.4	73.5	9.9	74.9	9.5
34.0	61.7	9.9	65.9	10.6	69.1	10.1	71.4	9.5	72.5	9.1
36.0	59.7	8.3	63.8	10.0	67.1	9.7	69.1	9.1	70.0	8.9
38.0	57.6	6.8	61.6	8.4	64.9	9.2	66.8	8.6	67.4	8.5
40.0	55.4	5.5	59.3	7.0	62.6	8.2	64.5	8.3	64.7	8.2
42.0	53.2	4.3	57.0	5.7	60.1	6.8	61.8	7.6		
44.0	50.8	3.3	54.6	4.5	57.6	5.5	59.0	6.1		
46.0	48.3	2.3	52.1	3.4	54.9	4.3	56.1	4.8		
48.0			49.5	2.4	52.0	3.2	53.0	3.6		
50.0					49.0	2.2	49.6	2.5		
危険角度 (°)	46		47		48		48.5		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SD性能 45mブーム + 2m + 25mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.1	12.0	79.0	12.0	83.4	10.3				
24.0	72.6	12.0	77.4	11.4	81.7	9.8				
26.0	71.1	12.0	75.8	10.7	80.0	9.4	83.5	8.4		
28.0	69.5	11.8	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
30.0	67.9	10.9	72.5	9.6	76.5	8.7	79.8	8.0	82.2	7.2
32.0	66.2	10.2	70.8	9.1	74.8	8.3	77.9	7.8	80.2	7.1
34.0	64.5	9.5	69.0	8.7	72.9	8.0	75.9	7.6	78.1	7.1
36.0	62.8	8.9	67.2	8.3	71.1	7.8	73.9	7.4	75.9	7.0
38.0	60.9	7.9	65.4	7.9	69.2	7.5	71.8	7.3	73.7	7.0
40.0	59.0	6.6	63.5	7.5	67.2	7.3	69.7	7.1	71.2	6.8
42.0	56.8	5.4	61.6	7.2	65.2	7.1	67.6	6.8	68.7	6.7
44.0	54.7	4.4	59.4	6.0	63.0	6.9	65.4	6.5	66.0	6.5
46.0	52.5	3.4	57.1	4.9	60.8	6.1	63.1	6.2		
48.0	50.2	2.5	54.8	3.8	58.3	5.0	60.6	5.7		
50.0	47.9	1.7	52.4	2.9	55.8	3.9	57.6	4.6		
52.0			49.9	2.1	53.1	3.0	54.5	3.5		
54.0					50.1	2.0	51.2	2.4		
危険角度 (°)	46		47.5		48		48.5		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SD性能 45mブーム + 2m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0	75.4	9.5	81.1	9.5						
24.0	74.1	9.5	79.7	9.5	84.1	8.1				
26.0	72.7	9.5	78.2	9.2	82.6	7.8				
28.0	71.3	9.5	76.7	8.7	81.1	7.5				



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SE性能 45mブーム + 2m + 10.85mSLジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.4	24.0	76.2	24.0	77.9	22.6	79.6	20.5	80.6	19.4
20.0	72.6	23.7	74.1	23.5	75.9	21.1	77.3	19.3	78.2	18.5
22.0	70.3	19.4	71.9	20.7	73.8	19.7	75.0	18.2	75.8	17.6
24.0	68.0	15.9	69.6	17.1	71.7	18.2	72.7	17.3	73.4	16.8
26.0	65.6	13.0	67.3	14.0	69.2	15.3	70.4	16.2	71.0	16.0
28.0	63.3	10.5	64.8	11.4	66.7	12.5	67.9	13.3	68.3	13.6
30.0	60.9	8.3	62.3	9.1	64.2	10.1	65.3	10.8	65.5	11.0
32.0	58.5	6.4	59.8	7.1	61.6	8.0	62.7	8.6		
34.0	55.9	4.7	57.3	5.4	58.9	6.1	59.8	6.6		
36.0	53.2	3.2	54.7	3.8	56.1	4.5	56.9	4.8		
38.0					53.2	3.0	53.9	3.3		
危険角度 (°)	51		52		52		52		63	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SE性能 45mブーム + 2m + 15mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	12.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.9	12.0	70.0	12.0	72.7	12.0	74.7	12.0	76.0	12.0
28.0	65.0	11.6	68.1	12.0	70.8	12.0	72.6	12.0	73.7	12.0
30.0	62.7	9.4	66.0	11.2	68.7	12.0	70.4	12.0	71.3	12.0
32.0	60.5	7.5	63.8	9.1	66.4	10.5	68.1	11.4	68.7	11.8
34.0	58.2	5.9	61.5	7.3	64.0	8.5	65.6	9.4	66.0	9.7
36.0	55.9	4.4	59.1	5.7	61.5	6.8	62.9	7.5		
38.0	53.5	3.1	56.6	4.3	58.9	5.2	60.1	5.8		
40.0			54.0	3.0	56.2	3.8	57.3	4.3		
42.0					53.5	2.6	54.3	2.9		
危険角度 (°)		52		52		52		52		63.5
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SE性能 45mブーム + 2m + 20mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0	83.4	11.3		
24.0	70.7	12.0	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	69.0	12.0	73.2	12.0	76.7	11.9	79.5	10.7	81.4	9.9
28.0	67.3	12.0	71.5	12.0	74.9	11.2	77.6	10.4	79.3	9.7
30.0	65.4	10.7	69.8	12.0	73.0	10.8	75.6	10.2	77.1	9.6
32.0	63.3	8.8	67.8	10.9	71.1	10.4	73.5	9.9	74.9	9.5
34.0	61.3	7.2	65.7	9.1	69.1	10.1	71.4	9.5	72.5	9.1
36.0	59.3	5.7	63.5	7.5	67.0	9.0	69.1	9.1	70.0	8.9
38.0	57.2	4.4	61.2	6.0	64.6	7.4	66.8	8.4	67.4	8.5
40.0	55.0	3.2	59.0	4.7	62.2	5.9	64.3	6.8	64.6	7.2
42.0	52.8	2.2	56.7	3.5	59.8	4.6	61.6	5.4		
44.0			54.3	2.4	57.2	3.4	58.8	4.1		
46.0					54.6	2.3	55.8	2.8		
48.0							52.7	1.7		
危険角度 (°)		52		52		52		52		63.5
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SE性能 45mブーム + 2m + 25mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.6	12.0								
7.0	83.9	12.0								
8.0	83.2	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.2	12.0								
12.0	80.2	12.0	84.9	12.0						
14.0	78.4	12.0	83.4	12.0						
16.0	76.4	12.0	82.0	12.0						
18.0	74.5	12.0	80.5	12.0						
20.0	72.6	12.0	78.4	11.4	81.7	9.8				
22.0	70.7	12.0	76.5	10.7	80.0	9.4	83.5	8.4		
24.0	68.8	11.8	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
26.0	66.9	10.9	72.5	9.6	76.5	8.7	79.8	8.0	82.2	7.2
28.0	65.0	10.0	70.8	9.1	74.8	8.3	77.9	7.8	80.2	7.1
30.0	63.3	8.3	69.0	8.7	72.9	8.0	75.9	7.6	78.1	7.1
32.0	61.3	6.8	67.2	8.3	71.1	7.8	73.9	7.4	75.9	7.0
34.0	60.4	5.5	65.4	7.5	69.2	7.5	71.8	7.3	73.7	7.0
36.0	58.4	4.3	63.3	6.2	67.2	7.3	69.7	7.1	71.2	6.8
38.0	56.4	3.3	61.1	5.0	65.0	6.5	67.6	6.8	68.7	6.7
40.0	54.2	2.3	58.9	3.9	62.7	5.2	65.3	6.2	66.0	6.5
42.0			56.7	2.9	60.4	4.1	62.8	5.0		
44.0			54.3	1.9	57.9	3.1	60.1	3.8		
46.0					55.4	2.1	57.1	2.7		
48.0							54.1	1.7		
50.0										
52.0										
危険角度 (°)		52.5		53		53		53		63.5
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SE性能 45mブーム + 2m + 30mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0	75.4	9.5	81.1	9.5						
24.0	74.1	9.5	79.7	9.5	84.1	8.1				
26.0	72.7	9.5	78.2	9.2	82.6	7.8				
28.0	71.3	9.5	76.7	8.7	81.1	7.5				
30.0	69.9	9.5	75.1	8.2	79.6	7.2	83.7	6.1		
32.0	68.4	8.8	73.5	7.7	78.1	7.0	82.0	5.9		
34.0	66.8	8.2	71.9	7.4	76.5	6.7	80.2	5.8	83.2	5.2
36.0	65.1	7.6	70.3	7.0	74.9	6.4	78.4	5.7	81.1	5.1
38.0	63.3	6.5	68.7	6.7	73.2	6.2	76.6	5.5		



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SF性能 45mブーム + 2m + 10.85mSLジブ

オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.4	24.0	76.2	24.0	77.9	22.6	79.6	20.5	80.6	19.4
20.0	72.4	20.8	74.0	22.3	75.9	21.1	77.3	19.3	78.2	18.5
22.0	70.0	16.9	71.7	18.2	73.8	19.7	75.0	18.2	75.8	17.6
24.0	67.7	13.6	69.4	14.7	71.5	16.2	72.7	17.3	73.4	16.8
26.0	65.4	10.8	67.1	11.8	69.0	13.1	70.3	14.1	70.8	14.5
28.0	63.1	8.5	64.6	9.4	66.5	10.5	67.8	11.3	68.2	11.6
30.0	60.7	6.4	62.2	7.2	64.0	8.2	65.1	8.9	65.4	9.1
32.0	58.3	4.6	59.7	5.4	61.4	6.2	62.5	6.8		
34.0	55.7	3.1	57.1	3.7	58.7	4.5	59.7	4.9		
36.0					56.0	2.9	56.8	3.3		
危険角度 (°)	54		55		55		55		63	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SF性能 45mブーム + 2m + 15mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	12.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.9	11.9	70.0	12.0	72.7	12.0	74.7	12.0	76.0	12.0
28.0	64.7	9.6	68.0	11.5	70.8	12.0	72.6	12.0	73.7	12.0
30.0	62.5	7.6	65.9	9.3	68.6	10.8	70.4	11.9	71.3	12.0
32.0	60.3	5.8	63.6	7.4	66.2	8.7	67.9	9.7	68.6	10.2
34.0	58.0	4.2	61.3	5.7	63.8	6.9	65.4	7.7	65.8	8.1
36.0	55.6	2.9	58.9	4.2	61.3	5.3	62.7	6.0		
38.0			56.4	2.8	58.7	3.8	59.9	4.4		
40.0					56.1	2.5	57.1	2.9		
危険角度 (°)	54		55		55		55		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SF性能 45mブーム + 2m + 20mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0				
24.0	70.7	12.0	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	69.0	12.0	73.2	12.0	76.7	11.9	79.5	10.7	81.4	9.9
28.0	67.1	10.9	71.5	12.0	74.9	11.2	77.6	10.4	79.3	9.7
30.0	65.2	8.9	69.7	11.2	73.0	10.8	75.6	10.2	77.1	9.6
32.0	63.1	7.1	67.6	9.2	71.1	10.4	73.5	9.9	74.9	9.5
34.0	61.1	5.5	65.5	7.5	69.0	9.1	71.4	9.5	72.5	9.1
36.0	59.1	4.2	63.3	5.9	66.8	7.5	69.1	8.6	70.0	8.9
38.0	56.9	2.9	61.0	4.6	64.4	5.9	66.6	6.9	67.3	7.4
40.0	54.7	1.8	58.8	3.3	62.0	4.6	64.1	5.4	64.4	5.8
42.0			56.5	2.2	59.6	3.3	61.4	4.1		
44.0					57.1	2.2	58.6	2.8		
46.0							55.7	1.6		
危険角度 (°)	54		55		55		55		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SF性能 45mブーム + 2m + 25mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.1	12.0	79.0	12.0	83.4	10.3				
24.0	72.6	12.0	77.4	11.4	81.7	9.8				
26.0	71.1	12.0	75.8	10.7	80.0	9.4	83.5	8.4		
28.0	69.5	11.8	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
30.0	67.7	10.0	72.5	9.6	76.5	8.7	79.8	8.0	82.2	7.2
32.0	65.8	8.2	70.8	9.1	74.8	8.3	77.9	7.8	80.2	7.1
34.0	64.0	6.7	69.0	8.7	72.9	8.0	75.9	7.6	78.1	7.1
36.0	62.1	5.3	67.1	7.4	71.1	7.8	73.9	7.4	75.9	7.0
38.0	60.1	4.0	65.0	6.0	69.2	7.5	71.8	7.3	73.7	7.0
40.0	58.1	2.9	63.0	4.8	67.0	6.4	69.7	7.1	71.2	6.8
42.0	56.1	1.9	60.8	3.6	64.7	5.1	67.5	6.3	68.7	6.7
44.0			58.6	2.6	62.5	4.0	65.1	5.0	65.9	5.5
46.0					56.4	1.7	60.1	2.9	62.5	3.8
48.0							57.7	1.9	59.8	2.7
50.0									56.9	1.6
危険角度 (°)	55		55		56		56		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SF性能 45mブーム + 2m + 30mSLジブ

オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0	75.4	9.5	81.1	9.5						
24.0	74.1	9.5	79.7	9.5	84.1	8.1				
26.0	72.7	9.5	78.2	9.2	82.6	7.8				
28.0	71.3	9.5	76.7	8.7	81.1	7.5				
30.0	69.9	9.5	75.1	8.2	79.6	7.2	83.7	6.1		
32.0	68.4	8.8	73.5	7.7	78.1	7.0	82.0	5.9		
34.0	66.6	7.6	71.9	7.4	76.5	6.7	80.2	5.8	83.2	5.2
36.0	64.8	6.2	70.3	7.0	74.9	6.4	78.4	5.7	81.1	5.1
38.0	62.9	5.0	68.7	6.7	73.2	6.2	76.6	5.5	79.0	5.0
40.0	61.0	3.9	66.9	6.1	71.5	6.0	74.7	5.4	76.9	5.0
42.0	59.1	2.9	64.9	4.9	69.7	5.8	72.7	5.3	74.7	5.0
44.0	57.2	2.0	62.9	3.9	67.8	5.6	70.7	5.2	72.3	5.0
46.0			60.8	2.9	65.6	4.5	68.6	5.2	69.9	5.0
48.0			58.8	2.0	63.3	3.5	66.3	4.6	67.3	5.0
50.0					60.9	2.5	63.7	3.5	64.5	4.0
52.0					58.6	1.7	61.0	2.5		
54.0							58.3	1.6		
危険角度 (°)	56</									



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SG性能 45mブーム + 2m + 10.85mSLジブ

オフセット 作業半径 (m)	5'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.3	22.6	76.2	24.0	77.9	22.6	79.6	20.5	80.6	19.4
20.0	72.1	18.0	73.8	19.5	75.9	21.1	77.3	19.3	78.2	18.5
22.0	69.8	14.3	71.5	15.6	73.6	17.3	75.0	18.2	75.8	17.6
24.0	67.5	11.3	69.2	12.4	71.3	13.8	72.6	14.9	73.3	15.5
26.0	65.2	8.7	66.9	9.7	68.8	11.0	70.1	11.9	70.7	12.4
28.0	62.9	6.5	64.4	7.4	66.3	8.5	67.6	9.3	68.0	9.6
30.0	60.5	4.5	62.0	5.4	63.8	6.4	65.0	7.0	65.2	7.3
32.0	58.1	2.9	59.5	3.6	61.2	4.5	62.3	5.1		
34.0					58.6	2.8	59.5	3.3		
危険角度 (°)	56		58		58		58		63	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SG性能 45mブーム + 2m + 15mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	12.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.7	9.8	70.0	11.9	72.7	12.0	74.7	12.0	76.0	12.0
28.0	64.5	7.6	67.9	9.5	70.7	11.2	72.6	12.0	73.7	12.0
30.0	62.3	5.7	65.7	7.4	68.4	8.9	70.2	10.1	71.2	10.7
32.0	60.0	4.1	63.4	5.6	66.1	7.0	67.7	7.9	68.4	8.4
34.0	57.7	2.6	61.1	4.0	63.6	5.2	65.2	6.1	65.7	6.4
36.0			58.7	2.6	61.1	3.7	62.5	4.4		
38.0					58.6	2.3	59.7	2.9		
危険角度 (°)	56		58		58		58		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SG性能 45mブーム + 2m + 20mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0	83.4	11.3		
24.0	70.7	12.0	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	68.9	11.1	73.2	12.0	76.7	11.9	79.5	10.7	81.4	9.9
28.0	66.9	8.9	71.5	11.4	74.9	11.2	77.6	10.4	79.3	9.7
30.0	64.9	7.0	69.5	9.3	73.0	10.8	75.6	10.2	77.1	9.6
32.0	62.9	5.4	67.4	7.5	71.0	9.3	73.5	9.9	74.9	9.5
34.0	60.9	3.9	65.3	5.8	68.8	7.5	71.3	8.8	72.5	9.1
36.0	58.8	2.6	63.1	4.4	66.5	5.9	68.9	7.1	69.9	7.7
38.0			60.8	3.1	64.2	4.5	66.4	5.5	67.1	6.0
40.0			58.6	1.9	61.8	3.2	63.9	4.0	64.2	4.4
42.0					59.4	2.0	61.2	2.7		
44.0							58.4	1.5		
危険角度 (°)	57		58		58		58		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SG性能 45mブーム + 2m + 25mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.1	12.0	79.0	12.0	83.4	10.3				
24.0	72.6	12.0	77.4	11.4	81.7	9.8				
26.0	71.1	12.0	75.8	10.7	80.0	9.4	83.5	8.4		
28.0	69.2	10.0	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
30.0	67.4	8.1	72.5	9.6	76.5	8.7	79.8	8.0	82.2	7.2
32.0	65.5	6.5	70.7	9.0	74.8	8.3	77.9	7.8	80.2	7.1
34.0	63.6	5.0	68.8	7.4	72.9	8.0	75.9	7.6	78.1	7.1
36.0	61.7	3.7	66.8	5.9	71.1	7.8	73.9	7.4	75.9	7.0
38.0	59.8	2.6	64.7	4.6	69.0	6.4	71.8	7.3	73.7	7.0
40.0	57.8	1.5	62.6	3.4	66.7	5.0	69.6	6.3	71.2	6.8
42.0			60.5	2.3	64.5	3.8	67.3	5.0	68.5	5.6
44.0			58.3	1.3	62.2	2.7	64.8	3.7	65.7	4.2
46.0					59.9	1.7	62.3	2.6		
48.0							59.5	1.5		
危険角度 (°)	57		58		58		58		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SG性能 45mブーム + 2m + 30mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0	75.4	9.5	81.1	9.5						
24.0	74.1	9.5	79.7	9.5	84.1	8.1				
26.0	72.7	9.5	78.2	9.2	82.6	7.8				
28.0	71.3	9.5	76.7	8.7	81.1	7.5				
30.0	69.8	9.1	75.1	8.2	79.6	7.2	83.7	6.1		
32.0	68.0	7.4	73.5	7.7	78.1	7.0	82.0	5.9		
34.0	66.2	6.0	71.9	7.4	76.5	6.7	80.2	5.8	83.2	5.2
36.0	64.4	4.7	70.3	7.0	74.9	6.4	78.4	5.7	81.1	5.1
38.0	62.5	3.5	68.4	5.9	73.2	6.2	76.6	5.5	79.0	5.0
40.0	60.7	2.5	66.5	4.7	71.5	6.0	74.7	5.4	76.9	5.0
42.0			64.5	3.6	69.5	5.4	72.7	5.3	74.7	5.0
44.0			62.5	2.6	67.4	4.3	70.7	5.2	72.3	5.0
46.0					65.2	3.3	68.4	4.5	69.9	5.0
48.0					62.9	2.3	66.0	3.4	67.2	4.0
50.0							63.4	2.4	64.3	2.9
危険角度 (°)	59		61		61		61		63.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1			



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SH性能 45mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.2	24.0	78.0	24.0	80.0	24.0	81.8	21.9	83.0	20.4
18.0	74.1	19.4	76.0	21.1	77.9	22.6	79.6	20.5	80.6	19.4
20.0	71.9	15.2	73.6	16.6	75.7	18.5	77.3	19.3	78.2	18.5
22.0	69.6	11.8	71.3	13.0	73.4	14.7	74.9	16.0	75.8	16.6
24.0	67.3	8.9	69.0	10.0	71.1	11.5	72.4	12.6	73.1	13.2
26.0	64.9	6.5	66.6	7.5	68.6	8.8	69.9	9.7	70.5	10.2
28.0			64.2	5.4	66.1	6.5	67.4	7.3	67.8	7.6
30.0					64.8	5.2	64.8	5.2	65.0	5.4
危険角度 (°)	63		63		64		64		64	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SH性能 45mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.6	12.0	73.7	12.0	76.6	12.0	78.8	12.0	80.4	12.0
24.0	68.8	10.0	71.9	12.0	74.7	12.0	76.8	12.0	78.2	12.0
26.0	66.4	7.6	69.8	9.7	72.7	11.5	74.7	12.0	76.0	12.0
28.0	64.2	5.6	67.7	7.5	70.5	9.2	72.4	10.3	73.6	10.9
30.0			65.5	5.6	68.2	7.1	70.1	8.2	71.0	8.7
32.0					65.8	5.2	67.6	6.2	68.3	6.7
34.0							65.0	4.4	65.6	4.7
危険角度 (°)	63		64		64		64		64	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 45mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.3	12.0	76.6	12.0	80.3	12.0	83.4	11.3		
24.0	70.6	11.3	74.9	12.0	78.6	12.0	81.5	10.9	83.5	10.0
26.0	68.7	8.9	73.2	11.6	76.7	11.9	79.5	10.7	81.4	9.9
28.0	66.7	6.9	71.3	9.4	74.9	11.2	77.6	10.4	79.3	9.7
30.0	64.7	5.1	69.3	7.4	72.8	9.3	75.6	10.2	77.1	9.6
32.0			67.2	5.7	70.7	7.6	73.4	8.7	74.9	9.4
34.0			65.0	4.1	68.5	5.9	71.1	7.1	72.3	7.7
36.0					66.3	4.3	68.7	5.5	69.7	6.1
38.0							66.2	3.9	66.9	4.4
危険角度 (°)	63		64		64		64		64.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 45mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.1	12.0	79.0	12.0	83.4	10.3				
24.0	72.6	12.0	77.4	11.4	81.7	9.8				
26.0	70.8	10.1	75.8	10.7	80.0	9.4	83.5	8.4		
28.0	68.9	8.0	74.1	10.1	78.3	9.0	81.7	8.2	84.2	7.2
30.0	67.1	6.3	72.3	8.9	76.5	8.7	79.8	8.0	82.2	7.2
32.0	65.2	4.7	70.4	7.3	74.8	8.3	77.9	7.8	80.2	7.1
34.0			68.5	5.7	72.9	7.6	75.9	7.6	78.1	7.1
36.0			66.5	4.3	70.8	6.3	73.9	7.4	75.9	7.0
38.0					68.7	4.9	71.7	6.2	73.7	6.9
40.0					66.4	3.4	69.4	4.9	71.1	5.6
42.0							67.0	3.4	68.3	4.1
危険角度 (°)	64		65		65		65		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 45mブーム + 2m + 30mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0	75.4	9.5	81.1	9.5						
24.0	74.1	9.5	79.7	9.5	84.1	8.1				
26.0	72.7	9.5	78.2	9.2	82.6	7.8				
28.0	71.2	9.0	76.7	8.7	81.1	7.5				
30.0	69.5	7.2	75.1	8.2	79.6	7.2	83.7	6.1		
32.0	67.7	5.7	73.5	7.7	78.1	7.0	82.0	5.9		
34.0			71.8	7.0	76.5	6.7	80.2	5.8	83.2	5.2
36.0			70.0	5.7	74.9	6.4	78.4	5.7	81.1	5.1
38.0			68.0	4.3	73.2	6.2	76.6	5.5	79.0	5.0
40.0					71.3	5.3	74.7	5.4	76.9	5.0
42.0					69.1	4.0	72.7	5.3	74.7	5.0
44.0							70.5	4.3	72.3	5.0
46.0							68.1	3.1	69.7	3.9
危険角度 (°)	66		67		67.5		67.5		67.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 45mブーム + 2m + 35mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.9	8.0								
9.0	84.3	8.0								
10.0	83.7	8.0								
11.0	83.1	8.0								
12.0	82.5	8.0								
14.0	81.4	8.0								
16.0	80.2	8.0								
18.0	79.0	8.0								
20.0	77.7	7.5	83.7	4.9						
22.0	76.4	6.8	82.3	4.6						
24.0	75.0	6.3	80.9	4.3						
26.0	73.7	5.8	79.5	4.1						
28.0	72.3	5.4	78.1	3.9						



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SJ性能 45mブーム + 2m + 10.85mSLジブ

オフセット 作業半径 (m)	5°		15°		30°		45°		60°	
	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	78.0	24.0	79.7	24.0	81.9	24.0	83.9	22.6		
16.0	76.0	21.0	77.9	22.9	80.0	24.0	81.8	21.9	83.0	20.4
18.0	73.9	15.8	75.7	17.2	77.7	19.2	79.6	20.5	80.6	19.4
20.0	71.6	11.7	73.3	13.0	75.5	14.7	77.1	15.9	78.1	16.7
22.0	69.3	8.4	71.0	9.8	73.2	11.2	74.6	12.3	75.5	12.9
24.0					70.8	8.5	72.2	9.4	72.9	9.8
危険角度 (°)	68		69		69		70		71	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SJ性能 45mブーム + 2m + 15mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.1	12.0	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0	72.4	12.0	75.6	12.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0	70.3	9.4	73.7	11.8	76.6	12.0	78.8	12.0	80.4	12.0
24.0			71.7	9.2	74.6	10.9	76.8	12.0	78.2	12.0
26.0			69.6	6.8	72.4	8.5	74.5	9.6	75.8	10.4
28.0					70.2	6.3	72.2	7.5	73.3	8.1
危険角度 (°)		69		69		69		70		71
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SJ性能 45mブーム + 2m + 20mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	12.0	79.9	12.0	83.7	12.0				
20.0	74.0	12.0	78.3	12.0	82.0	12.0				
22.0	72.2	10.6	76.6	12.0	80.3	12.0	83.4	11.3		
24.0	70.3	8.0	74.8	10.8	78.6	12.0	81.5	10.9	83.5	10.0
26.0			72.9	8.5	76.6	10.5	79.5	10.7	81.4	9.9
28.0			71.0	6.6	74.6	8.5	77.5	9.9	79.3	9.7
30.0					72.5	6.7	75.3	8.0	77.0	8.9
32.0					70.4	4.8	73.1	6.3	74.6	7.1
34.0							70.8	4.6	72.1	5.4
危険角度 (°)	69		69.5		69.5		70		71	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SJ性能 45mブーム + 2m + 25mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.5	12.0	80.5	12.0						
22.0	74.0	11.5	79.0	12.0	83.4	10.3				
24.0	72.2	9.0	77.4	11.4	81.7	9.8				
26.0	70.4	6.9	75.7	9.9	80.0	9.4	83.5	8.4		
28.0			73.8	8.0	78.3	9.0	81.7	8.2	84.2	7.2
30.0			71.9	6.3	76.5	8.4	79.8	8.0	82.2	7.2
32.0					74.5	6.8	77.9	7.8	80.2	7.1
34.0					72.5	5.3	75.8	6.8	78.1	7.1
36.0							73.6	5.4	75.8	6.3
38.0							71.4	3.9	73.4	4.9
危険角度 (°)	69		70.5		70.5		70.5		71	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SJ性能 45mブーム + 2m + 30mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0	75.4	9.5	81.1	9.5						
24.0	74.1	9.5	79.7	9.5	84.1	8.1				
26.0	72.4	7.7	78.2	9.2	82.6	7.8				
28.0			76.7	8.7	81.1	7.5				
30.0			75.0	7.5	79.6	7.2	83.7	6.1		
32.0			73.2	6.0	78.1	7.0	82.0	5.9		
34.0					76.5	6.7	80.2	5.8	83.2	5.2
36.0					74.7	5.5	78.4	5.7	81.1	5.1
38.0							76.6	5.5	79.0	5.0
40.0							74.5	4.7	76.9	5.0
42.0									74.6	4.5
危険角度 (°)	71		72		73		73		73	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SJ性能 45mブーム + 2m + 35mSLジブ

オフセット 作業半径 (m)	0°		15°		30°		45°		60°	
	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.9	8.0								
9.0	84.3	8.0								
10.0	83.7	8.0								
11.0	83.1	8.0								
12.0	82.5	8.0								
14.0	81.4	8.0								
16.0	80.2	8.0								
18.0	79.0	8.0								
20.0	77.7	7.5	83.7	4.9						
22.0	76.4	6.8	82.3	4.6						
24.0	75.0	6.3	80.9	4.3						
26.0	73.7	5.8	79.5	4.1						
28.0	72.3	5.4	78.1	3.9	83.5	2.8				
30.0			76.7	3.7	81.9	2.7				
32.0			75.2	3.5	80.3	2.6				
34.0			73.8	3.3	78.8	2.4	83.4	1.9		
36.0					77.3	2.3	81.7	1.8		
38.0					75.7	2.2	80.0	1.8	83.3	1.5
40.0					74.2	2.1	78.2	1.7	81.5	1.5
42.0							76.5	1.7	79.4	1.4
44.0							74.7	1.6	77.4	1.4
46.0									75.2	1.4
危険角度 (°)	71		72.5		73		73		73.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	



10.85m — 35m

スーパーラフィングジブ【45mブーム時】

SK性能 45mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.9	24.0								
7.0	84.0	24.0								
8.0	83.2	24.0								
9.0	82.3	24.0	84.2	24.0						
10.0	81.5	24.0	83.3	24.0						
11.0	80.6	24.0	82.4	24.0	84.9	24.0				
12.0	79.7	24.0	81.5	24.0	83.9	24.0				
14.0	77.7	19.3	79.6	21.7	81.9	24.0				
16.0	75.6	13.6	77.5	15.7	79.6	17.9	81.6	19.6	83.0	20.4
18.0			75.3	11.0	77.4	13.0	79.1	14.5	80.3	15.4
20.0					75.2	9.5	76.7	10.7	77.7	11.4
危険角度 (°)	73.5		74		74		75		76	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SK性能 45mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.3	12.0								
7.0	83.5	12.0								
8.0	82.6	12.0								
9.0	81.8	12.0								
10.0	81.0	12.0	84.3	12.0						
11.0	80.1	12.0	83.5	12.0						
12.0	79.3	12.0	82.6	12.0						
14.0	77.6	12.0	80.9	12.0	84.0	12.0				
16.0	75.9	12.0	79.1	12.0	82.2	12.0	84.7	12.0		
18.0	74.0	10.1	77.4	12.0	80.4	12.0	82.8	12.0	84.6	12.0
20.0			75.4	10.0	78.5	12.0	80.8	12.0	82.5	12.0
22.0					76.4	9.1	78.7	10.6	80.4	11.7
24.0							76.5	8.1	77.9	8.9
危険角度 (°)	73.5		74		75		75		76	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SK性能 45mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.0	12.0								
8.0	83.3	12.0								
9.0	82.5	12.0								
10.0	81.8	12.0								
11.0	81.0	12.0								
12.0	80.2	12.0	84.5	12.0						
14.0	78.7	12.0	83.0	12.0						
16.0	77.2	12.0	81.4	12.0						
18.0	75.6	11.3	79.9	12.0	83.7	12.0				
20.0			78.2	11.7	82.0	12.0				
22.0			76.4	8.9	80.2	11.3	83.4	11.3		
24.0					78.2	8.8	81.4	10.7	83.5	10.0
26.0					76.2	6.8	79.3	8.4	81.4	9.5
28.0							77.2	6.5	79.1	7.5
30.0									76.7	5.7
危険角度 (°)	74		75		75		75.5		76	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SK性能 45mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	83.9	12.0								
9.0	83.2	12.0								
10.0	82.5	12.0								
11.0	81.8	12.0								
12.0	81.2	12.0								
14.0	79.8	12.0	84.9	12.0						
16.0	78.4	12.0	83.4	12.0						
18.0	77.0	12.0	82.0	12.0						
20.0	75.2	9.0	80.5	12.0						
22.0			78.8	10.3	83.4	10.3				
24.0			77.0	8.1	81.7	9.8				
26.0					79.9	8.5	83.5	8.4		
28.0					77.9	6.7	81.7	8.2	84.2	7.2
30.0							79.6	6.9	82.2	7.2
32.0							77.6	5.4	80.1	6.4
34.0									77.8	5.0
危険角度 (°)	74		75.5		76.5		76.5		77	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SK性能 45mブーム + 2m + 30mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	9.5								
9.0	83.8	9.5								
10.0	83.2	9.5								
11.0	82.5	9.5								
12.0	81.9	9.5								
14.0	80.7	9.5								
16.0	79.4	9.5								
18.0	78.1	9.5	83.8	9.5						
20.0	76.8	9.5	82.4	9.5						
22.0			81.1	9.5						
24.0			79.7	9.2	84.1	8.1				
26.0			77.9	7.3	82.6	7.8				
28.0					81.1	7.5				
30.0					79.5	6.6	83.7	6.1		
32.0					77.7	5.3	82.0	5.9		
34.0							80.2	5.7	83.2	5.2
36.0									81.1	5.1
危険角度 (°)	75.5		76.5		76.5		78.5		79	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SK性能 45mブーム + 2m + 35mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.9	8.0								
9.0	84.3	8.0								
10.0	83.7	8.0								
11.0	83.1	8.0								
12.0	82.5	8.0								
14.0	81.4	8.0								
16.0	80.2	8.0								
18.0	79.0	8.0								
20.0	77.7	7.5	83.7	4.9						
22.0			82.3	4.6						
24.0			80.9	4.3						
26.0			79.5	4.1						
28.0			78.1	3.9						
30.0					83.5	2.8				
32.0					81.9	2.7				
34.0					80.3	2.6				
36.0					78.8	2.4	83.4	1.9		
38.0							81.7	1.8		
40.0							80.0	1.8	83.3	1.5
									81.5	1.5
危険角度 (°)	76.5		77		77.5		78.5		79.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	