

HA性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.7 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 5.3 | 5.1 | 4.9 | 4.7 | |
| 70.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HA性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.4 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 7.2 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 6.6 | 6.2 | 5.9 | 5.5 | 5.1 |
| 60.0 | 6.1 | 5.8 | 5.6 | 5.2 | 4.8 |
| 65.0 | 5.7 | 5.5 | 5.2 | 4.8 | |
| 70.0 | 5.2 | 5.0 | 4.8 | | |
| 75.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HA性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.3 | 7.6 | 7.1 | | |
| 46.0 | 8.0 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 7.7 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 7.4 | 6.9 | 6.5 | 5.9 | |
| 55.0 | 6.8 | 6.4 | 6.0 | 5.6 | 5.1 |
| 60.0 | 6.3 | 6.0 | 5.7 | 5.3 | 4.8 |
| 65.0 | 5.9 | 5.6 | 5.4 | 4.9 | 4.7 |
| 70.0 | 5.5 | 5.3 | 5.0 | 4.7 | |
| 75.0 | 4.8 | 4.9 | 4.7 | | |
| 危険角度 (°) | 15 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HA性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.6 | 8.3 | 7.5 | | |
| 44.0 | 8.6 | 8.0 | 7.3 | | |
| 46.0 | 8.6 | 7.7 | 7.1 | | |
| 48.0 | 8.3 | 7.5 | 6.9 | 6.1 | |
| 50.0 | 8.0 | 7.3 | 6.7 | 6.0 | |
| 55.0 | 7.4 | 6.8 | 6.3 | 5.7 | 5.2 |
| 60.0 | 6.8 | 6.3 | 5.9 | 5.5 | 4.9 |
| 65.0 | 6.4 | 6.0 | 5.6 | 5.2 | 4.7 |
| 70.0 | 5.2 | 5.7 | 5.4 | 4.9 | 4.6 |
| 75.0 | 3.9 | 4.5 | 5.0 | 4.7 | |
| 80.0 | 2.8 | 3.2 | 3.6 | | |
| 85.0 | 1.8 | 2.0 | | | |
| 危険角度 (°) | 18 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HA性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 55.0 | 6.0 | 6.0 | 6.0 | 5.8 | 4.9 |
| 60.0 | 6.0 | 6.0 | 6.0 | 5.6 | 4.8 |
| 65.0 | 5.9 | 6.0 | 5.8 | 5.4 | 4.7 |
| 70.0 | 4.4 | 5.4 | 5.6 | 5.1 | 4.7 |
| 75.0 | 3.2 | 4.0 | 4.7 | 4.8 | |
| 80.0 | 2.1 | 2.7 | 3.3 | 3.9 | |
| 85.0 | | 1.6 | 2.0 | | |
| 危険角度 (°) | 35 | 36 | 37 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HA性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | 5.5 | |
| 55.0 | 5.5 | 5.5 | 5.5 | 5.3 | |
| 60.0 | 5.5 | 5.5 | 5.5 | 5.1 | 3.8 |
| 65.0 | 5.5 | 5.5 | 5.5 | 5.0 | 3.8 |
| 70.0 | 4.0 | 5.0 | 5.5 | 4.9 | 3.8 |
| 75.0 | 2.8 | 3.6 | 4.4 | 4.9 | 3.8 |
| 80.0 | 1.7 | 2.4 | 3.1 | 3.8 | |
| 85.0 | | | 1.8 | 2.3 | |
| 危険角度 (°) | 40 | 44 | 44 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HA性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 4.1 | 3.9 | 3.3 | 2.3 | |
| 55.0 | 4.1 | 3.7 | 3.1 | 2.2 | |
| 60.0 | 4.0 | 3.5 | 2.9 | 2.1 | |
| 65.0 | 3.8 | 3.3 | 2.8 | 2.0 | |
| 70.0 | 3.2 | 3.2 | 2.7 | 2.0 | |
| 75.0 | 2.4 | 3.0 | 2.7 | 2.0 | |
| 80.0 | | 2.1 | 2.6 | 2.0 | |
| 85.0 | | | 1.6 | 2.0 | |
| 危険角度 (°) | 47 | 47 | 48 | 50 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HA性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | 2.9 | 2.4 | 1.8 | | |
| 55.0 | 2.7 | 2.2 | 1.7 | | |
| 60.0 | 2.5 | 2.0 | 1.6 | | |
| 65.0 | 2.3 | 1.9 | | | |
| 70.0 | 2.0 | 1.9 | | | |
| 75.0 | | 1.8 | | | |
| 危険角度 (°) | 53 | 54 | 67 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |

HB性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.7 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 5.3 | 5.1 | 4.9 | 4.7 | |
| 70.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HB性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.4 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 7.2 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 6.6 | 6.2 | 5.9 | 5.5 | 5.1 |
| 60.0 | 6.1 | 5.8 | 5.6 | 5.2 | 4.8 |
| 65.0 | 5.7 | 5.5 | 5.2 | 4.8 | |
| 70.0 | 5.2 | 5.0 | 4.8 | | |
| 75.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HB性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.3 | 7.6 | 7.1 | | |
| 46.0 | 8.0 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 7.7 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 7.4 | 6.9 | 6.5 | 5.9 | |
| 55.0 | 6.8 | 6.4 | 6.0 | 5.6 | 5.1 |
| 60.0 | 6.3 | 6.0 | 5.7 | 5.3 | 4.8 |
| 65.0 | 5.9 | 5.6 | 5.4 | 4.9 | 4.7 |
| 70.0 | 5.2 | 5.3 | 5.0 | 4.7 | |
| 75.0 | 4.0 | 4.3 | 4.6 | | |
| 危険角度 (°) | 15 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HB性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.6 | 8.3 | 7.5 | | |
| 44.0 | 8.6 | 8.0 | 7.3 | | |
| 46.0 | 8.6 | 7.7 | 7.1 | | |
| 48.0 | 8.3 | 7.5 | 6.9 | 6.1 | |
| 50.0 | 8.0 | 7.3 | 6.7 | 6.0 | |
| 55.0 | 7.4 | 6.8 | 6.3 | 5.7 | 5.2 |
| 60.0 | 6.8 | 6.3 | 5.9 | 5.5 | 4.9 |
| 65.0 | 5.7 | 6.0 | 5.6 | 5.2 | 4.7 |
| 70.0 | 4.3 | 5.1 | 5.4 | 4.9 | 4.6 |
| 75.0 | 3.1 | 3.7 | 4.3 | 4.7 | |
| 80.0 | 2.0 | 2.5 | 2.9 | | |
| 危険角度 (°) | 23 | 27 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HB性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 55.0 | 6.0 | 6.0 | 6.0 | 5.8 | 4.9 |
| 60.0 | 6.0 | 6.0 | 6.0 | 5.6 | 4.8 |
| 65.0 | 4.9 | 6.0 | 5.8 | 5.4 | 4.7 |
| 70.0 | 3.6 | 4.5 | 5.3 | 5.1 | 4.7 |
| 75.0 | 2.4 | 3.2 | 3.9 | 4.7 | |
| 80.0 | | 2.0 | 2.5 | 3.1 | |
| 危険角度 (°) | 41 | 42 | 43 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HB性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | 5.5 | |
| 55.0 | 5.5 | 5.5 | 5.5 | 5.3 | |
| 60.0 | 5.5 | 5.5 | 5.5 | 5.1 | 3.8 |
| 65.0 | 4.5 | 5.5 | 5.5 | 5.0 | 3.8 |
| 70.0 | 3.2 | 4.2 | 5.1 | 4.9 | 3.8 |
| 75.0 | 2.0 | 2.8 | 3.6 | 4.6 | 3.8 |
| 80.0 | | 1.7 | 2.3 | 3.0 | |
| 85.0 | | | | 1.6 | |
| 危険角度 (°) | 44 | 46 | 47 | 47 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HB性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 4.1 | 3.9 | 3.3 | 2.3 | |
| 55.0 | 4.1 | 3.7 | 3.1 | 2.2 | |
| 60.0 | 4.0 | 3.5 | 2.9 | 2.1 | |
| 65.0 | 3.8 | 3.3 | 2.8 | 2.0 | |
| 70.0 | 2.8 | 3.2 | 2.7 | 2.0 | |
| 75.0 | 1.6 | 2.5 | 2.7 | 2.0 | |
| 80.0 | | | 2.1 | 2.0 | |
| 危険角度 (°) | 49 | 52 | 52 | 54 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HB性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | 2.9 | 2.4 | 1.8 | | |
| 55.0 | 2.7 | 2.2 | 1.7 | | |
| 60.0 | 2.5 | 2.0 | 1.6 | | |
| 65.0 | 2.3 | 1.9 | | | |
| 70.0 | 2.0 | 1.9 | | | |
| 75.0 | | 1.8 | | | |
| 危険角度 (°) | 53 | 54 | 67 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |

HC性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.7 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 5.3 | 5.1 | 4.9 | 4.7 | |
| 70.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HC性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.4 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 7.2 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 6.6 | 6.2 | 5.9 | 5.5 | 5.1 |
| 60.0 | 6.1 | 5.8 | 5.6 | 5.2 | 4.8 |
| 65.0 | 5.7 | 5.5 | 5.2 | 4.8 | |
| 70.0 | 5.2 | 5.0 | 4.8 | | |
| 75.0 | 4.2 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HC性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.3 | 7.6 | 7.1 | | |
| 46.0 | 8.0 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 7.7 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 7.4 | 6.9 | 6.5 | 5.9 | |
| 55.0 | 6.8 | 6.4 | 6.0 | 5.6 | 5.1 |
| 60.0 | 6.3 | 6.0 | 5.7 | 5.3 | 4.8 |
| 65.0 | 5.6 | 5.6 | 5.4 | 4.9 | 4.7 |
| 70.0 | 4.3 | 4.9 | 5.0 | 4.7 | |
| 75.0 | 3.2 | 3.5 | 3.8 | | |
| 危険角度 (°) | 15 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HC性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.6 | 8.3 | 7.5 | | |
| 44.0 | 8.6 | 8.0 | 7.3 | | |
| 46.0 | 8.6 | 7.7 | 7.1 | | |
| 48.0 | 8.3 | 7.5 | 6.9 | 6.1 | |
| 50.0 | 8.0 | 7.3 | 6.7 | 6.0 | |
| 55.0 | 7.4 | 6.8 | 6.3 | 5.7 | 5.2 |
| 60.0 | 6.3 | 6.3 | 5.9 | 5.5 | 4.9 |
| 65.0 | 4.7 | 5.6 | 5.6 | 5.2 | 4.7 |
| 70.0 | 3.4 | 4.2 | 4.9 | 4.9 | 4.6 |
| 75.0 | 2.3 | 2.9 | 3.5 | 4.1 | |
| 80.0 | | 1.7 | 2.1 | | |
| 危険角度 (°) | 33 | 33 | 35 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HC性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 55.0 | 6.0 | 6.0 | 6.0 | 5.8 | 4.9 |
| 60.0 | 5.5 | 6.0 | 6.0 | 5.6 | 4.8 |
| 65.0 | 4.0 | 5.1 | 5.8 | 5.4 | 4.7 |
| 70.0 | 2.7 | 3.6 | 4.5 | 5.1 | 4.7 |
| 75.0 | 1.6 | 2.3 | 3.1 | 3.9 | |
| 80.0 | | | 1.8 | 2.4 | |
| 危険角度 (°) | 43 | 45 | 45 | 46 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HC性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | 5.5 | |
| 55.0 | 5.5 | 5.5 | 5.5 | 5.3 | |
| 60.0 | 5.1 | 5.5 | 5.5 | 5.1 | 3.8 |
| 65.0 | 3.6 | 4.7 | 5.5 | 5.0 | 3.8 |
| 70.0 | 2.3 | 3.3 | 4.2 | 4.9 | 3.8 |
| 75.0 | | 2.0 | 2.8 | 3.8 | 3.8 |
| 80.0 | | | | 2.3 | |
| 危険角度 (°) | 49 | 49 | 52 | 52 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HC性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 4.1 | 3.9 | 3.3 | 2.3 | |
| 55.0 | 4.1 | 3.7 | 3.1 | 2.2 | |
| 60.0 | 4.0 | 3.5 | 2.9 | 2.1 | |
| 65.0 | 3.2 | 3.3 | 2.8 | 2.0 | |
| 70.0 | 1.9 | 3.0 | 2.7 | 2.0 | |
| 75.0 | | 1.7 | 2.6 | 2.0 | |
| 80.0 | | | | 2.0 | |
| 危険角度 (°) | 51 | 53 | 55 | 55 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HC性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | 2.9 | 2.4 | 1.8 | | |
| 55.0 | 2.7 | 2.2 | 1.7 | | |
| 60.0 | 2.5 | 2.0 | 1.6 | | |
| 65.0 | 2.3 | 1.9 | | | |
| 70.0 | 1.7 | 1.9 | | | |
| 危険角度 (°) | 54 | 57 | 67 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |

HD性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.7 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 5.3 | 5.1 | 4.9 | 4.7 | |
| 70.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HD性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.4 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 7.2 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 6.6 | 6.2 | 5.9 | 5.5 | 5.1 |
| 60.0 | 6.1 | 5.8 | 5.6 | 5.2 | 4.8 |
| 65.0 | 5.7 | 5.5 | 5.2 | 4.8 | |
| 70.0 | 4.5 | 4.9 | 4.8 | | |
| 75.0 | 3.4 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HD性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.3 | 7.6 | 7.1 | | |
| 46.0 | 8.0 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 7.7 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 7.4 | 6.9 | 6.5 | 5.9 | |
| 55.0 | 6.8 | 6.4 | 6.0 | 5.6 | 5.1 |
| 60.0 | 6.1 | 6.0 | 5.7 | 5.3 | 4.8 |
| 65.0 | 4.7 | 5.4 | 5.4 | 4.9 | 4.7 |
| 70.0 | 3.5 | 4.0 | 4.5 | 4.7 | |
| 75.0 | 2.4 | 2.7 | 3.0 | | |
| 危険角度 (°) | 20 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HD性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.6 | 8.3 | 7.5 | | |
| 44.0 | 8.6 | 8.0 | 7.3 | | |
| 46.0 | 8.6 | 7.7 | 7.1 | | |
| 48.0 | 8.3 | 7.5 | 6.9 | 6.1 | |
| 50.0 | 8.0 | 7.3 | 6.7 | 6.0 | |
| 55.0 | 6.9 | 6.8 | 6.3 | 5.7 | 5.2 |
| 60.0 | 5.2 | 6.3 | 5.9 | 5.5 | 4.9 |
| 65.0 | 3.8 | 4.7 | 5.6 | 5.2 | 4.7 |
| 70.0 | 2.6 | 3.3 | 4.0 | 4.9 | 4.6 |
| 75.0 | | 2.1 | 2.6 | 3.2 | |
| 危険角度 (°) | 39 | 39 | 41 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HD性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 55.0 | 6.0 | 6.0 | 6.0 | 5.8 | 4.9 |
| 60.0 | 4.5 | 5.7 | 6.0 | 5.6 | 4.8 |
| 65.0 | 3.1 | 4.1 | 5.2 | 5.4 | 4.7 |
| 70.0 | 1.8 | 2.8 | 3.6 | 4.7 | 4.7 |
| 75.0 | | | 2.2 | 3.1 | |
| 80.0 | | | | 1.6 | |
| 危険角度 (°) | 47 | 50 | 50 | 50 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HD性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | 5.5 | |
| 55.0 | 5.5 | 5.5 | 5.5 | 5.3 | |
| 60.0 | 4.1 | 5.4 | 5.5 | 5.1 | 3.8 |
| 65.0 | 2.7 | 3.8 | 4.9 | 5.0 | 3.8 |
| 70.0 | | 2.4 | 3.4 | 4.6 | 3.8 |
| 75.0 | | | 2.0 | 3.0 | 3.5 |
| 危険角度 (°) | 53 | 53 | 54 | 56 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HD性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 4.1 | 3.9 | 3.3 | 2.3 | |
| 55.0 | 4.1 | 3.7 | 3.1 | 2.2 | |
| 60.0 | 3.7 | 3.5 | 2.9 | 2.1 | |
| 65.0 | 2.3 | 3.3 | 2.8 | 2.0 | |
| 70.0 | | 2.1 | 2.7 | 2.0 | |
| 75.0 | | | 1.8 | 2.0 | |
| 危険角度 (°) | 55 | 56 | 56 | 59 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HD性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | 2.9 | 2.4 | 1.8 | | |
| 55.0 | 2.7 | 2.2 | 1.7 | | |
| 60.0 | 2.5 | 2.0 | 1.6 | | |
| 65.0 | 2.0 | 1.9 | | | |
| 70.0 | | 1.9 | | | |
| 危険角度 (°) | 57 | 58 | 67 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |

HE性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.7 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 5.3 | 5.1 | 4.9 | 4.7 | |
| 70.0 | 4.8 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HE性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.4 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 7.2 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 6.6 | 6.2 | 5.9 | 5.5 | 5.1 |
| 60.0 | 5.7 | 5.8 | 5.6 | 5.2 | 4.8 |
| 65.0 | 4.4 | 4.9 | 5.2 | 4.8 | |
| 70.0 | 3.2 | 3.6 | 4.0 | | |
| 75.0 | 2.2 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HE性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.3 | 7.6 | 7.1 | | |
| 46.0 | 8.0 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 7.7 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 7.4 | 6.9 | 6.5 | 5.9 | |
| 55.0 | 6.2 | 6.4 | 6.0 | 5.6 | 5.1 |
| 60.0 | 4.6 | 5.5 | 5.7 | 5.3 | 4.8 |
| 65.0 | 3.3 | 4.0 | 4.7 | 4.9 | 4.7 |
| 70.0 | | 2.7 | 3.2 | 3.8 | |
| 75.0 | | | 1.8 | | |
| 危険角度 (°) | 28 | 33 | 34 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HE性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.6 | 8.3 | 7.5 | | |
| 44.0 | 8.6 | 8.0 | 7.3 | | |
| 46.0 | 8.6 | 7.7 | 7.1 | | |
| 48.0 | 8.0 | 7.5 | 6.9 | 6.1 | |
| 50.0 | 7.1 | 7.3 | 6.7 | 6.0 | |
| 55.0 | 5.3 | 6.5 | 6.3 | 5.7 | 5.2 |
| 60.0 | 3.7 | 4.8 | 5.8 | 5.5 | 4.9 |
| 65.0 | | 3.3 | 4.2 | 5.2 | 4.7 |
| 70.0 | | 2.0 | 2.7 | 3.7 | 4.1 |
| 75.0 | | | | 2.0 | |
| 危険角度 (°) | 45 | 45 | 48 | 48 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HE性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 55.0 | 4.5 | 6.0 | 6.0 | 5.8 | 4.9 |
| 60.0 | 3.0 | 4.2 | 5.4 | 5.6 | 4.8 |
| 65.0 | 1.7 | 2.7 | 3.7 | 5.1 | 4.7 |
| 70.0 | | | 2.3 | 3.4 | 4.1 |
| 75.0 | | | | 1.9 | |
| 危険角度 (°) | 51 | 55 | 55 | 55 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HE性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 5.5 | 5.5 | 5.5 | 5.5 | |
| 55.0 | 4.1 | 5.5 | 5.5 | 5.3 | |
| 60.0 | 2.6 | 3.9 | 5.2 | 5.1 | 3.8 |
| 65.0 | | 2.4 | 3.5 | 5.0 | 3.8 |
| 70.0 | | | 2.1 | 3.3 | 3.8 |
| 75.0 | | | | 1.8 | 2.3 |
| 危険角度 (°) | 56 | 57 | 57 | 58 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HE性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 4.1 | 3.9 | 3.3 | 2.3 | |
| 55.0 | 3.8 | 3.7 | 3.1 | 2.2 | |
| 60.0 | 2.2 | 3.5 | 2.9 | 2.1 | |
| 65.0 | | 2.1 | 2.8 | 2.0 | |
| 70.0 | | | 1.8 | 2.0 | |
| 75.0 | | | | 1.7 | |
| 危険角度 (°) | 58 | 59 | 60 | 61 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HE性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | 2.9 | 2.4 | 1.8 | | |
| 55.0 | 2.7 | 2.2 | 1.7 | | |
| 60.0 | 1.9 | 2.0 | 1.6 | | |
| 65.0 | | 1.9 | | | |
| 危険角度 (°) | 60 | 61 | 67 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |

HF性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.7 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 5.1 | 5.1 | 4.9 | 4.7 | |
| 70.0 | 4.0 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HF性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.4 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 7.2 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 6.2 | 6.2 | 5.9 | 5.5 | 5.1 |
| 60.0 | 4.8 | 5.5 | 5.6 | 5.2 | 4.8 |
| 65.0 | 3.5 | 4.1 | 4.6 | 4.8 | |
| 70.0 | 2.5 | 2.8 | 3.2 | | |
| 危険角度 (°) | 18 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HF性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.3 | 7.6 | 7.1 | | |
| 46.0 | 8.0 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 7.7 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 6.9 | 6.9 | 6.5 | 5.9 | |
| 55.0 | 5.1 | 6.2 | 6.0 | 5.6 | 5.1 |
| 60.0 | 3.7 | 4.6 | 5.4 | 5.3 | 4.8 |
| 65.0 | 2.4 | 3.2 | 3.9 | 4.8 | 4.7 |
| 70.0 | | 1.9 | 2.4 | 3.0 | |
| 危険角度 (°) | 37 | 37 | 38 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HF性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.6 | 8.3 | 7.5 | | |
| 44.0 | 8.6 | 8.0 | 7.3 | | |
| 46.0 | 7.7 | 7.7 | 7.1 | | |
| 48.0 | 6.8 | 7.5 | 6.9 | 6.1 | |
| 50.0 | 6.0 | 7.3 | 6.7 | 6.0 | |
| 55.0 | 4.3 | 5.5 | 6.3 | 5.7 | 5.2 |
| 60.0 | 2.8 | 3.9 | 4.9 | 5.5 | 4.9 |
| 65.0 | | 2.5 | 3.3 | 4.5 | 4.7 |
| 70.0 | | | 1.9 | 2.9 | 3.3 |
| 危険角度 (°) | 50 | 50 | 51 | 52 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HF性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 6.0 | 6.0 | 6.0 | | |
| 48.0 | 6.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 5.3 | 6.0 | 6.0 | 6.0 | |
| 55.0 | 3.5 | 4.9 | 6.0 | 5.8 | 4.9 |
| 60.0 | 2.1 | 3.3 | 4.5 | 5.6 | 4.8 |
| 65.0 | | 1.9 | 2.9 | 4.3 | 4.7 |
| 70.0 | | | | 2.6 | 3.4 |
| 危険角度 (°) | 54 | 56 | 59 | 59 | 61 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HF性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.5 | 5.5 | 5.5 | | |
| 48.0 | 5.5 | 5.5 | 5.5 | | |
| 50.0 | 4.9 | 5.5 | 5.5 | 5.5 | |
| 55.0 | 3.1 | 4.6 | 5.5 | 5.3 | |
| 60.0 | 1.7 | 3.0 | 4.2 | 5.1 | 3.8 |
| 65.0 | | 1.6 | 2.6 | 4.1 | 3.8 |
| 70.0 | | | | 2.5 | 3.3 |
| 75.0 | | | | | 1.6 |
| 危険角度 (°) | 57 | 58 | 61 | 62 | 62 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HF性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 4.1 | 3.9 | 3.3 | 2.3 | |
| 55.0 | 2.8 | 3.7 | 3.1 | 2.2 | |
| 60.0 | | 2.7 | 2.9 | 2.1 | |
| 65.0 | | | 2.4 | 2.0 | |
| 70.0 | | | | 2.0 | |
| 危険角度 (°) | 62 | 63 | 63 | 64 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HF性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | 2.9 | 2.4 | 1.8 | | |
| 55.0 | 2.5 | 2.2 | 1.7 | | |
| 60.0 | | 2.0 | 1.6 | | |
| 危険角度 (°) | 64 | 65 | 67 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |

HG性能 14.4mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 18.0 | 9.3 | | | | |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 8.9 | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 8.8 | 8.7 | | | |
| 34.0 | 8.8 | 8.6 | | | |
| 36.0 | 8.8 | 8.5 | 7.9 | | |
| 38.0 | 8.7 | 8.1 | 7.6 | | |
| 40.0 | 8.3 | 7.8 | 7.3 | | |
| 42.0 | 7.9 | 7.5 | 7.0 | | |
| 44.0 | 7.6 | 7.2 | 6.8 | | |
| 46.0 | 7.3 | 6.9 | 6.6 | 6.1 | |
| 48.0 | 7.0 | 6.7 | 6.4 | 5.9 | |
| 50.0 | 6.8 | 6.5 | 6.2 | 5.8 | |
| 55.0 | 6.2 | 6.0 | 5.7 | 5.5 | 5.0 |
| 60.0 | 5.3 | 5.6 | 5.4 | 5.0 | 4.7 |
| 65.0 | 4.2 | 4.5 | 4.8 | 4.7 | |
| 70.0 | 3.2 | | | | |
| 危険角度 (°) | 10 | 20 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HG性能 19.55mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.2 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.0 | 8.9 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.9 | | | |
| 34.0 | 8.9 | 8.8 | | | |
| 36.0 | 8.9 | 8.7 | 8.0 | | |
| 38.0 | 8.8 | 8.4 | 7.7 | | |
| 40.0 | 8.7 | 8.0 | 7.5 | | |
| 42.0 | 8.3 | 7.7 | 7.2 | | |
| 44.0 | 8.0 | 7.5 | 7.0 | | |
| 46.0 | 7.7 | 7.2 | 6.7 | 6.2 | |
| 48.0 | 7.3 | 7.0 | 6.5 | 6.0 | |
| 50.0 | 6.7 | 6.7 | 6.3 | 5.8 | |
| 55.0 | 5.2 | 5.9 | 5.9 | 5.5 | 5.1 |
| 60.0 | 3.8 | 4.5 | 5.2 | 5.2 | 4.8 |
| 65.0 | 2.7 | 3.2 | 3.8 | 4.5 | |
| 70.0 | 1.7 | 2.0 | 2.4 | | |
| 危険角度 (°) | 25 | 28 | 30 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HG性能 23.6mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 20.0 | 9.3 | | | | |
| 22.0 | 9.3 | | | | |
| 24.0 | 9.2 | | | | |
| 26.0 | 9.2 | | | | |
| 28.0 | 9.2 | 9.1 | | | |
| 30.0 | 9.0 | 8.9 | | | |
| 32.0 | 8.9 | 8.8 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.9 | 8.6 | 8.1 | | |
| 38.0 | 8.8 | 8.5 | 7.8 | | |
| 40.0 | 8.7 | 8.2 | 7.6 | | |
| 42.0 | 8.6 | 7.9 | 7.3 | | |
| 44.0 | 8.0 | 7.6 | 7.1 | | |
| 46.0 | 7.3 | 7.4 | 6.9 | 6.2 | |
| 48.0 | 6.5 | 7.1 | 6.7 | 6.0 | |
| 50.0 | 5.8 | 6.8 | 6.5 | 5.9 | |
| 55.0 | 4.1 | 5.2 | 6.0 | 5.6 | 5.1 |
| 60.0 | 2.8 | 3.6 | 4.5 | 5.3 | 4.8 |
| 65.0 | 1.6 | 2.3 | 3.0 | 4.0 | 4.5 |
| 70.0 | | | 1.6 | 2.2 | |
| 危険角度 (°) | 39 | 42 | 42 | 45 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HG性能 32mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 9.0 | | | | |
| 24.0 | 9.0 | | | | |
| 26.0 | 9.0 | | | | |
| 28.0 | 9.0 | | | | |
| 30.0 | 9.0 | 8.8 | | | |
| 32.0 | 9.0 | 8.7 | | | |
| 34.0 | 8.9 | 8.7 | | | |
| 36.0 | 8.8 | 8.6 | | | |
| 38.0 | 8.8 | 8.6 | 8.0 | | |
| 40.0 | 8.7 | 8.6 | 7.7 | | |
| 42.0 | 8.3 | 8.3 | 7.5 | | |
| 44.0 | 7.4 | 8.0 | 7.3 | | |
| 46.0 | 6.5 | 7.7 | 7.1 | | |
| 48.0 | 5.7 | 7.1 | 6.9 | 6.1 | |
| 50.0 | 4.9 | 6.3 | 6.7 | 6.0 | |
| 55.0 | 3.2 | 4.5 | 5.7 | 5.7 | 5.2 |
| 60.0 | 1.9 | 2.9 | 4.0 | 5.3 | 4.9 |
| 65.0 | | 1.6 | 2.5 | 3.7 | 4.5 |
| 70.0 | | | | 2.1 | 2.5 |
| 危険角度 (°) | 51 | 52 | 55 | 55 | 60 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HG性能 40mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 22.0 | 6.0 | | | | |
| 24.0 | 6.0 | | | | |
| 26.0 | 6.0 | | | | |
| 28.0 | 6.0 | | | | |
| 30.0 | 6.0 | | | | |
| 32.0 | 6.0 | 6.0 | | | |
| 34.0 | 6.0 | 6.0 | | | |
| 36.0 | 6.0 | 6.0 | | | |
| 38.0 | 6.0 | 6.0 | 6.0 | | |
| 40.0 | 6.0 | 6.0 | 6.0 | | |
| 42.0 | 6.0 | 6.0 | 6.0 | | |
| 44.0 | 6.0 | 6.0 | 6.0 | | |
| 46.0 | 5.8 | 6.0 | 6.0 | | |
| 48.0 | 5.0 | 6.0 | 6.0 | 6.0 | |
| 50.0 | 4.2 | 5.8 | 6.0 | 6.0 | |
| 55.0 | 2.5 | 3.9 | 5.3 | 5.8 | 4.9 |
| 60.0 | | 2.4 | 3.5 | 5.1 | 4.8 |
| 65.0 | | | 2.0 | 3.4 | 4.4 |
| 70.0 | | | | 1.8 | 2.6 |
| 危険角度 (°) | 58 | 59 | 60 | 61 | 63 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HG性能 45mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 5.5 | | | | |
| 26.0 | 5.5 | | | | |
| 28.0 | 5.5 | | | | |
| 30.0 | 5.5 | | | | |
| 32.0 | 5.5 | 5.5 | | | |
| 34.0 | 5.5 | 5.5 | | | |
| 36.0 | 5.5 | 5.5 | | | |
| 38.0 | 5.5 | 5.5 | | | |
| 40.0 | 5.5 | 5.5 | 5.5 | | |
| 42.0 | 5.5 | 5.5 | 5.5 | | |
| 44.0 | 5.5 | 5.5 | 5.5 | | |
| 46.0 | 5.4 | 5.5 | 5.5 | | |
| 48.0 | 4.6 | 5.5 | 5.5 | | |
| 50.0 | 3.8 | 5.5 | 5.5 | 5.5 | |
| 55.0 | | 3.6 | 5.1 | 5.3 | |
| 60.0 | | | 3.3 | 5.0 | 3.8 |
| 65.0 | | | 1.8 | 3.3 | 3.8 |
| 70.0 | | | | 1.7 | 2.5 |
| 危険角度 (°) | 63 | 64 | 64 | 65 | 65 |
| フック種類 | 12t | 12t | 12t | 12t | 12t |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | 0.53 |
| 掛数 | 1 | 1 | 1 | 1 | 1 |

HG性能 50mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 4.1 | | | | |
| 26.0 | 4.1 | | | | |
| 28.0 | 4.1 | | | | |
| 30.0 | 4.1 | | | | |
| 32.0 | 4.1 | 4.0 | | | |
| 34.0 | 4.1 | 4.0 | | | |
| 36.0 | 4.1 | 4.0 | | | |
| 38.0 | 4.1 | 4.0 | | | |
| 40.0 | 4.1 | 4.0 | 3.8 | | |
| 42.0 | 4.1 | 4.0 | 3.7 | | |
| 44.0 | 4.1 | 4.0 | 3.6 | | |
| 46.0 | 4.1 | 4.0 | 3.5 | | |
| 48.0 | 4.1 | 4.0 | 3.4 | | |
| 50.0 | 3.4 | 3.9 | 3.3 | 2.3 | |
| 55.0 | | 3.3 | 3.1 | 2.2 | |
| 60.0 | | | 2.9 | 2.1 | |
| 65.0 | | | | 2.0 | |
| 危険角度 (°) | 66 | 67 | 68 | 69 | |
| フック種類 | 12t | 12t | 12t | 12t | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | 0.53 | |
| 掛数 | 1 | 1 | 1 | 1 | |

HG性能 53.9mブーム+4.4m+54mヘビーリフトジブ

| オフセット | 10° | 20° | 30° | 45° | 60° |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 24.0 | 3.5 | | | | |
| 26.0 | 3.5 | | | | |
| 28.0 | 3.5 | | | | |
| 30.0 | 3.5 | | | | |
| 32.0 | 3.5 | | | | |
| 34.0 | 3.5 | 3.3 | | | |
| 36.0 | 3.5 | 3.1 | | | |
| 38.0 | 3.5 | 3.0 | | | |
| 40.0 | 3.5 | 2.9 | 2.2 | | |
| 42.0 | 3.4 | 2.8 | 2.1 | | |
| 44.0 | 3.3 | 2.7 | 2.0 | | |
| 46.0 | 3.2 | 2.5 | 2.0 | | |
| 48.0 | 3.0 | 2.5 | 1.9 | | |
| 50.0 | | 2.4 | 1.8 | | |
| 55.0 | | 2.2 | 1.7 | | |
| 60.0 | | | 1.6 | | |
| 危険角度 (°) | 68 | 69 | 70 | | |
| フック種類 | 12t | 12t | 12t | | |
| フック質量 (t) | 0.53 | 0.53 | 0.53 | | |
| 掛数 | 1 | 1 | 1 | | |