

**HS性能 13.6mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
7.0	100.0				
8.0	100.0				
9.0	100.0				
10.0	100.0				
11.0	95.9	89.3			
12.0	91.1	85.2			
14.0	82.6	78.2	67.7		
16.0	70.9	72.3	63.5		
18.0	61.0	63.0	59.8	51.8	
20.0	53.1	54.8	56.4	49.8	46.3
22.0	46.6	48.1	49.5	48.1	45.4
24.0	41.2	42.5	43.7	45.2	44.8
26.0	36.7	37.8	38.8	40.0	40.6
28.0	32.7	33.7	34.5	35.5	
30.0	29.3	30.1	30.8	31.5	
32.0	26.4	27.0	27.6	27.9	
34.0	23.7	24.3	24.6		
36.0	21.4	21.7	21.9		
38.0	16.6				
危険角度 (°)	10	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	10	10	10	10	10

**HA性能 13.6mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
7.0	100.0				
8.0	100.0				
9.0	100.0				
10.0	100.0				
11.0	95.9	89.3			
12.0	91.1	85.2			
14.0	77.7	78.2	67.7		
16.0	66.9	69.0	63.5		
18.0	58.3	60.1	59.8	51.8	
20.0	51.3	52.8	54.3	49.8	46.3
22.0	45.4	46.8	48.1	48.1	45.4
24.0	40.5	41.7	42.8	44.2	44.8
26.0	36.3	37.3	38.2	39.4	40.0
28.0	32.6	33.5	34.3	35.2	
30.0	29.3	30.1	30.8	31.4	
32.0	26.4	27.0	27.6	27.9	
34.0	23.7	24.3	24.6		
36.0	21.4	21.7	21.9		
38.0	16.6				
危険角度 (°)	10	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	10	10	10	10	10

**HS性能 22.7mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	75.0				
11.0	75.0				
12.0	75.0				
14.0	74.0	66.5			
16.0	67.7	64.8	59.3		
18.0	57.7	60.4	58.1		
20.0	49.7	52.1	54.2	51.7	
22.0	43.2	45.3	47.1	49.6	48.5
24.0	37.8	39.6	41.2	43.4	44.8
26.0	33.2	34.8	36.2	38.1	39.2
28.0	29.2	30.7	31.9	33.5	34.3
30.0	25.8	27.1	28.2	29.5	30.1
32.0	22.8	23.9	24.9	26.0	26.3
34.0	20.1	21.1	22.0	22.8	
36.0	17.8	18.7	19.4	20.0	
38.0	15.7	16.4	17.0	17.4	
40.0	13.8	14.4	14.8		
42.0	12.1	12.6	12.8		
44.0	10.5	10.9	11.0		
46.0	8.4	9.0			
危険角度 (°)	10	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	8	8	8	8	8

**HA性能 22.7mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	75.0				
11.0	75.0				
12.0	75.0				
14.0	74.0	66.5			
16.0	63.9	64.8	59.3		
18.0	55.2	57.6	58.1		
20.0	48.1	50.3	52.2	51.7	
22.0	42.2	44.1	45.9	48.1	48.5
24.0	37.2	38.9	40.5	42.4	43.8
26.0	32.9	34.5	35.8	37.5	38.6
28.0	29.2	30.6	31.8	33.3	34.1
30.0	25.8	27.1	28.2	29.5	30.1
32.0	22.8	23.9	24.9	26.0	26.3
34.0	20.1	21.1	22.0	22.8	
36.0	17.8	18.7	19.4	20.0	
38.0	15.7	16.4	17.0	17.4	
40.0	13.8	14.4	14.8		
42.0	12.1	12.6	12.8		
44.0	10.5	10.9	11.0		
46.0	8.4	9.0			
危険角度 (°)	10	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	8	8	8	8	8

**HS性能 31.8mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	60.0				
14.0	60.0				
16.0	60.0	60.0			
18.0	56.1	60.0	57.6		
20.0	49.1	51.6	54.0	51.0	
22.0	42.6	44.8	46.9	49.5	
24.0	37.1	39.1	40.9	43.3	44.9
26.0	32.5	34.3	35.9	38.0	39.3
28.0	28.5	30.2	31.6	33.4	34.5
30.0	25.1	26.6	27.9	29.4	30.3
32.0	22.1	23.4	24.6	25.9	26.6
34.0	19.4	20.6	21.7	22.9	23.3
36.0	17.1	18.2	19.1	20.1	20.4
38.0	15.0	15.9	16.7	17.6	
40.0	13.1	13.9	14.6	15.3	
42.0	11.3	12.1	12.7	13.2	
44.0	9.8	10.5	11.0	11.3	
46.0	8.3	8.9	9.3		
48.0	7.0	7.5	7.8		
50.0	5.8	6.2	6.4		
危険角度 (°)	25	25	30	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	6	6	6	6	6

**HA性能 31.8mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	60.0				
14.0	60.0				
16.0	60.0	60.0			
18.0	54.6	57.2	57.6		
20.0	47.5	49.8	52.0	51.0	
22.0	41.6	43.7	45.6	48.0	
24.0	36.6	38.4	40.1	42.3	43.9
26.0	32.3	34.0	35.5	37.4	38.7
28.0	28.5	30.1	31.5	33.2	34.2
30.0	25.1	26.6	27.9	29.4	30.3
32.0	22.1	23.4	24.6	25.9	26.6
34.0	19.4	20.6	21.7	22.9	23.3
36.0	17.1	18.2	19.1	20.1	20.4
38.0	15.0	15.9	16.7	17.6	
40.0	13.1	13.9	14.6	15.3	
42.0	11.3	12.1	12.7	13.2	
44.0	9.8	10.5	11.0	11.3	
46.0	8.3	8.9	9.3		
48.0	7.0	7.5	7.8		
50.0	5.8	6.2	6.4		
危険角度 (°)	25	25	30	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	6	6	6	6	6

**HB性能 13.6mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
7.0	100.0				
8.0	100.0				
9.0	100.0				
10.0	91.6				
11.0	83.0	86.1			
12.0	75.7	78.5			
14.0	63.8	66.2	67.7		
16.0	54.3	56.6	58.6		
18.0	46.3	48.3	50.1	51.8	
20.0	39.8	41.5	42.8	44.6	46.0
22.0	34.2	35.4	36.6	38.0	39.1
24.0	29.6	30.6	31.5	32.7	33.5
26.0	25.8	26.6	27.4	28.4	28.9
28.0	22.6	23.3	24.0	24.7	
30.0	19.9	20.5	21.1	21.6	
32.0	17.6	18.1	18.5	18.8	
34.0	15.6	16.0	16.3		
36.0	13.9	14.1	14.2		
38.0	12.3				
危険角度 (°)	10	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	10	10	10	10	10

**HC性能 13.6mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
7.0	100.0				
8.0	98.2				
9.0	87.4				
10.0	78.4				
11.0	70.8	73.9			
12.0	64.4	67.2			
14.0	53.3	56.0	58.6		
16.0	44.4	46.7	48.9		
18.0	37.5	39.4	41.3	43.4	
20.0	31.9	33.3	34.6	36.4	37.7
22.0	27.1	28.3	29.4	30.8	31.9
24.0	23.3	24.2	25.2	26.3	27.1
26.0	20.1	20.9	21.7	22.6	23.1
28.0	17.4	18.1	18.8	19.5	
30.0	15.1	15.8	16.3	16.8	
32.0	13.1	13.6	14.0	14.3	
34.0	11.3	11.8	12.1		
36.0	9.6	10.0	10.1		
38.0	8.1				
危険角度 (°)	10	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	10	10	10	10	10

**HB性能 22.7mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	75.0				
11.0	75.0				
12.0	73.0				
14.0	60.9	64.1			
16.0	51.1	54.2	56.9		
18.0	43.0	45.6	48.1		
20.0	36.5	38.8	41.0	43.4	
22.0	31.2	33.2	34.7	36.7	38.2
24.0	26.7	28.3	29.7	31.4	32.6
26.0	23.0	24.4	25.5	26.9	27.9
28.0	19.8	21.0	22.0	23.2	23.9
30.0	17.0	18.2	19.1	20.1	20.6
32.0	14.5	15.6	16.5	17.4	17.7
34.0	12.4	13.4	14.2	15.0	
36.0	10.4	11.3	12.0	12.6	
38.0	8.7	9.5	10.0	10.4	
40.0	7.2	7.8	8.2		
42.0	5.8	6.3	6.5		
危険角度 (°)	31	33	34	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	8	8	8	8	8

**HC性能 22.7mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	75.0				
11.0	68.2				
12.0	61.7				
14.0	50.2	53.8			
16.0	41.2	44.2	47.1		
18.0	34.2	36.8	39.3		
20.0	28.5	30.9	32.9	35.2	
22.0	23.9	26.0	27.6	29.6	31.0
24.0	20.1	21.9	23.3	25.0	26.2
26.0	16.9	18.5	19.8	21.2	22.1
28.0	14.1	15.5	16.8	18.0	18.7
30.0	11.7	12.9	14.1	15.3	15.8
32.0	9.5	10.7	11.6	12.7	13.1
34.0	7.7	8.7	9.5	10.4	
36.0	6.0	6.9	7.6	8.2	
38.0			5.8	6.3	
危険角度 (°)	44	46	46	46	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	8	8	8	8	8

**HB性能 31.8mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	60.0				
14.0	60.0				
16.0	50.5	53.8			
18.0	42.4	45.2	47.9		
20.0	35.9	38.4	40.7	43.4	
22.0	30.5	32.8	34.6	36.7	
24.0	26.1	28.0	29.5	31.4	32.7
26.0	22.3	24.0	25.3	26.9	28.0
28.0	19.1	20.7	21.8	23.2	24.1
30.0	16.3	17.7	18.9	20.1	20.8
32.0	13.8	15.1	16.3	17.4	17.9
34.0	11.6	12.9	13.9	15.0	15.4
36.0	9.7	10.8	11.7	12.7	13.0
38.0	8.0	9.0	9.8	10.6	
40.0	6.4	7.3	8.0	8.7	
42.0	5.0	5.8	6.4	6.9	
44.0		4.4	4.9	5.3	
危険角度 (°)	45	45	45	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	6	6	6	6	6

**HC性能 31.8mブーム+9.4m+18mヘビーリフトジブ**

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	60.0				
14.0	49.7				
16.0	40.6	43.9			
18.0	33.6	36.4	39.1		
20.0	27.9	30.4	32.8	35.2	
22.0	23.3	25.5	27.4	29.6	
24.0	19.4	21.5	23.1	25.0	26.3
26.0	16.2	18.0	19.6	21.2	22.3
28.0	13.4	15.0	16.5	18.0	18.9
30.0	11.0	12.4	13.7	15.3	16.0
32.0	8.8	10.2	11.3	12.7	13.4
34.0	7.0	8.2	9.2	10.4	10.9
36.0	5.3	6.4	7.3	8.3	8.6
38.0		4.8	5.6	6.4	
40.0			4.0	4.7	
危険角度 (°)	53	53	53	53	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	6	6	6	6	6

## HD性能 13.6mブーム+9.4m+18mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
7.0	100.0				
8.0	93.4				
9.0	83.1				
10.0	74.5				
11.0	66.3	69.8			
12.0	59.2	62.5			
14.0	46.7	49.1	51.4		
16.0	37.1	39.1	41.0		
18.0	30.2	31.9	33.4	35.5	
20.0	25.0	26.4	27.7	29.5	30.8
22.0	21.0	22.2	23.3	24.7	25.7
24.0	17.7	18.7	19.6	20.8	21.6
26.0	15.0	15.9	16.7	17.6	18.1
28.0	12.8	13.5	14.2	14.9	
30.0	10.9	11.5	12.0	12.5	
32.0	9.3	9.8	10.1	10.4	
34.0	7.9	8.2	8.5		
36.0	6.6	6.8	6.9		
危険角度 (°)	20	20	30	45	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	10	10	10	10	10

## HD性能 22.7mブーム+9.4m+18mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	71.9				
11.0	63.4				
12.0	56.3				
14.0	44.0	47.2			
16.0	34.5	37.1	39.5		
18.0	27.6	29.8	31.9		
20.0	22.4	24.3	26.0	28.3	
22.0	18.3	20.0	21.5	23.4	24.9
24.0	15.1	16.5	17.8	19.5	20.6
26.0	12.4	13.6	14.8	16.2	17.1
28.0	10.2	11.2	12.2	13.4	14.1
30.0	8.3	9.2	10.1	11.1	11.5
32.0	6.3	7.5	8.2	9.0	9.3
34.0			6.4	7.2	
危険角度 (°)	50	53	53	54	60
フック種類	200t	200t	200t	200t	200t
フック質量 (t)	2.60	2.60	2.60	2.60	2.60
掛数	8	8	8	8	8

## HD性能 31.8mブーム+9.4m+18mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	55.8				
14.0	43.6				
16.0	34.1	36.8			
18.0	27.2	29.5	31.7		
20.0	22.0	24.0	25.9	28.3	
22.0	17.9	19.7	21.3	23.4	
24.0	14.6	16.2	17.6	19.4	20.8
26.0	11.9	13.3	14.6	16.2	17.2
28.0	9.7	10.9	12.0	13.4	14.3
30.0	7.8	8.9	9.9	11.0	11.8
32.0	5.6	7.0	8.0	9.0	9.6
34.0		5.0	6.1	7.2	7.9
36.0			4.2	5.3	5.7
危険角度 (°)	58	58	58	60	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	6	6	6	6	6