

HA性能 22.7mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
16.0	45.0				
18.0	45.0				
20.0	45.0				
22.0	45.0	42.9			
24.0	40.9	41.4			
26.0	36.5	39.1			
28.0	32.7	35.3	32.8		
30.0	29.4	31.8	31.4		
32.0	26.5	28.7	30.1		
34.0	23.8	25.9	27.9	25.3	
36.0	21.4	23.4	25.3	24.6	
38.0	19.2	21.1	22.8	24.0	21.5
40.0	17.3	19.0	20.6	22.8	21.1
42.0	15.5	17.1	18.5	20.5	20.7
44.0	13.9	15.3	16.7	18.5	19.8
46.0	12.4	13.8	15.0	16.6	17.7
48.0	11.1	12.3	13.4	14.9	15.7
50.0	9.9	11.0	12.0	13.2	13.8
55.0	7.2	8.0	8.7	9.5	
60.0	4.9	5.5	5.9		
危険角度 (°)	25	25	30	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HA性能 40.9mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	24.0				
22.0	24.0				
24.0	24.0				
26.0	24.0	24.0			
28.0	24.0	24.0			
30.0	24.0	24.0	24.0		
32.0	22.5	24.0	24.0		
34.0	20.4	22.4	24.0		
36.0	18.4	20.4	22.1	24.0	
38.0	16.2	18.5	20.1	22.1	
40.0	14.2	16.6	18.3	20.0	
42.0	12.4	14.6	16.6	18.0	18.9
44.0	10.8	12.9	14.7	16.3	17.0
46.0	9.3	11.2	13.0	14.8	15.3
48.0	8.0	9.7	11.4	13.2	13.7
50.0	6.7	8.4	9.9	11.7	12.0
55.0	3.9	5.4	6.6	8.2	8.5
60.0			3.9	5.1	
危険角度 (°)	50	53	53	55	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HA性能 31.8mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
18.0	32.0				
20.0	32.0				
22.0	32.0				
24.0	32.0	32.0			
26.0	32.0	32.0			
28.0	32.0	32.0	32.0		
30.0	28.6	31.3	32.0		
32.0	25.7	28.2	30.5		
34.0	22.9	25.4	27.6		
36.0	20.5	22.7	24.9	25.0	
38.0	18.3	20.4	22.4	24.4	
40.0	16.3	18.3	20.1	22.6	21.5
42.0	14.6	16.4	18.1	20.3	21.1
44.0	12.9	14.6	16.2	18.3	19.7
46.0	11.5	13.0	14.5	16.4	17.7
48.0	10.1	11.6	12.9	14.6	15.8
50.0	8.8	10.2	11.4	13.0	13.9
55.0	6.1	7.2	8.2	9.4	
60.0	3.8	4.7	5.5	6.2	
危険角度 (°)	40	40	43	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HA性能 50.0mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	18.0				
22.0	18.0				
24.0	18.0				
26.0	18.0	18.0			
28.0	18.0	18.0			
30.0	18.0	18.0			
32.0	18.0	18.0	18.0		
34.0	16.8	18.0	18.0		
36.0	15.3	17.0	18.0		
38.0	13.8	15.4	16.9	18.0	
40.0	12.5	13.9	15.2	17.0	
42.0	11.2	12.6	13.8	15.4	16.4
44.0	10.0	11.3	12.4	13.9	14.7
46.0	8.9	10.1	11.1	12.4	13.2
48.0	7.6	9.0	9.9	11.1	11.7
50.0	6.4	7.9	8.8	9.8	10.3
55.0	3.6	5.2	6.3	7.0	7.1
60.0		2.6	3.8	4.5	4.3
危険角度 (°)	55	56	58	60	60
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

HB性能 22.7mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
16.0	45.0				
18.0	45.0				
20.0	41.0				
22.0	35.5	38.5			
24.0	30.7	33.3			
26.0	26.7	29.1			
28.0	23.4	25.5	27.6		
30.0	20.6	22.5	24.4		
32.0	18.1	19.9	21.6		
34.0	16.0	17.7	19.2	21.4	
36.0	14.0	15.7	17.1	19.1	
38.0	12.2	14.0	15.3	17.1	18.6
40.0	10.6	12.3	13.6	15.2	16.6
42.0	9.2	10.8	12.1	13.6	14.7
44.0	7.9	9.3	10.7	12.1	13.1
46.0	6.7	8.0	9.2	10.7	11.5
48.0	5.6	6.8	7.9	9.3	10.0
50.0	4.6	5.7	6.7	7.9	8.5
55.0				4.6	
危険角度 (°)	45	46	49	49	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HB性能 40.9mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	24.0				
22.0	24.0				
24.0	24.0				
26.0	24.0	24.0			
28.0	20.9	24.0			
30.0	18.0	21.0	23.4		
32.0	15.4	18.4	20.6		
34.0	13.1	16.0	18.1		
36.0	11.1	13.7	15.9	18.5	
38.0	9.3	11.7	14.0	16.3	
40.0	7.6	9.9	12.1	14.5	
42.0	6.1	8.3	10.3	12.7	14.3
44.0	4.8	6.8	8.7	11.2	12.6
46.0		5.5	7.2	9.5	11.0
48.0		4.2	5.9	8.0	9.4
50.0			4.6	6.5	7.8
危険角度 (°)	62	62	64	68	68
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HB性能 31.8mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
18.0	32.0				
20.0	32.0				
22.0	32.0				
24.0	30.2	32.0			
26.0	26.1	28.8			
28.0	22.8	25.2	27.4		
30.0	19.9	22.1	24.2		
32.0	17.4	19.5	21.4		
34.0	15.1	17.2	19.0		
36.0	13.1	15.3	16.9	19.1	
38.0	11.3	13.4	15.0	17.0	
40.0	9.7	11.7	13.3	15.1	16.6
42.0	8.3	10.1	11.8	13.5	14.8
44.0	6.9	8.6	10.2	11.9	13.1
46.0	5.7	7.3	8.7	10.5	11.5
48.0	4.6	6.0	7.4	9.1	10.1
50.0		4.9	6.1	7.7	8.8
55.0				4.5	
危険角度 (°)	54	56	58	58	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HB性能 50.0mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	18.0				
22.0	18.0				
24.0	18.0				
26.0	18.0	18.0			
28.0	18.0	18.0			
30.0	17.8	18.0			
32.0	15.2	18.0	18.0		
34.0	12.9	15.9	18.0		
36.0	10.8	13.7	16.0		
38.0	9.0	11.7	14.1	16.5	
40.0	7.4	9.8	12.1	14.6	
42.0	5.9	8.2	10.3	12.9	14.5
44.0		6.7	8.7	11.3	12.8
46.0		5.3	7.2	9.7	11.2
48.0		4.1	5.8	8.1	9.7
50.0			4.6	6.7	8.1
55.0				3.5	4.5
危険角度 (°)	66	66	67	68	68
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

HC性能 22.7mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
16.0	45.0				
18.0	38.9				
20.0	33.1				
22.0	28.3	31.2			
24.0	24.3	26.9			
26.0	20.9	23.2			
28.0	18.0	20.2	22.3		
30.0	15.5	17.6	19.5		
32.0	13.3	15.4	17.1		
34.0	11.3	13.5	15.1	17.2	
36.0	9.6	11.6	13.2	15.2	
38.0	8.1	9.9	11.6	13.4	14.9
40.0	6.7	8.4	10.0	11.8	13.1
42.0	5.4	7.0	8.5	10.3	11.4
44.0	4.3	5.7	7.1	8.9	9.9
46.0		4.5	5.8	7.4	8.5
48.0			4.6	6.0	6.8
50.0				4.7	5.3
危険角度 (°)	53	55	56	58	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HC性能 40.9mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	24.0				
22.0	24.0				
24.0	21.7				
26.0	18.2	21.9			
28.0	15.2	18.8			
30.0	12.7	16.0	18.5		
32.0	10.4	13.5	16.1		
34.0	8.4	11.3	13.9		
36.0	6.7	9.3	11.8	14.5	
38.0		7.6	9.9	12.7	
40.0		6.0	8.1	11.0	
42.0			6.5	9.2	11.0
44.0			5.1	7.6	9.4
46.0				6.1	7.7
48.0				4.7	6.1
50.0					4.6
危険角度 (°)	68	69	70	70	71
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HC性能 31.8mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
18.0	32.0				
20.0	32.0				
22.0	27.6				
24.0	23.5	26.6			
26.0	20.1	23.0			
28.0	17.2	19.9	22.1		
30.0	14.7	17.3	19.3		
32.0	12.4	15.0	16.9		
34.0	10.5	12.9	14.8		
36.0	8.7	11.0	13.0	15.1	
38.0	7.2	9.2	11.2	13.3	
40.0	5.7	7.7	9.5	11.7	13.1
42.0	4.5	6.3	8.0	10.2	11.5
44.0		5.0	6.6	8.6	10.0
46.0			5.3	7.2	8.5
48.0			4.1	5.8	6.9
50.0				4.5	5.5
危険角度 (°)	60	62	62	64	64
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HC性能 50.0mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	18.0				
22.0	18.0				
24.0	18.0				
26.0	18.0	18.0			
28.0	15.1	18.0			
30.0	12.5	16.0			
32.0	10.2	13.5	16.2		
34.0	8.2	11.2	14.0		
36.0	6.4	9.3	11.9		
38.0		7.5	9.9	12.9	
40.0		5.9	8.2	11.1	
42.0			6.6	9.4	11.2
44.0				7.7	9.7
46.0				6.2	8.0
48.0				4.8	6.4
50.0					4.9
危険角度 (°)	71	72	73	73	74
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

HD性能 22.7mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
16.0	39.5				
18.0	32.1				
20.0	26.6				
22.0	22.2	25.1			
24.0	18.8	21.3			
26.0	15.9	18.2			
28.0	13.5	15.6	17.6		
30.0	11.5	13.4	15.2		
32.0	9.7	11.5	13.2		
34.0	8.2	9.8	11.4	13.5	
36.0	6.9	8.4	9.8	11.7	
38.0	5.5	7.1	8.4	10.1	11.6
40.0	4.1	5.9	7.1	8.7	10.0
42.0		4.5	6.0	7.4	8.6
44.0			4.7	6.2	7.2
46.0				5.1	5.9
48.0					4.7
危険角度 (°)	57	60	61	64	64
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HD性能 40.9mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	24.0				
22.0	20.3				
24.0	16.8				
26.0	13.8	16.9			
28.0	11.3	14.2			
30.0	9.1	11.9	14.3		
32.0		9.9	12.1		
34.0		8.1	10.2		
36.0			8.6	11.1	
38.0			7.1	9.4	
40.0				7.9	
42.0				6.6	8.1
44.0					6.7
46.0					5.5
危険角度 (°)	73	74	75	76	76
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HD性能 31.8mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
18.0	31.7				
20.0	26.1				
22.0	21.7				
24.0	18.2	21.1			
26.0	15.3	17.9			
28.0	12.9	15.3	17.5		
30.0	10.9	13.0	15.1		
32.0	9.1	11.1	13.0		
34.0	7.6	9.4	11.1		
36.0	6.1	7.9	9.5	11.7	
38.0		6.6	8.1	10.1	
40.0		5.2	6.8	8.6	10.1
42.0			5.6	7.3	8.6
44.0			4.2	6.1	7.2
46.0				4.9	6.0
48.0					4.8
危険角度 (°)	65	66	67	68	69
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

HD性能 50.0mブーム+9.4m+36mヘビーリフトジブ

オフセット	10°	20°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
20.0	18.0				
22.0	18.0				
24.0	15.9				
26.0	13.0	16.9			
28.0	10.5	14.1			
30.0		11.7			
32.0		9.5	12.2		
34.0		7.6	10.3		
36.0			8.4		
38.0			6.7	9.6	
40.0				8.1	
42.0				6.6	8.3
44.0					7.0
46.0					5.6
危険角度 (°)	76	76	77	78	78
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2