



# 10m — 31m

# スーパーラフィングブーム【50.0mブーム時】

### SA性能 50.0mブーム+2.3m+10mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
11.0	40.0				
12.0	40.0				
14.0	35.6	30.0			
16.0	31.6	27.1	25.0	22.0	
18.0	28.4	24.6	23.0	21.3	19.5
20.0	25.6	22.5	21.0	19.7	19.0
22.0	23.0	20.6	19.0	18.3	17.8
24.0	20.8	19.0	17.5	16.8	16.5
26.0	18.9	17.5	16.3	15.6	15.3
28.0	17.2	16.3	15.2	14.6	14.4
30.0	15.8	15.0	14.2	13.7	13.6
32.0	14.4	13.8	13.3	12.9	12.9
34.0	13.3	12.7	12.3	12.1	12.2
36.0	12.2	11.7	11.4	11.3	
38.0	11.2	10.8	10.6	10.5	
40.0	10.4	10.0	9.8	9.8	
42.0	9.5	9.3	9.1	9.1	
44.0	8.3	8.6	8.5	8.5	
46.0	7.0	7.5	7.8		
48.0	5.9	6.3	6.5		
50.0	4.8	5.2	5.3		
52.0		4.1	4.2		
危険角度 (°)	33	33	33	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

### SA性能 50.0mブーム+2.3m+23mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0				
20.0	18.0	16.3			
22.0	18.0	15.0			
24.0	16.5	13.8	11.9		
26.0	15.1	12.8	11.1		
28.0	13.9	11.8	10.5	9.5	
30.0	12.7	11.0	9.8	8.9	8.5
32.0	11.7	10.2	9.2	8.5	8.1
34.0	10.9	9.5	8.6	8.0	7.7
36.0	10.1	8.9	8.1	7.6	7.3
38.0	9.3	8.3	7.6	7.1	7.0
40.0	8.7	7.7	7.1	6.7	6.6
42.0	8.1	7.2	6.7	6.4	6.3
44.0	7.5	6.8	6.3	6.1	6.0
46.0	7.0	6.4	6.0	5.7	5.8
48.0	6.5	6.0	5.6	5.4	
50.0	6.1	5.6	5.3	5.2	
52.0	5.6	5.3	5.0	4.9	
54.0	5.2	5.0	4.7	4.7	
56.0	4.8	4.7	4.5	4.5	
58.0	4.1	4.3	4.3	4.3	
60.0		4.0	4.0		
危険角度 (°)	37	38	40	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

### SA性能 50.0mブーム+2.3m+15mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
10.0	18.0				
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0	18.0			
18.0	18.0	18.0			
20.0	18.0	18.0	17.2		
22.0	18.0	17.9	15.9	14.6	13.9
24.0	18.0	16.5	14.8	13.7	13.1
26.0	17.4	15.2	13.8	12.9	12.4
28.0	16.0	14.1	12.9	12.1	11.7
30.0	14.7	13.1	12.0	11.4	11.1
32.0	13.5	12.2	11.3	10.7	10.5
34.0	12.4	11.4	10.6	10.1	10.0
36.0	11.4	10.6	9.9	9.5	9.5
38.0	10.5	9.9	9.3	9.0	9.0
40.0	9.7	9.3	8.8	8.5	
42.0	9.0	8.6	8.3	8.1	
44.0	8.3	8.0	7.8	7.7	
46.0	7.7	7.4	7.2	7.2	
48.0	7.1	6.9	6.8	6.7	
50.0	6.0	6.4	6.3	6.3	
52.0	5.1	5.7	5.9		
54.0	4.1	4.7	5.0		
危険角度 (°)	34	36	37	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

### SA性能 50.0mブーム+2.3m+27mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
14.0	15.0				
16.0	15.0				
18.0	15.0				
20.0	15.0				
22.0	15.0	13.6			
24.0	15.0	12.9			
26.0	14.7	12.3			
28.0	13.5	11.4	9.5		
30.0	12.5	10.6	9.2		
32.0	11.5	9.9	8.8	7.8	
34.0	10.7	9.3	8.3	7.6	7.1
36.0	9.9	8.7	7.8	7.2	6.9
38.0	9.2	8.1	7.4	6.9	6.6
40.0	8.6	7.6	6.9	6.5	6.3
42.0	8.0	7.1	6.5	6.2	6.0
44.0	7.4	6.7	6.2	5.8	5.7
46.0	6.9	6.3	5.8	5.5	5.5
48.0	6.5	5.9	5.5	5.2	5.2
50.0	6.1	5.5	5.2	5.0	5.0
52.0	5.7	5.2	4.9	4.7	
54.0	5.3	4.9	4.6	4.5	
56.0	5.0	4.6	4.4	4.3	
58.0	4.6	4.3	4.1	4.1	
60.0	4.3	4.1	3.9	3.9	
62.0	3.6	3.9	3.7	3.7	
64.0		3.6	3.5		
危険角度 (°)	37	38	40	45	60
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

### SA性能 50.0mブーム+2.3m+19mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0	18.0			
20.0	18.0	17.7			
22.0	18.0	16.3	14.2		
24.0	17.7	15.0	13.2	12.0	
26.0	16.2	13.9	12.3	11.3	10.7
28.0	14.8	12.8	11.5	10.7	10.2
30.0	13.6	11.9	10.8	10.0	9.7
32.0	12.6	11.1	10.1	9.5	9.2
34.0	11.6	10.3	9.5	8.9	8.7
36.0	10.8	9.6	8.9	8.4	8.3
38.0	10.0	9.0	8.3	8.0	7.9
40.0	9.3	8.4	7.9	7.5	7.5
42.0	8.6	7.9	7.4	7.1	7.2
44.0	7.9	7.4	7.0	6.8	
46.0	7.4	7.0	6.6	6.4	
48.0	6.8	6.5	6.2	6.1	
50.0	6.3	6.1	5.9	5.8	
52.0	5.8	5.6	5.5	5.5	
54.0	5.0	5.2	5.2	5.2	
56.0	4.1	4.8	4.8		
58.0		4.0	4.3		
危険角度 (°)	36	36	37	45	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

### SA性能 50.0mブーム+2.3m+31mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
14.0	12.0				
16.0	12.0				
18.0	12.0				
20.0	12.0				
22.0	12.0				
24.0	12.0	10.5			
26.0	12.0	10.2			
28.0	12.0	9.7			
30.0	11.9	9.3	7.4		
32.0	10.9	8.9	7.2		
34.0	10.1	8.6	7.0	6.0	
36.0	9.4	8.1	6.8	5.9	
38.0	8.7	7.6	6.6	5.8	5.3
40.0	8.1	7.1	6.3	5.7	5.3
42.0	7.6	6.7	6.1	5.6	5.3
44.0	7.1	6.3	5.7	5.4	5.2
46.0	6.6	5.9	5.4	5.1	5.0
48.0	6.2	5.5	5.1	4.8	4.7
50.0	5.8	5.2	4.8	4.6	4.5
52.0	5.4	4.9	4.5	4.3	4.3
54.0	5.0	4.6	4.3	4.1	4.1
56.0	4.7	4.3	4.0	3.9	
58.0	4.4	4.1	3.8	3.7	
60.0	4.1	3.8	3.6	3.5	
62.0	3.9	3.6	3.4	3.4	
64.0	3.5	3.4	3.2	3.2	
66.0	2.9	3.2	3.1	3.1	
68.0		3.0	2.9		
70.0		2.5	2.7		
危険角度 (°)	36	36	38	45	60
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

# 10m — 31m スーパーラフティングブーム【50.0mブーム時】

SB性能 50.0mブーム+2.3m+10mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
11.0	40.0				
12.0	40.0				
14.0	35.6	30.0			
16.0	31.6	27.1	25.0	22.0	
18.0	28.4	24.6	23.0	21.3	19.5
20.0	25.6	22.5	21.0	19.7	19.0
22.0	23.0	20.6	19.0	18.3	17.8
24.0	20.8	19.0	17.5	16.8	16.5
26.0	18.7	17.5	16.3	15.6	15.3
28.0	15.9	16.3	15.2	14.6	14.4
30.0	13.4	14.4	14.2	13.7	13.6
32.0	11.2	12.2	12.9	12.9	12.9
34.0	9.3	10.2	10.9	11.3	11.3
36.0	7.6	8.4	9.1	9.4	
38.0	6.0	6.8	7.4	7.7	
40.0	4.6	5.4	5.8	6.1	
42.0			4.4	4.5	
危険角度 (°)	48	49	49	49	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SB性能 50.0mブーム+2.3m+23mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0				
20.0	18.0	16.3			
22.0	18.0	15.0			
24.0	16.5	13.8	11.9		
26.0	15.1	12.8	11.1		
28.0	13.9	11.8	10.5	9.5	
30.0	12.7	11.0	9.8	8.9	8.5
32.0	11.7	10.2	9.2	8.5	8.1
34.0	10.9	9.5	8.6	8.0	7.7
36.0	10.1	8.9	8.1	7.6	7.3
38.0	8.9	8.3	7.6	7.1	7.0
40.0	7.5	7.7	7.1	6.7	6.6
42.0	6.3	7.2	6.7	6.4	6.3
44.0	5.2	6.7	6.3	6.1	6.0
46.0	4.0	5.5	6.0	5.7	5.8
48.0		4.4	5.5	5.4	
50.0			4.4	5.0	
危険角度 (°)	51	53	54	55	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SB性能 50.0mブーム+2.3m+15mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
10.0	18.0				
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0	18.0			
18.0	18.0	18.0			
20.0	18.0	18.0	17.2		
22.0	18.0	17.9	15.9	14.6	13.9
24.0	18.0	16.5	14.8	13.7	13.1
26.0	17.4	15.2	13.8	12.9	12.4
28.0	16.0	14.1	12.9	12.1	11.7
30.0	14.5	13.1	12.0	11.4	11.1
32.0	12.4	12.2	11.3	10.7	10.5
34.0	10.5	11.4	10.6	10.1	10.0
36.0	8.8	10.1	9.9	9.5	9.5
38.0	7.3	8.5	9.3	9.0	9.0
40.0	5.9	7.0	7.9	8.5	
42.0	4.6	5.7	6.5	7.0	
44.0		4.4	5.1	5.5	
46.0				4.1	
危険角度 (°)	50	50	51	51	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SB性能 50.0mブーム+2.3m+27mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
14.0	15.0				
16.0	15.0				
18.0	15.0				
20.0	15.0				
22.0	15.0	13.6			
24.0	15.0	12.9			
26.0	14.7	12.3			
28.0	13.5	11.4	9.5		
30.0	12.5	10.6	9.2		
32.0	11.5	9.9	8.8	7.8	
34.0	10.7	9.3	8.3	7.6	7.1
36.0	9.9	8.7	7.8	7.2	6.9
38.0	9.2	8.1	7.4	6.9	6.6
40.0	8.6	7.6	6.9	6.5	6.3
42.0	7.4	7.1	6.5	6.2	6.0
44.0	6.3	6.7	6.2	5.8	5.7
46.0	5.1	6.3	5.8	5.5	5.5
48.0	4.1	5.7	5.5	5.2	5.2
50.0	3.1	4.6	5.2	5.0	5.0
52.0		3.7	4.8	4.7	
54.0			3.8	4.5	
危険角度 (°)	51	53	54	55	60
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

SB性能 50.0mブーム+2.3m+19mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0	18.0			
20.0	18.0	17.7			
22.0	18.0	16.3	14.2		
24.0	17.7	15.0	13.2	12.0	
26.0	16.2	13.9	12.3	11.3	10.7
28.0	14.8	12.8	11.5	10.7	10.2
30.0	13.6	11.9	10.8	10.0	9.7
32.0	12.6	11.1	10.1	9.5	9.2
34.0	11.3	10.3	9.5	8.9	8.7
36.0	9.7	9.6	8.9	8.4	8.3
38.0	8.2	9.0	8.3	8.0	7.9
40.0	6.8	8.2	7.9	7.5	7.5
42.0	5.5	6.9	7.4	7.1	7.2
44.0	4.3	5.6	6.6	6.8	
46.0		4.4	5.4	6.0	
48.0			4.1	4.6	
危険角度 (°)	51	51	51	53	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SB性能 50.0mブーム+2.3m+31mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
14.0	12.0				
16.0	12.0				
18.0	12.0				
20.0	12.0				
22.0	12.0				
24.0	12.0	10.5			
26.0	12.0	10.2			
28.0	12.0	9.7			
30.0	11.9	9.3	7.4		
32.0	10.9	8.9	7.2		
34.0	10.1	8.6	7.0	6.0	
36.0	9.4	8.1	6.8	5.9	
38.0	8.7	7.6	6.6	5.8	5.3
40.0	8.1	7.1	6.3	5.7	5.3
42.0	7.6	6.7	6.1	5.6	5.3
44.0	6.9	6.3	5.7	5.4	5.2
46.0	5.8	5.9	5.4	5.1	5.0
48.0	4.8	5.5	5.1	4.8	4.7
50.0	3.8	5.2	4.8	4.6	4.5
52.0	3.0	4.6	4.5	4.3	4.3
54.0		3.7	4.3	4.1	4.1
56.0			4.0	3.9	
58.0			3.1	3.7	
危険角度 (°)	51	53	54	55	60
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2



# 10m — 31m

# スーパーラフィングブーム【50.0mブーム時】

SC性能 50.0mブーム+2.3m+10mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
11.0	40.0				
12.0	40.0				
14.0	35.6	30.0			
16.0	31.6	27.1	25.0	22.0	
18.0	28.0	24.6	23.0	21.3	19.5
20.0	23.0	22.5	21.0	19.7	19.0
22.0	18.9	20.6	19.0	18.3	17.8
24.0	15.5	17.0	17.5	16.8	16.5
26.0	12.7	14.0	15.0	15.6	15.3
28.0	10.2	11.5	12.4	12.9	13.2
30.0	8.1	9.2	10.2	10.7	10.8
32.0	6.2	7.3	8.1	8.6	8.7
34.0	4.4	5.5	6.3	6.7	6.8
36.0			4.4	4.8	
危険角度 (°)	56	57	57	57	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SC性能 50.0mブーム+2.3m+23mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0				
20.0	18.0	16.3			
22.0	18.0	15.0			
24.0	16.5	13.8	11.9		
26.0	15.1	12.8	11.1		
28.0	12.9	11.8	10.5	9.5	
30.0	10.9	11.0	9.8	8.9	8.5
32.0	9.1	10.2	9.2	8.5	8.1
34.0	7.5	9.4	8.6	8.0	7.7
36.0	6.0	7.9	8.1	7.6	7.3
38.0	4.6	6.6	7.6	7.1	7.0
40.0		5.2	6.7	6.7	6.6
42.0			5.4	6.4	6.3
44.0			4.1	5.1	5.6
危険角度 (°)	59	61	61	63	63
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SC性能 50.0mブーム+2.3m+15mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	18.0				
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0	18.0			
18.0	18.0	18.0			
20.0	18.0	18.0	17.2		
22.0	18.0	17.9	15.9	14.6	13.9
24.0	16.8	16.5	14.8	13.7	13.1
26.0	13.9	15.2	13.8	12.9	12.4
28.0	11.5	13.1	12.9	12.1	11.7
30.0	9.4	10.9	12.0	11.4	11.1
32.0	7.5	9.1	10.2	10.7	10.5
34.0	5.8	7.3	8.5	9.1	9.5
36.0	4.2	5.7	6.8	7.6	7.8
38.0		4.1	5.2	5.9	6.1
40.0				4.2	
危険角度 (°)	57	57	59	59	60
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SC性能 50.0mブーム+2.3m+27mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
14.0	15.0				
16.0	15.0				
18.0	15.0				
20.0	15.0				
22.0	15.0	13.6			
24.0	15.0	12.9			
26.0	14.7	12.3			
28.0	13.5	11.4	9.5		
30.0	11.8	10.6	9.2		
32.0	10.1	9.9	8.8	7.8	
34.0	8.6	9.3	8.3	7.6	7.1
36.0	7.2	8.7	7.8	7.2	6.9
38.0	5.8	7.7	7.4	6.9	6.6
40.0	4.4	6.6	6.9	6.5	6.3
42.0		5.3	6.5	6.2	6.0
44.0		4.1	5.8	5.8	5.7
46.0			4.5	5.5	5.5
48.0			3.4	4.4	4.9
危険角度 (°)	59	61	61	63	63
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

SC性能 50.0mブーム+2.3m+19mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0	18.0			
20.0	18.0	17.7			
22.0	18.0	16.3	14.2		
24.0	17.5	15.0	13.2	12.0	
26.0	14.6	13.9	12.3	11.3	10.7
28.0	12.3	12.8	11.5	10.7	10.2
30.0	10.2	11.9	10.8	10.0	9.7
32.0	8.4	10.1	10.1	9.5	9.2
34.0	6.7	8.5	9.5	8.9	8.7
36.0	5.2	7.0	8.2	8.4	8.3
38.0		5.4	6.8	7.6	7.9
40.0		4.0	5.3	6.2	6.6
42.0				4.7	5.0
危険角度 (°)	58	59	61	61	61
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SC性能 50.0mブーム+2.3m+31mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
14.0	12.0				
16.0	12.0				
18.0	12.0				
20.0	12.0				
22.0	12.0				
24.0	12.0	10.5			
26.0	12.0	10.2			
28.0	12.0	9.7			
30.0	11.9	9.3	7.4		
32.0	10.6	8.9	7.2		
34.0	9.1	8.6	7.0	6.0	
36.0	7.8	8.1	6.8	5.9	
38.0	6.5	7.6	6.6	5.8	5.3
40.0	5.1	7.1	6.3	5.7	5.3
42.0	4.0	6.4	6.1	5.6	5.3
44.0		5.1	5.7	5.4	5.2
46.0		3.9	5.4	5.1	5.0
48.0			4.6	4.8	4.7
50.0			3.5	4.6	4.5
52.0				3.7	4.2
危険角度 (°)	59	61	61	63	63
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

# 10m — 31m スーパーラフティングブーム【50.0mブーム時】

SD性能 50.0mブーム+2.3m+10mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
11.0	40.0				
12.0	40.0				
14.0	34.8	30.0			
16.0	26.7	27.1	25.0	22.0	
18.0	20.9	22.8	23.0	21.3	19.5
20.0	16.6	18.2	19.5	19.7	19.0
22.0	13.2	14.6	15.7	16.6	17.1
24.0	10.4	11.7	12.7	13.4	13.8
26.0	8.0	9.3	10.2	10.8	11.1
28.0	5.6	7.0	8.1	8.6	8.9
30.0			5.8	6.4	6.7
危険角度 (°)	63	64	64	64	64
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SD性能 50.0mブーム+2.3m+23mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0				
20.0	18.0	16.3			
22.0	15.5	15.0			
24.0	12.8	13.8	11.9		
26.0	10.5	12.8	11.1		
28.0	8.6	10.7	10.5	9.5	
30.0	6.8	8.9	9.8	8.9	8.5
32.0		7.4	9.0	8.5	8.1
34.0		5.8	7.5	8.0	7.7
36.0			6.2	7.2	7.3
38.0			4.6	6.0	6.6
40.0				4.5	5.3
危険角度 (°)	66	67	67	68	68
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SD性能 50.0mブーム+2.3m+15mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
10.0	18.0				
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0	18.0			
18.0	18.0	18.0			
20.0	17.6	18.0	17.2		
22.0	14.2	16.3	15.9	14.6	13.9
24.0	11.4	13.3	14.8	13.7	13.1
26.0	9.2	10.8	12.2	12.9	12.4
28.0	7.0	8.8	10.0	11.0	11.6
30.0		6.8	8.2	9.0	9.5
32.0			6.3	7.3	7.7
34.0				5.4	5.9
危険角度 (°)	64	65	65	65	65
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SD性能 50.0mブーム+2.3m+27mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
14.0	15.0				
16.0	15.0				
18.0	15.0				
20.0	15.0				
22.0	15.0	13.6			
24.0	13.7	12.9			
26.0	11.4	12.3			
28.0	9.5	11.4	9.5		
30.0	7.8	10.1	9.2		
32.0	6.2	8.5	8.8	7.8	
34.0		7.1	8.3	7.6	7.1
36.0		5.7	7.5	7.2	6.9
38.0			6.3	6.9	6.6
40.0			5.0	6.3	6.3
42.0			3.7	5.2	5.8
44.0				3.9	4.6
危険角度 (°)	66	67	67	68	68
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

SD性能 50.0mブーム+2.3m+19mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	18.0	18.0			
20.0	18.0	17.7			
22.0	14.9	16.3	14.2		
24.0	12.1	14.4	13.2	12.0	
26.0	9.9	11.9	12.3	11.3	10.7
28.0	8.0	9.8	11.4	10.7	10.2
30.0	5.9	8.0	9.5	10.0	9.7
32.0		6.3	7.8	8.9	9.2
34.0			6.3	7.3	7.8
36.0			4.6	5.8	6.4
38.0				4.7	4.7
危険角度 (°)	65	66	66	67	67
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SD性能 50.0mブーム+2.3m+31mSLブーム

オフセット 作業半径 (m)	0° 荷重 (ton)	15° 荷重 (ton)	30° 荷重 (ton)	45° 荷重 (ton)	60° 荷重 (ton)
14.0	12.0				
16.0	12.0				
18.0	12.0				
20.0	12.0				
22.0	12.0				
24.0	12.0	10.5			
26.0	11.9	10.2			
28.0	10.0	9.7			
30.0	8.3	9.3	7.4		
32.0	6.9	8.9	7.2		
34.0		5.3	7.8	7.0	6.0
36.0			6.6	6.8	5.9
38.0			5.3	6.6	5.8
40.0				6.1	5.7
42.0				5.0	5.6
44.0				3.8	5.3
46.0					4.1
48.0					3.8
危険角度 (°)	66	67	67	68	68
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2



# 10m — 31m

# スーパーラフィングブーム【50.0mブーム時】

SE性能 50.0mブーム+2.3m+10mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
11.0	40.0				
12.0	35.2				
14.0	26.1	29.4			
16.0	19.6	22.4	24.9	22.0	
18.0	14.6	17.0	19.0	20.3	19.5
20.0	10.7	12.8	14.5	15.6	16.3
22.0		9.5	11.1	12.0	12.6
24.0			8.1	9.2	9.6
危険角度 (°)	70	71	71	71	71
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SE性能 50.0mブーム+2.3m+23mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	16.8				
20.0	13.2	16.3			
22.0	10.2	14.0			
24.0		11.1	11.9		
26.0		8.7	11.1		
28.0			9.1	9.5	
30.0			7.3	8.9	8.5
32.0				7.2	8.1
34.0				5.7	6.6
36.0					5.2
危険角度 (°)	72	73	74	74	74
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SE性能 50.0mブーム+2.3m+15mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	18.0				
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0	18.0			
18.0	15.6	18.0			
20.0	11.8	14.9	17.2		
22.0	8.8	11.5	13.6	14.6	13.9
24.0		8.7	10.7	12.0	12.9
26.0			8.2	9.5	10.2
28.0				7.4	8.0
危険角度 (°)	71	72	72	72	73
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SE性能 50.0mブーム+2.3m+27mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
14.0	15.0				
16.0	15.0				
18.0	15.0				
20.0	14.3				
22.0	11.3	13.6			
24.0	8.8	12.6			
26.0		10.3			
28.0		8.2	9.5		
30.0			8.8		
32.0			7.2	7.8	
34.0			5.8	7.4	7.1
36.0				6.0	6.9
38.0					5.7
40.0					4.4
危険角度 (°)	72	73	74	74	74
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

SE性能 50.0mブーム+2.3m+19mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	18.0				
18.0	16.3	18.0			
20.0	12.6	16.3			
22.0	9.5	12.8	14.2		
24.0		10.0	12.3	12.0	
26.0		7.6	9.8	11.3	10.7
28.0			7.8	9.2	10.1
30.0				7.3	8.1
32.0					6.4
危険角度 (°)	72	72	73	73	73
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SE性能 50.0mブーム+2.3m+31mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
14.0	12.0				
16.0	12.0				
18.0	12.0				
20.0	12.0				
22.0	11.8				
24.0	9.4	10.5			
26.0	7.3	10.2			
28.0		9.1			
30.0		7.3	7.4		
32.0		5.8	7.2		
34.0			6.8	6.0	
36.0			5.6	5.9	
38.0				5.8	5.3
40.0				4.9	5.3
42.0					4.7
危険角度 (°)	72	73	74	75	75
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2



10m — 31m

## スーパーラフィングブーム【50.0mブーム時】

SF性能 50.0mブーム+2.3m+10mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
11.0	31.4				
12.0	26.5				
14.0	18.8	22.1			
16.0	13.3	16.0	18.4	18.4	
18.0		11.5	13.5	14.8	15.5
20.0			9.7	11.0	11.6
危険角度 (°)	74	75	75	75	76
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SF性能 50.0mブーム+2.3m+23mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
12.0	18.0				
14.0	18.0				
16.0	15.5				
18.0	11.5				
20.0		12.7			
22.0		9.7			
24.0			9.9		
26.0			7.9		
28.0				7.7	
30.0					7.1
危険角度 (°)	76	77	78	79	79
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SF性能 50.0mブーム+2.3m+15mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
10.0	18.0				
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	14.3	18.0			
18.0		13.6			
20.0		10.0	12.4		
22.0			9.4	10.9	10.9
24.0				8.3	9.2
危険角度 (°)	75	76	76	77	77
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SF性能 50.0mブーム+2.3m+27mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
14.0	15.0				
16.0	15.0				
18.0	12.7				
20.0					
22.0		11.2			
24.0		8.8			
26.0					
28.0			7.6		
30.0					
32.0				6.2	
34.0					6.0
危険角度 (°)	76	77	78	79	79
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2

SF性能 50.0mブーム+2.3m+19mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
11.0	18.0				
12.0	18.0				
14.0	18.0				
16.0	14.9				
18.0	10.9	15.1			
20.0		11.4			
22.0		8.4	11.1		
24.0			8.6	10.2	
26.0				8.0	9.1
28.0					7.1
危険角度 (°)	75	76	77	78	78
フック種類	83t	83t	83t	83t	83t
フック質量 (t)	1.35	1.35	1.35	1.35	1.35
掛数	4	4	4	4	4

SF性能 50.0mブーム+2.3m+31mSLブーム

オフセット	0°	15°	30°	45°	60°
作業半径 (m)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)	荷重 (ton)
14.0	12.0				
16.0	12.0				
18.0	12.0				
20.0	10.0				
22.0					
24.0		9.7			
26.0		7.6			
28.0					
30.0			7.0		
32.0					
34.0				6.0	
36.0					
38.0					4.9
危険角度 (°)	76	77	78	79	79
フック種類	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88
掛数	2	2	2	2	2