






KATO



Evolution Towards True Value

Product Guide

KATO WORKS CO.,LTD.



Web site
kato-works.co.jp

/ KATO WORKS OFFICIAL
youtube.com/user/katowork

Instagram
instagram.com/kato_works_official/

- Before you operate the machine, study the instruction manual thoroughly and follow the instructions it contains.
- Some differences may arise between the machine delivered and the photographs in the catalog due to any added improvements.
- Note: The specification may be changed without notice.
- The actual colors of the body and interior may appear slightly different from those shown in this catalog due to the limitation of photography and printing.

● Contact for enquiry:

KATO **KATO WORKS CO.,LTD.**
 9-37, Higashi-ohi 1-chome, Shinagawa-ku, Tokyo, 140-0011, Japan
 Tel.: Head Office: Tokyo +81 (0)3 3458-1111
 Overseas Marketing Department: Tokyo +81 (0)3 3458-1115 / FAX: Tokyo +81 (0)3 3458-1163
<https://www.kato-works.co.jp>

C04975
12.2025-1000(FB)5

EXPLANATORY NOTES

Crane

-  Overall Length, Overall Width, Overall Height (Traveling Position)
-  GVW
-  Maximum Rated Lifting Capacity
-  Boom Section / Length
-  Super Luffing Jib Section / Length / Offset Angle
-  Power Jib Section / Length / Offset Angle
-  Manual Jib Section / Length / Offset Angle
-  Heavy Lift Jib Section / Length / Offset Angle
-  Outriggers Extension Width / Fully Extended
-  Maximum Traveling Speed
-  ACS (Automatic Crane System)
-  Searcher Hook / Length

Crawler Crane

-  Rated Output
-  Maximum Rated Lifting Capacity
-  Boom Section / Length
-  Jib Section / Length

Excavator/Mini Excavator

-  Rated Output
-  Operating Weight
-  Machine Weight
-  Bucket Capacity
-  Maximum Digging Depth
-  APC (Automatic Power Control)

Lineup

-  Long Crawler Specification
-  Dozer Specification

Crawler Carrier

-  Rated Output
-  Machine Weight
-  Maximum Payload

Vacuum Crawler

-  Rated Output
-  Machine Weight
-  Maximum Payload
-  Hopper Capacity
-  Air Volume (Only Blower)

Vacuum Truck

-  GVW
-  Hopper Capacity
-  Air Volume (Only Blower)

Street Sweeper

-  Rated Output (Superstructure Engine)
-  Hopper Capacity
-  Maximum Payload
-  Maximum Sweep Speed
-  Maximum Sweep Width

Snow Sweeper

-  Rated Output (Superstructure Engine)
-  Maximum Sweep Width
-  Maximum Sweep Speed

Earth Boring Rig

-  Rated Output
-  Operating Weight
-  Maximum Digging Depth
-  Maximum Digging Diameter

Compact Track Loader

-  Rated Output
-  Operating Weight
-  Bucket Capacity

CONTENTS

	Rough Terrain Crane	03
	Cityrange Crane	05
	All Terrain Crane	06
	Crawler Crane	07
	Excavator	08
	Mini Excavator	10
	Crawler Carrier/Full-Rotating Crawler Carrier	12
	Vacuum Crawler	13
	Vacuum Truck	13
	Snow Sweeper	13
	Compact Track Loader	13
	Street Sweeper	14
	Earth Drilling Rig	14



Rough Terrain Crane

Powerful lifting and tough design
SR Rough Terrain Crane

Roughter

SR-800L



- L : 12,500mm
W : 2,990mm
H : 3,680mm
- 39,800kg
- 80t x 1.7m
(10.0m Boom)
- 10.0~44.5m
(6 sections)
- 8.3~13.2m
(2 sections)
7~60°
- 7.6m (6 sections)
- 49km/h
- ACS MS-200

SR-500L



- L : 13,030mm
W : 2,980mm
H : 3,595mm
- 33,970kg
(with standard tires)
- 51t x 2.5m
(10.7m Boom)
- 10.7~35.0m
(4 sections)
- 8.8m, 15.2m
(2 sections)
5°, 25°, 45°
- 7.0m (4 sections)
- 48km/h
- ACS MS-200

SR-700LII



- L : 12,500mm
W : 2,990mm
H : 3,680mm
- 39,800kg
- 70t x 2.5m
(10.0m Boom)
- 10.0~44.5m
(6 sections)
- 8.3~13.2m
(2 sections)
7~60°
- 7.6m (6 sections)
- 49km/h
- ACS MS-200

SR-300LX



- L : 11,360mm
W : 2,620mm
H : 3,475mm
- 26,990kg
- 30t x 3.0m
(9.35m Boom)
- 9.35~30.5m
(4 sections)
- 7.9m, 13.0m
(2 sections)
5°, 25°, 45°
- 6.6m (5 sections)
- 49km/h
- ACS MS-200

SR-500LX

EJIB



- L : 12,760mm
W : 2,900mm
H : 3,880mm
- 37,075kg
(with standard tires)
- 51t x 2.5m
(10.8m Boom)
- 10.8~42.0m
(5 sections)
- 9.4m~13.7m
(2 sections)
5~60°
- 7.0m (4 sections)
- 45km/h
- ACS MS-230C

SR-300R

EJIB



- L : 11,565mm
W : 2,620mm
H : 3,475mm
- 26,515kg
- 30t x 3.0m
(9.35m Boom)
- 9.35~30.5m
(4 sections)
- 8.7, 13.1m
(2 sections)
5~60°
- 6.6m (5 sections)
- 49km/h
- ACS MS-200

Easy Jib mounting by newly developed EJIB system
Efficient Jib operation is available



Cityrange Crane

Compact and versatile
High performance CITYRANGE Crane

CITYRANGE



All Terrain Crane

Advanced All Terrain Crane
Various operations with latest KATO technologies

ALLTERR

CR-250RV

EJIBS



- L : 9,195mm
W : 2,395mm
H : 3,495mm
- 23,795kg
- MAX 25t×2.8m
(6.7m Boom)
- 6.7~29.0m
(6 sections)
- SL 5.3m~8.2m
(2 sections)
7°~60°
- 6.0m (5 sections)
- 54km/h
- ACS MS-230D
- 1.0m
2 positions
(high/low)

CR-200Rf



- L : 8,710mm
W : 2,290mm
H : 3,245mm
- 19,755kg
- MAX 20t×2.5m
(6.5m Boom)
- 6.5~28.0m
(6 sections)
- PJ 4.0m, 5.8m
(2 sections)
7°~60°
- 5.4m (5 sections)
- 55km/h
- ACS MS-250
- 1.0m
2 positions
(high/low)

CR-130RV



- L : 7,465mm
W : 1,995mm
H : 2,870mm
- 13,825kg
- MAX 13t×1.7m
(5.3m Boom)
- 5.3~24.0m
(6 sections)
- PJ 3.6m, 5.5m
(2 sections)
5°~60°
- 4.75m (5 sections)
- 55km/h
- ACS MS-250A
- 0.8m
2 positions
(high/low)

KA-3000RX



Traveling position on work sites only.

- L : 17,760mm
W : 2,990mm
H : 4,100mm
(Work site driving position)
- 44,370kg
(Only carrier)
- MAX 300t×2.5m
(14.4m Boom)
(Heavy load hoisting device)
- 14.4~55.0m
(5 sections)
- SL 10.85~35.0m
(4 sections)
0°~60°
- HL 13m, 22m, 31m,
40m, 47m, 54m
(6 sections)
10°~60°
- 9.4m (5 sections)
- 75km/h
(Only carrier)
- ACS MS-270

KA-1300RX



Traveling position on work sites only.

- L : 15,400mm
W : 2,990mm
H : 4,000mm
(Work site driving position)
- 36,620kg
(Only carrier)
- MAX 130t×2.5m
(11.8m Boom)
(Heavy load hoisting device)
- 11.8~52.0m
(6 sections)
- SL 9.2~26.6m
(4 sections)
2°(5°)~60°
- 8.4m (6 sections)
- 75km/h
(Only carrier)
- ACS MS-270

KA-1100RX



Traveling position on work sites only.

- L : 13,200mm
W : 2,750mm
H : 3,790mm
- 48,000kg
- MAX 110t×2.0m
(11.1m Boom)
(Heavy load hoisting device)
- 11.1~51.3m
(6 sections)
- SL 8.8~20.4m
(3 sections)
2°(5°)~60°
- 7.2m (5 sections)
- 75km/h
- ACS MS-280



Crawler Crane

Tough, reliable performance
High lifting capacity

CCH2500-6



- 242kW/2,000min⁻¹
- MAX 250t×5.2m
- (STD) 18.0~72.0m
(Light) 72.0~93.0m
- 13.0~37.0m

CCH1000-6



- 179kW/2,000min⁻¹
- MAX 100t×4.0m
- 13.0~61.0m
- 10.0~22.0m

CCH550-3II



- 149kW/2,100min⁻¹
- MAX 55t×3.0m
- 9.0~51.0m
- 6.0~15.0m

CCH550T-3



- 179kW/2,000min⁻¹
(Tier3)
- MAX 55t×3.0m
- 11.3~34.4m



Excavator

High-performance and high-power
Environmentally-friendly excavator

REGZM

HD820-8



- 120.7kW/2,000min⁻¹
- 21,100kg
LC:21,800kg
- 0.45~1.1m³
- 6,700mm
LC:6,690mm
- APC7
- Lineup
- LC

HD1025-7



- 121.6kW/1,900min⁻¹
- 25,000kg
LC:25,800kg
- 0.55~1.4m³
- 7,000mm
- APC7
- Lineup
- LC

HD512-7



- 76.4kW/2,000min⁻¹
- 12,900kg
LC:13,400kg
Dozer:13,800kg
- 0.25~0.60m³
- 5,590mm
- APC7
- Lineup
- LC

HD2050-7



HD512-7





Excavator

REGZM

Environmentally-friendly model
Global standard working performance

HD823_{MR}-8

MINI RADIUS



- 120.7kW/2,000min⁻¹
- 23,100kg
LC: 24,000kg
- 0.45–1.1m³
- 6,700mm
LC: 6,690mm
- APC7
- Lineup
- LC

HD514_{MR}-7

MINI RADIUS



- 76.4kW/2,000min⁻¹
- 14,100kg
LC: 14,500kg
Dozer: 15,100kg
- 0.25–0.60m³
- 5,540mm
- APC7
- Lineup
- LC

HD308_{US}-7

ULTRA SHORT TAIL SWING



- 40.8kW/2,000min⁻¹
- 7,470kg
Dozer: 7,940kg
- 0.12–0.34m³
- 4,120mm
- APC300
- Lineup
- LC



Mini Excavator

High quality, great performance
Environmentally-friendly mini-midi excavator

HD85V5



- 42.7kW/2,100min⁻¹
- 8,100kg
- 0.11–0.28m³
- 4,020mm

HD60V5



- 32.4kW/2,400min⁻¹
- 5,370kg
- 0.08–0.18m³
- 3,800mm

HD50V5



- 32.4kW/2,400min⁻¹
- 4,650kg
- 0.08–0.16m³
- 3,330mm

HD35V5



- 17.2kW/2,200min⁻¹
- 3,450kg
- 0.055–0.12m³
- 3,060mm



Mini Excavator

High quality, great performance
Environmentally-friendly mini-midi excavator

HD30V5



- 17.2kW/2,200min⁻¹
- 3,020kg
- 0.04–0.10m³
- 2,700mm

HD25V5



- 17.6kW/2,400min⁻¹
- 2,500kg
- 0.04–0.09m³
- 2,440mm

HD17V5



- 10.5kW/2,300min⁻¹
- 1,780kg
- 0.024–0.055m³
- 2,190mm

HD35N5



- 17.2kW/2,200min⁻¹
- 3,220kg
- 0.055–0.12m³
- 3,030mm

HD55N4



- 47.6kW/2,400min⁻¹
- 5,350kg
- 0.11–0.19m³
- 3,850mm



Crawler Carrier

Excellent driving force, comfortable operation



IC120-2

- 224kW/2,200min⁻¹
- 14,020kg
- 11,000kg



IC100-5

- 191kW/2,000min⁻¹
- 11,570kg
- 10,000kg



IC75-5

- 140kW/2,400min⁻¹
- 9,760kg
- 7,500kg



IC55

- 78.3kW/2,400min⁻¹
- 6,440kg
- 5,000kg



Full-Rotating Crawler Carrier



Safe, compact and easy-to-use
full-rotating crawler carrier.

IC70R

- 140kW/2,200min⁻¹
- 11,525kg
- 7,000kg



IC110R

- 191kW/2,000min⁻¹
- 16,610kg
- 11,000kg





Vacuum Crawler

IC

High performance and fuss-free maintenance
Vacuum Crawler

IC75MV



	168kW/2,200min ⁻¹
	12,300kg
	4,700kg
	2.5-4.5m ³
	35m ³ /min



Vacuum Truck

MultiVac

Simple mechanism and easy to maintain Multi-purpose Vacuum Truck

MV-2200S

	22t
	11.3m ³
	50m ³ /min



MV-600S

	14.5t
	6.3m ³
	30m ³ /min



MV-400S

	8t
	2.7m ³
	30m ³ /min



Earth Drilling Rig

CITY DRILL

High-performance Earth Drilling Rig
Various digging methods are available

KE-1500Ⅲ



	98kW/2,000min ⁻¹
	23t
	43m
	1.5m

KB-1500RⅡ



	205kW/2,000min ⁻¹
	56.5t
	45m
	1.5m

PE-650



	98kW/2,000min ⁻¹
	19t
	14.5m
	1.2m



Street Sweeper

Street-Master

High-performance with compact body
Low noise and efficient Street Sweeper

HS-800W

	98kW/2,000min ⁻¹
	6.4m ³
	3.0-3.5t
	30km/h
	Left: 2.5m Right: 2.5m Full: 3.5m



HS-400W

	40.3kW/2,100min ⁻¹
	3.4m ³
	1.6-2.0t
	20km/h
	Left: 1.8m Right: 1.8m Full: 2.4m



Snow Sweeper

Powerful brush and blow system introduced
Speedy snow removal operation

S-250CIX



	270kW/2,100min ⁻¹
	2.5m
	40km/h



COMPACT TRACK LOADER

Compact, Powerful and Versatile!

CL35-4F

	46.3kW/2,700min ⁻¹
	canopy: 3,540kg cabin: 3,600kg
	0.36m ³

