



10.85m — 35m

スーパーラフリングジブ【50mブーム時】

SA性能 50mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.4	21.0	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.9	21.0	76.3	21.0	78.1	20.0	79.2	18.6	80.1	17.7
22.0	72.9	20.0	74.3	19.6	76.2	18.3	77.2	17.4	78.0	16.8
24.0	70.9	18.4	72.4	17.8	74.2	16.7	75.2	16.0	75.8	15.7
26.0	68.9	16.4	70.4	16.0	72.1	15.3	73.2	14.8	73.6	14.6
28.0	66.9	14.7	68.3	14.5	70.1	14.1	71.1	13.7	71.4	13.5
30.0	64.7	13.3	66.3	13.1	68.0	13.0	68.9	12.6	69.1	12.6
32.0	62.6	11.9	64.1	11.8	65.8	12.0	66.7	11.7	66.7	11.7
34.0	60.4	10.7	61.9	10.7	63.4	10.8	64.5	10.9		
36.0	58.1	9.5	59.6	9.7	61.0	9.8	61.9	9.8		
38.0	55.8	8.3	57.3	8.5	58.5	8.8	59.3	8.9		
40.0	53.3	7.2	54.8	7.4	55.9	7.9	56.6	8.0		
42.0	50.8	6.1	52.2	6.5	53.2	6.9	53.8	7.0		
44.0	48.2	4.8	49.4	5.2	50.4	5.7	50.8	5.8		
46.0	45.5	3.7	46.5	4.0	47.5	4.4				
48.0			43.5	2.9	44.3	3.2				
危険角度 (°)		43		43		43		48		65
標準フック		24t		24t		24t		24t		24t
フック質量 (t)		0.88		0.88		0.88		0.88		0.88
巻掛本数		2		2		2		2		2

SA性能 50mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	71.2	12.0	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	69.5	12.0	72.5	12.0	75.1	12.0	76.9	12.0	77.9	12.0
28.0	67.9	12.0	70.9	12.0	73.4	12.0	75.1	12.0	75.9	12.0
30.0	66.2	12.0	69.2	12.0	71.7	12.0	73.0	11.8	73.8	11.6
32.0	64.3	11.7	67.2	11.9	69.6	11.3	70.9	11.0	71.6	10.8
34.0	62.4	10.7	65.3	10.9	67.6	10.5	68.8	10.2	69.4	10.1
36.0	60.4	9.7	63.3	9.9	65.4	9.7	66.6	9.5	67.1	9.4
38.0	58.4	8.8	61.2	9.1	63.2	9.0	64.3	8.8		
40.0	56.3	7.9	59.0	8.2	61.0	8.4	62.0	8.3		
42.0	54.1	6.9	56.8	7.4	58.6	7.5	59.6	7.7		
44.0	51.7	6.0	54.6	6.5	56.1	6.7	57.0	6.9		
46.0	49.3	4.8	52.0	5.6	53.5	6.0	54.3	6.2		
48.0	46.7	3.8	49.3	4.6	50.7	5.1	51.4	5.3		
50.0	44.0	2.8	46.5	3.5	47.8	4.0				
52.0			43.6	2.5	44.7	2.9				
危険角度 (°)		43		43		43		48.5		65
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SA性能 50mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	73.0	12.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.6	12.0	75.4	12.0	78.6	11.9	81.2	10.7	82.8	9.9
28.0	70.1	12.0	73.9	12.0	76.9	11.4	79.4	10.5	80.9	9.7
30.0	68.6	12.0	72.4	12.0	75.2	11.0	77.6	10.1	79.0	9.6
32.0	67.1	12.0	70.6	11.1	73.5	10.4	75.8	9.6	77.1	9.2
34.0	65.3	11.0	68.8	10.3	71.7	9.7	73.9	9.2	75.0	8.8
36.0	63.5	10.0	67.0	9.5	69.8	9.0	71.9	8.7	72.7	8.5
38.0	61.6	9.2	65.1	8.8	67.8	8.4	69.8	8.2	70.5	8.1
40.0	59.7	8.4	63.2	8.2	65.8	7.8	67.6	7.6	68.1	7.6
42.0	57.8	7.5	61.2	7.6	63.7	7.3	65.4	7.1		
44.0	55.8	6.6	59.2	6.9	61.5	6.8	63.1	6.7		
46.0	53.5	5.8	57.0	6.1	59.3	6.3	60.7	6.2		
48.0	51.3	5.0	54.7	5.5	57.0	5.6	58.2	5.8		
50.0	48.9	4.0	52.4	4.8	54.6	5.0	55.5	5.3		
52.0	46.4	3.1	50.0	4.0	52.0	4.6	52.7	4.7		
54.0	43.9	2.3	47.4	3.1	49.3	3.7	49.7	4.0		
56.0			44.7	2.3	46.5	2.8				
危険角度 (°)		43		43		43.5		48.5		66
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SA性能 50mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	73.0	10.0	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.6	10.0	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	70.3	10.0	74.8	9.9	78.3	8.8	81.6	8.0	83.7	7.2
32.0	68.9	10.0	73.2	9.4	76.8	8.5	80.0	7.8	81.8	7.1
34.0	67.5	10.0	71.6	8.9	75.2	8.2	78.3	7.6	79.9	7.1
36.0	65.8	9.4	70.0	8.5	73.4	7.9	76.5	7.5	78.0	7.0
38.0	64.1	8.8	68.3	8.1	71.7	7.7	74.6	7.2	75.9	6.9
40.0	62.4	8.3	66.6	7.8	69.9	7.4	72.7	6.9	73.9	6.6
42.0	60.6	7.6	64.8	7.2	68.1	6.9	70.7	6.6	71.7	6.4
44.0	58.8	6.8	62.9	6.7	66.2	6.4	68.7	6.3	69.4	6.1
46.0	57.0	6.1	61.0	6.2	64.3	6.0	66.6	5.9	67.1	5.8
48.0	55.0	5.5	59.1	5.7	62.3	5.6	64.5	5.5		
50.0	53.0	4.8	57.1	5.1	60.3	5.2	62.1	5.1		
52.0	50.9	4.1	54.9	4.6	58.0	4.8	59.6	4.8		
54.0	48.7	3.3	52.7	4.1	55.6	4.3	57.0	4.5		
56.0	46.5	2.5	50.4	3.6	53.1	3.8	54.2	4.0		
58.0	44.1	1.8	48.0	2.8	50.5	3.5	51.3	3.6		
60.0			45.5	2.0	47.7	2.6				
62.0					44.8	1.8				
危険角度 (°)		43		43		43.5		48.5		66
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

SA性能 50mブーム + 2m + 30mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								



# 10.85m — 35m

# スーパラフィンギジブ【50mブーム時】

SB性能 50mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.4	21.0	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.9	21.0	76.3	21.0	78.1	20.0	79.2	18.6	80.1	17.7
22.0	72.9	20.0	74.3	19.6	76.2	18.3	77.2	17.4	78.0	16.8
24.0	70.9	18.4	72.4	17.8	74.2	16.7	75.2	16.0	75.8	15.7
26.0	68.9	16.4	70.4	16.0	72.1	15.3	73.2	14.8	73.6	14.6
28.0	66.9	14.7	68.3	14.5	70.1	14.1	71.1	13.7	71.4	13.5
30.0	64.7	13.3	66.3	13.1	68.0	13.0	68.9	12.6	69.1	12.6
32.0	62.6	11.9	64.1	11.8	65.8	12.0	66.7	11.7	66.7	11.7
34.0	60.4	10.7	61.9	10.7	63.4	10.8	64.5	10.9		
36.0	58.0	9.1	59.6	9.7	61.0	9.8	61.9	9.8		
38.0	55.6	7.4	57.2	8.0	58.5	8.7	59.3	8.9		
40.0	53.2	6.0	54.7	6.5	55.8	7.1	56.5	7.4		
42.0	50.6	4.6	52.0	5.1	53.0	5.6	53.6	5.8		
44.0	48.0	3.4	49.2	3.8	50.2	4.3	50.5	4.4		
46.0			46.2	2.7	47.2	3.0				
危険角度 (°)	45.5		45.5		46		48		65	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SB性能 50mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	71.2	12.0	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	69.5	12.0	72.5	12.0	75.1	12.0	76.9	12.0	77.9	12.0
28.0	67.9	12.0	70.9	12.0	73.4	12.0	75.1	12.0	75.9	12.0
30.0	66.2	12.0	69.2	12.0	71.7	12.0	73.0	11.8	73.8	11.6
32.0	64.3	11.7	67.2	11.9	69.6	11.3	70.9	11.0	71.6	10.8
34.0	62.4	10.7	65.3	10.9	67.6	10.5	68.8	10.2	69.4	10.1
36.0	60.4	9.7	63.3	9.9	65.4	9.7	66.6	9.5	67.1	9.4
38.0	58.3	8.6	61.2	9.1	63.2	9.0	64.3	8.8		
40.0	56.1	7.1	59.0	8.2	61.0	8.4	62.0	8.3		
42.0	53.9	5.8	56.7	6.8	58.6	7.5	59.6	7.7		
44.0	51.5	4.6	54.4	5.6	56.0	6.3	57.0	6.7		
46.0	49.0	3.5	51.7	4.4	53.3	5.0	54.1	5.3		
48.0	46.3	2.5	49.0	3.3	50.5	3.8	51.2	4.1		
50.0			46.3	2.3	47.6	2.8				
危険角度 (°)	45.5		45.5		46		48.5		65	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SB性能 50mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	73.0	12.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.6	12.0	75.4	12.0	78.6	11.9	81.2	10.7	82.8	9.9
28.0	70.1	12.0	73.9	12.0	76.9	11.4	79.4	10.5	80.9	9.7
30.0	68.6	12.0	72.4	12.0	75.2	11.0	77.6	10.1	79.0	9.6
32.0	67.1	12.0	70.6	11.1	73.5	10.4	75.8	9.6	77.1	9.2
34.0	65.3	11.0	68.8	10.3	71.7	9.7	73.9	9.2	75.0	8.8
36.0	63.5	10.0	67.0	9.5	69.8	9.0	71.9	8.7	72.7	8.5
38.0	61.6	9.2	65.1	8.8	67.8	8.4	69.8	8.2	70.5	8.1
40.0	59.7	8.3	63.2	8.2	65.8	7.8	67.6	7.6	68.1	7.6
42.0	57.7	7.0	61.2	7.6	63.7	7.3	65.4	7.1		
44.0	55.6	5.8	59.2	6.9	61.5	6.8	63.1	6.7		
46.0	53.3	4.7	56.9	5.9	59.3	6.3	60.7	6.2		
48.0	51.0	3.7	54.6	4.8	57.0	5.6	58.2	5.8		
50.0	48.7	2.8	52.2	3.8	54.5	4.6	55.5	5.0		
52.0	46.3	1.9	49.7	2.9	51.8	3.6	52.6	3.9		
54.0			47.1	2.0	49.1	2.6	49.5	2.8		
危険角度 (°)	45.5		45.5		46.5		48.5		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SB性能 50mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	73.0	10.0	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.6	10.0	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	70.3	10.0	74.8	9.9	78.3	8.8	81.6	8.0	83.7	7.2
32.0	68.9	10.0	73.2	9.4	76.8	8.5	80.0	7.8	81.8	7.1
34.0	67.5	10.0	71.6	8.9	75.2	8.2	78.3	7.6	79.9	7.1
36.0	65.8	9.4	70.0	8.5	73.4	7.9	76.5	7.5	78.0	7.0
38.0	64.1	8.8	68.3	8.1	71.7	7.7	74.6	7.2	75.9	6.9
40.0	62.4	8.3	66.6	7.8	69.9	7.4	72.7	6.9	73.9	6.6
42.0	60.6	7.6	64.8	7.2	68.1	6.9	70.7	6.6	71.7	6.4
44.0	58.8	6.8	62.9	6.7	66.2	6.4	68.7	6.3	69.4	6.1
46.0	56.9	5.7	61.0	6.2	64.3	6.0	66.6	5.9	67.1	5.8
48.0	54.8	4.7	59.1	5.7	62.3	5.6	64.5	5.5		
50.0	52.7	3.8	57.1	5.1	60.3	5.2	62.1	5.1		
52.0	50.6	3.0	54.8	4.2	58.0	4.8	59.6	4.8		
54.0	48.4	2.2	52.5	3.3	55.6	4.2	57.0	4.5		
56.0	46.2	1.4	50.2	2.5	53.0	3.3	54.1	3.7		
58.0			47.7	1.7	50.3	2.4	51.0	2.8		
60.0					47.5	1.6				
危険角度 (°)	45.5		46		46.5		48.5		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SB性能 50mブーム + 2m + 30mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								



# 10.85m — 35m

# スーパーラフティングジブ【50mブーム時】

**SC性能 50mブーム + 2m + 10.85mSLジブ**

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.4	21.0	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.9	21.0	76.3	21.0	78.1	20.0	79.2	18.6	80.1	17.7
22.0	72.9	20.0	74.3	19.6	76.2	18.3	77.2	17.4	78.0	16.8
24.0	70.9	18.4	72.4	17.8	74.2	16.7	75.2	16.0	75.8	15.7
26.0	68.9	16.4	70.4	16.0	72.1	15.3	73.2	14.8	73.6	14.6
28.0	66.9	14.7	68.3	14.5	70.1	14.1	71.1	13.7	71.4	13.5
30.0	64.7	13.3	66.3	13.1	68.0	13.0	68.9	12.6	69.1	12.6
32.0	62.5	11.1	64.1	11.8	65.8	12.0	66.7	11.7	66.7	11.7
34.0	60.1	9.1	61.8	9.8	63.4	10.7	64.5	10.9		
36.0	57.8	7.4	59.4	8.0	60.9	8.8	61.8	9.2		
38.0	55.4	5.8	56.9	6.4	58.3	7.1	59.1	7.4		
40.0	52.9	4.4	54.4	5.0	55.6	5.5	56.3	5.8		
42.0	50.4	3.2	51.7	3.6	52.8	4.2	53.3	4.4		
44.0					50.0	2.9	50.2	3.0		
危険角度 (°)		48		49		49		49		65
標準フック		24t		24t		24t		24t		24t
フック質量 (t)		0.88		0.88		0.88		0.88		0.88
巻掛本数		2		2		2		2		2

**SC性能 50mブーム + 2m + 15mSLジブ**

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	71.2	12.0	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	69.5	12.0	72.5	12.0	75.1	12.0	76.9	12.0	77.9	12.0
28.0	67.9	12.0	70.9	12.0	73.4	12.0	75.1	12.0	75.9	12.0
30.0	66.2	12.0	69.2	12.0	71.7	12.0	73.0	11.8	73.8	11.6
32.0	64.3	11.7	67.2	11.9	69.6	11.3	70.9	11.0	71.6	10.8
34.0	62.3	10.2	65.3	10.9	67.6	10.5	68.8	10.2	69.4	10.1
36.0	60.2	8.5	63.3	9.9	65.4	9.7	66.6	9.5	67.1	9.4
38.0	58.0	7.0	61.0	8.2	63.2	9.0	64.3	8.8		
40.0	55.8	5.6	58.8	6.7	60.9	7.7	62.0	8.3		
42.0	53.6	4.3	56.4	5.4	58.4	6.2	59.4	6.7		
44.0	51.2	3.2	54.0	4.2	55.8	4.9	56.8	5.3		
46.0	48.7	2.2	51.4	3.0	53.1	3.7	54.0	4.0		
48.0					50.4	2.6	51.0	2.8		
危険角度 (°)		48		49		49		49		65
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

**SC性能 50mブーム + 2m + 20mSLジブ**

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	73.0	12.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.6	12.0	75.4	12.0	78.6	11.9	81.2	10.7	82.8	9.9
28.0	70.1	12.0	73.9	12.0	76.9	11.4	79.4	10.5	80.9	9.7
30.0	68.6	12.0	72.4	12.0	75.2	11.0	77.6	10.1	79.0	9.6
32.0	67.1	12.0	70.6	11.1	73.5	10.4	75.8	9.6	77.1	9.2
34.0	65.3	11.0	68.8	10.3	71.7	9.7	73.9	9.2	75.0	8.8
36.0	63.4	9.7	67.0	9.5	69.8	9.0	71.9	8.7	72.7	8.5
38.0	61.4	8.2	65.1	8.8	67.8	8.4	69.8	8.2	70.5	8.1
40.0	59.4	6.8	63.2	8.2	65.8	7.8	67.6	7.6	68.1	7.6
42.0	57.3	5.5	61.1	7.0	63.7	7.3	65.4	7.1		
44.0	55.2	4.4	58.9	5.7	61.5	6.8	63.1	6.7		
46.0	53.0	3.4	56.6	4.6	59.2	5.6	60.7	6.2		
48.0	50.7	2.4	54.3	3.6	56.8	4.4	58.1	5.0		
50.0			51.9	2.6	54.2	3.4	55.3	3.8		
52.0			49.4	1.7	51.6	2.4	52.4	2.7		
危険角度 (°)		49		49		49		49.5		66
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

**SC性能 50mブーム + 2m + 25mSLジブ**

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	73.0	10.0	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.6	10.0	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	70.3	10.0	74.8	9.9	78.3	8.8	81.6	8.0	83.7	7.2
32.0	68.9	10.0	73.2	9.4	76.8	8.5	80.0	7.8	81.8	7.1
34.0	67.5	10.0	71.6	8.9	75.2	8.2	78.3	7.6	79.9	7.1
36.0	65.8	9.4	70.0	8.5	73.4	7.9	76.5	7.5	78.0	7.0
38.0	64.1	8.8	68.3	8.1	71.7	7.7	74.6	7.2	75.9	6.9
40.0	62.3	7.8	66.6	7.8	69.9	7.4	72.7	6.9	73.9	6.6
42.0	60.3	6.6	64.8	7.2	68.1	6.9	70.7	6.6	71.7	6.4
44.0	58.4	5.4	62.9	6.7	66.2	6.4	68.7	6.3	69.4	6.1
46.0	56.5	4.4	61.0	6.0	64.3	6.0	66.6	5.9	67.1	5.8
48.0	54.4	3.5	58.9	4.9	62.3	5.6	64.5	5.5		
50.0	52.4	2.6	56.7	3.9	60.2	5.0	62.1	5.1		
52.0	50.3	1.8	54.5	3.0	57.8	4.0	59.5	4.7		
54.0			52.2	2.2	55.3	3.1	56.7	3.6		
56.0			49.9	1.4	52.7	2.2	53.8	2.7		
58.0					50.1	1.4	50.7	1.7		
危険角度 (°)		49		49		49		49.5		66
標準フック		12t		12t		12t		12t		12t
フック質量 (t)		0.42		0.42		0.42		0.42		0.42
巻掛本数		1		1		1		1		1

**SC性能 50mブーム + 2m + 30mSLジブ**

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0	78.0	8.5	83.3	8.5						
22.0	76.8	8.5	82.1	8.5						
24.0	75.6	8.5	80.							



## 10.85m — 35m

## スーパーラフィングジブ 【50mブーム時】

SD性能 50mブーム+2m+10.85mSLジブ

オフセット	5'	15'	30'	45'	60'					
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)					
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.4	21.0	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.9	21.0	76.3	21.0	78.1	20.0	79.2	18.6	80.1	17.7
22.0	72.9	20.0	74.3	19.6	76.2	18.3	77.2	17.4	78.0	16.8
24.0	70.9	18.4	72.4	17.8	74.2	16.7	75.2	16.0	75.8	15.7
26.0	68.9	16.4	70.4	16.0	72.1	15.3	73.2	14.8	73.6	14.6
28.0	66.7	13.7	68.3	14.5	70.1	14.1	71.1	13.7	71.4	13.5
30.0	64.5	11.3	66.1	12.1	68.0	13.0	68.9	12.6	69.1	12.6
32.0	62.2	9.2	63.8	9.9	65.6	10.9	66.7	11.5	66.7	11.7
34.0	59.9	7.3	61.5	8.0	63.2	8.9	64.2	9.4		
36.0	57.5	5.7	59.1	6.3	60.6	7.1	61.5	7.5		
38.0	55.1	4.2	56.7	4.8	58.0	5.5	58.8	5.8		
40.0	52.7	2.9	54.2	3.4	55.4	4.0	56.0	4.3		
42.0					52.6	2.7	53.1	2.9		
危険角度 (°)	51	52	52	52	52	65				
標準フック	24t	24t	24t	24t	24t	24t				
フック質量 (t)	0.88	0.88	0.88	0.88	0.88	0.88				
巻掛本数	2	2	2	2	2	2				

SD性能 50mブーム+2m+15mSLジブ

オフセット	0'	15'	30'	45'	60'					
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)					
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	71.2	12.0	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	69.5	12.0	72.5	12.0	75.1	12.0	76.9	12.0	77.9	12.0
28.0	67.9	12.0	70.9	12.0	73.4	12.0	75.1	12.0	75.9	12.0
30.0	66.2	12.0	69.2	12.0	71.7	12.0	73.0	11.8	73.8	11.6
32.0	64.1	10.2	67.2	11.9	69.6	11.3	70.9	11.0	71.6	10.8
34.0	62.0	8.4	65.1	9.9	67.6	10.5	68.8	10.2	69.4	10.1
36.0	59.9	6.8	63.0	8.2	65.4	9.3	66.6	9.5	67.1	9.4
38.0	57.7	5.3	60.8	6.6	63.0	7.7	64.3	8.3		
40.0	55.5	4.1	58.5	5.2	60.6	6.1	61.8	6.7		
42.0	53.3	2.9	56.1	3.9	58.2	4.8	59.2	5.3		
44.0			53.7	2.8	55.6	3.5	56.6	3.9		
46.0					53.0	2.4	53.8	2.7		
危険角度 (°)	51	52	52	52	52	65				
標準フック	12t	12t	12t	12t	12t	12t				
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42				
巻掛本数	1	1	1	1	1	1				

SD性能 50mブーム+2m+20mSLジブ

オフセット	0'	15'	30'	45'	60'					
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)					
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	73.0	12.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.6	12.0	75.4	12.0	78.6	11.9	81.2	10.7	82.8	9.9
28.0	70.1	12.0	73.9	12.0	76.9	11.4	79.4	10.5	80.9	9.7
30.0	68.6	12.0	72.4	12.0	75.2	11.0	77.6	10.1	79.0	9.6
32.0	67.0	11.5	70.6	11.1	73.5	10.4	75.8	9.6	77.1	9.2
34.0	65.0	9.6	68.8	10.3	71.7	9.7	73.9	9.2	75.0	8.8
36.0	63.1	8.0	67.0	9.5	69.8	9.0	71.9	8.7	72.7	8.5
38.0	61.1	6.6	65.0	8.3	67.8	8.4	69.8	8.2	70.5	8.1
40.0	59.0	5.3	62.9	6.8	65.8	7.8	67.6	7.6	68.1	7.6
42.0	57.0	4.1	60.7	5.5	63.6	6.7	65.4	7.1		
44.0	54.9	3.0	58.6	4.3	61.3	5.5	63.0	6.2		
46.0	52.7	2.0	56.3	3.3	58.9	4.3	60.5	4.9		
48.0			54.0	2.3	56.5	3.2	57.9	3.7		
50.0					54.0	2.2	55.1	2.6		
危険角度 (°)	51	52	52	52.5	66					
標準フック	12t	12t	12t	12t	12t	12t				
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42				
巻掛本数	1	1	1	1	1	1				

SD性能 50mブーム+2m+25mSLジブ

オフセット	0'	15'	30'	45'	60'					
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)					
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	73.0	10.0	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.6	10.0	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	70.3	10.0	74.8	9.9	78.3	8.8	81.6	8.0	83.7	7.2
32.0	68.9	10.0	73.2	9.4	76.8	8.5	80.0	7.8	81.8	7.1
34.0	67.5	10.0	71.6	8.9	75.2	8.2	78.3	7.6	79.9	7.1
36.0	65.7	9.1	70.0	8.5	73.4	7.9	76.5	7.5	78.0	7.0
38.0	63.8	7.6	68.3	8.1	71.7	7.7	74.6	7.2	75.9	6.9
40.0	61.9	6.3	66.6	7.8	69.9	7.4	72.7	6.9	73.9	6.6
42.0	59.9	5.1	64.7	6.9	68.1	6.9	70.7	6.6	71.7	6.4
44.0	58.0	4.0	62.6	5.7	66.2	6.4	68.7	6.3	69.4	6.1
46.0	56.1	3.1	60.6	4.6	64.3	6.0	66.6	5.9	67.1	5.8
48.0	54.1	2.2	58.5	3.6	62.1	4.9	64.5	5.5		
50.0	52.0	1.4	56.4	2.7	59.9	3.8	61.9	4.6		
52.0			54.2	1.9	57.5	2.9	59.2	3.5		
54.0					55.0	2.0	56.4	2.5		
56.0							53.5	1.6		
危険角度 (°)	51	52.5	53	53	53	66				
標準フック	12t	12t	12t	12t	12t	12t				
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42				
巻掛本数	1	1	1	1	1	1				

SD性能 50mブーム+2m+30mSLジブ

オフセット	0'	15'	30'	45'	60'					
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)					
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0	78.0	8.5	83.3	8.5						
22.0	76.8	8.5	82.1	8.5						
24.0	75.6	8.5	80.9	8.5						
26.0	74.4	8.5	79.7	8.5	84.3	7.8				
28.0	73.2	8.5	78.4	8.5	82.9	7.5				
30.0	71.9	8.5	77.0	8.4	81.4	7.3				
32.0	70.7	8.5	75.6	8.0	80.0	7.0	83.5	5.9		
34.0	69.4	8.5	74.2	7.7	78.5	6.8	81.9	5.8	84.4	5.2
36.0	68.0	8.1	72.7	7.3	77.0	6.5	80.3	5.7	82.6	5.1
38.0	66.5	7.5	71.2	6.9	75.5	6.3	78.7	5.6	80.8	5.1
40.0	65.0	7.1	69.7	6.5	73.9	6.1	77.0	5.5	78.9	5.0
42.0	63.2	6.0	68.2	6.2	72.3	5.9	75.3	5.4	77.0	5.0
44.0	61.4	5.0	66.6	6.0	70.6	5.7	73.6	5.3	75.1	5.0
46.0	59.6	4.0	64.9	5.7	68.9	5.5	71.6	5.2	72.9	4.9
48.0	57.7	3.1	62.9	4.8	67.1	5.4	69.6	5.1	70.6	4.9
50.0	55.7	2.3	60.9	3.9	65.3	5.0	67.6	4.8	68.3	4.7
52.0	53.6	1.5	58.9	3.0	63.2	4.3	65.5	4.6		
54.0			56.8	2.2	60.9	3.4	63.3	4.3		
56.0			54.6	1.5	58.5	2.6	60.6	3.3		
58.0					56.1	1.8	57.9	2.4		
60.0							55.1	1.6		
危険角度 (°)	52	53	54	54	66					
標準フック	12t	12t	12t	12t	12t					



# 10.85m — 35m

# スーパーラフィングジブ【50mブーム時】

SE性能 50mブーム+2m+10.85mSLジブ										
オフセット	5°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.4	21.0	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.9	21.0	76.3	21.0	78.1	20.0	79.2	18.6	80.1	17.7
22.0	72.9	19.4	74.3	19.6	76.2	18.3	77.2	17.4	78.0	16.8
24.0	70.7	15.9	72.3	17.0	74.2	16.7	75.2	16.0	75.8	15.7
26.0	68.5	12.9	70.1	13.9	72.1	15.3	73.2	14.8	73.6	14.6
28.0	66.3	10.4	67.9	11.3	69.9	12.5	71.0	13.4	71.4	13.5
30.0	64.0	8.2	65.7	9.0	67.5	10.1	68.7	10.9	68.9	11.2
32.0	61.8	6.3	63.4	7.1	65.2	8.0	66.2	8.7	66.3	8.9
34.0	59.4	4.6	61.1	5.3	62.8	6.2	63.7	6.7		
36.0	57.1	3.1	58.7	3.8	60.3	4.5	61.1	5.0		
38.0					57.7	3.0	58.4	3.4		
危険角度 (°)	55		57		57		57		65	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SE性能 50mブーム+2m+15mSLジブ										
オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	71.2	12.0	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	69.5	12.0	72.5	12.0	75.1	12.0	76.9	12.0	77.9	12.0
28.0	67.8	11.4	70.9	12.0	73.4	12.0	75.1	12.0	75.9	12.0
30.0	65.7	9.3	69.0	11.1	71.7	12.0	73.0	11.8	73.8	11.6
32.0	63.6	7.4	66.8	9.0	69.5	10.4	70.9	11.0	71.6	10.8
34.0	61.5	5.7	64.7	7.2	67.2	8.5	68.7	9.4	69.4	9.9
36.0	59.4	4.2	62.6	5.6	65.0	6.8	66.3	7.6	66.9	7.9
38.0	57.2	2.9	60.4	4.2	62.6	5.2	63.9	5.9		
40.0			58.1	2.9	60.2	3.8	61.4	4.4		
42.0					57.8	2.6	58.9	3.1		
危険角度 (°)	56		57		57		57		65	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SE性能 50mブーム+2m+20mSLジブ										
オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	73.0	12.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.6	12.0	75.4	12.0	78.6	11.9	81.2	10.7	82.8	9.9
28.0	70.1	12.0	73.9	12.0	76.9	11.4	79.4	10.5	80.9	9.7
30.0	68.4	10.5	72.4	12.0	75.2	11.0	77.6	10.1	79.0	9.6
32.0	66.5	8.6	70.6	10.8	73.5	10.4	75.8	9.6	77.1	9.2
34.0	64.5	6.9	68.6	8.9	71.7	9.7	73.9	9.2	75.0	8.8
36.0	62.6	5.5	66.5	7.3	69.8	8.9	71.9	8.7	72.7	8.5
38.0	60.5	4.1	64.5	5.8	67.6	7.3	69.8	8.2	70.5	8.1
40.0	58.5	3.0	62.4	4.5	65.4	5.9	67.5	6.8	68.1	7.3
42.0	56.5	1.9	60.3	3.3	63.2	4.6	65.1	5.4		
44.0			58.1	2.3	60.9	3.4	62.7	4.1		
46.0					58.5	2.3	60.2	2.9		
48.0							57.6	1.8		
危険角度 (°)	56		57		57		57		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SE性能 50mブーム+2m+25mSLジブ										
オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	73.0	10.0	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.6	10.0	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	70.3	10.0	74.8	9.9	78.3	8.8	81.6	8.0	83.7	7.2
32.0	68.8	9.6	73.2	9.4	76.8	8.5	80.0	7.8	81.8	7.1
34.0	67.0	8.0	71.6	8.9	75.2	8.2	78.3	7.6	79.9	7.1
36.0	65.1	6.5	70.0	8.5	73.4	7.9	76.5	7.5	78.0	7.0
38.0	63.2	5.2	68.1	7.3	71.7	7.7	74.6	7.2	75.9	6.9
40.0	61.2	4.0	66.1	6.0	69.9	7.4	72.7	6.9	73.9	6.6
42.0	59.3	2.9	64.1	4.7	68.0	6.3	70.7	6.6	71.7	6.4
44.0	57.5	2.0	62.1	3.6	65.9	5.1	68.7	6.2	69.4	6.1
46.0			60.0	2.6	63.8	4.0	66.4	5.0	67.0	5.4
48.0					58.0	1.7	61.6	2.9	64.0	3.8
50.0							59.3	2.0	61.4	2.8
52.0									58.7	1.8
危険角度 (°)	56		57		58		58		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SE性能 50mブーム+2m+30mSLジブ										
オフセット	0°		15°		30°		45°		60°	
作業半径 (m)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)	ブーム角度 (°)	荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0	78.0	8.5	83.3	8.5						
22.0	76.8	8.5	82.1	8.5						
24.0	75.6	8.5	80.9	8.5						
26.0	74.4	8.5	79.7	8.5	84.3	7.8				
28.0	73.2	8.5	78.4	8.5	82.9	7.5				
30.0	71.9	8.5	77.0	8.4	81.4	7.3				
32.0	70.7	8.5	75.6	8.0	80.0	7.0	83.5	5.9		
34.0	69.4	8.5	74.2	7.7	78.5	6.8	81.9	5.8	84.4	5.2
36.0	67.8	7.4	72.7	7.3	77.0	6.5	80.3	5.7	82.6	5.1
38.0	66.0	6.1	71.2	6.9	75.5	6.3	78.7	5.6	80.8	5.1
40.0	64.2	4.9	69.7	6.5	73.9	6.1	77.0	5.5	78.9	5.0
42.0	62.5	3.8	68.1	6.0	72.3	5.9	75.3	5.4	77.0	5.0
44.0	60.7	2.9	66.1	4.9	70.6	5.7	73.6	5.3	75.1	5.0
46.0	58.8	2.0	64.2	3.9	68.9	5.5	71.6	5.2	72.9	4.9
48.0			62.1	2.9	66.7	4.5	69.6	5.1	70.6	4.9
50.0			60.2	2.1	64.7	3.5	67.5	4.6	68.3	4.7
52.0			58.1	1.3	62.5	2.6	65.1	3.6		
54.0					60.2	1.7				



# 10.85m — 35m

# スーパーラフィングジブ【50mブーム時】

**SF性能** 50mブーム+2m+10.85mSLジブ

オフセット 作業半径 (m)	5'		15'		30'		45'		60'	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.4	21.0	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.9	20.8	76.3	21.0	78.1	20.0	79.2	18.6	80.1	17.7
22.0	72.6	16.8	74.2	18.1	76.2	18.3	77.2	17.4	78.0	16.8
24.0	70.4	13.5	72.0	14.7	74.1	16.2	75.2	16.0	75.8	15.7
26.0	68.2	10.7	69.8	11.8	71.9	13.1	73.1	14.1	73.6	14.6
28.0	66.0	8.4	67.6	9.3	69.6	10.5	70.8	11.4	71.2	11.8
30.0	63.8	6.3	65.4	7.2	67.3	8.3	68.4	9.0	68.7	9.3
32.0	61.5	4.5	63.1	5.3	64.9	6.3	65.9	6.9	66.0	7.1
34.0	59.2	3.0	60.8	3.7	62.5	4.5	63.4	5.1		
36.0					60.1	3.0	60.8	3.4		
危険角度 (°)	57		59		59		59		65	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

**SF性能** 50mブーム+2m+15mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	71.2	12.0	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	69.5	11.7	72.5	12.0	75.1	12.0	76.9	12.0	77.9	12.0
28.0	67.5	9.4	70.8	11.4	73.4	12.0	75.1	12.0	75.9	12.0
30.0	65.4	7.4	68.8	9.2	71.5	10.8	73.0	11.8	73.8	11.6
32.0	63.3	5.6	66.6	7.3	69.2	8.7	70.8	9.7	71.6	10.3
34.0	61.2	4.1	64.5	5.6	67.0	6.9	68.5	7.8	69.1	8.2
36.0	59.1	2.7	62.3	4.1	64.7	5.2	66.1	6.0	66.7	6.4
38.0			60.1	2.7	62.4	3.8	63.7	4.5		
40.0					60.0	2.5	61.2	3.0		
危険角度 (°)	58		59		59		59		65	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

**SF性能** 50mブーム+2m+20mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	73.0	12.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.6	12.0	75.4	12.0	78.6	11.9	81.2	10.7	82.8	9.9
28.0	69.9	10.6	73.9	12.0	76.9	11.4	79.4	10.5	80.9	9.7
30.0	68.0	8.6	72.2	11.0	75.2	11.0	77.6	10.1	79.0	9.6
32.0	66.1	6.8	70.2	9.0	73.5	10.4	75.8	9.6	77.1	9.2
34.0	64.2	5.3	68.3	7.3	71.5	9.1	73.9	9.2	75.0	8.8
36.0	62.2	3.9	66.3	5.8	69.5	7.4	71.9	8.6	72.7	8.5
38.0	60.2	2.7	64.2	4.4	67.3	5.8	69.6	6.9	70.4	7.5
40.0	58.2	1.6	62.1	3.1	65.1	4.5	67.3	5.5	67.9	5.9
42.0			60.0	2.0	62.9	3.2	64.9	4.1		
44.0					60.6	2.1	62.5	2.8		
46.0							60.0	1.7		
危険角度 (°)	58		59		59		59		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

**SF性能** 50mブーム+2m+25mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	73.0	10.0	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.6	10.0	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	70.2	9.7	74.8	9.9	78.3	8.8	81.6	8.0	83.7	7.2
32.0	68.4	7.9	73.2	9.4	76.8	8.5	80.0	7.8	81.8	7.1
34.0	66.6	6.3	71.6	8.8	75.2	8.2	78.3	7.6	79.9	7.1
36.0	64.7	5.0	69.7	7.2	73.4	7.9	76.5	7.5	78.0	7.0
38.0	62.8	3.7	67.7	5.8	71.7	7.7	74.6	7.2	75.9	6.9
40.0	60.9	2.6	65.7	4.6	69.7	6.3	72.7	6.9	73.9	6.6
42.0	59.0	1.6	63.8	3.4	67.6	5.0	70.7	6.3	71.7	6.4
44.0			61.7	2.4	65.5	3.8	68.4	5.0	69.3	5.6
46.0			59.7	1.4	63.4	2.8	66.1	3.8	66.8	4.2
48.0					61.2	1.8	63.6	2.7		
50.0							61.1	1.6		
危険角度 (°)	58		59		60		60		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

**SF性能** 50mブーム+2m+30mSLジブ

オフセット 作業半径 (m)	0'		15'		30'		45'		60'	
	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0	78.0	8.5	83.3	8.5						
22.0	76.8	8.5	82.1	8.5						
24.0	75.6	8.5	80.9	8.5						
26.0	74.4	8.5	79.7	8.5	84.3	7.8				
28.0	73.2	8.5	78.4	8.5	82.9	7.5				
30.0	71.9	8.5	77.0	8.4	81.4	7.3				
32.0	70.7	8.5	75.6	8.0	80.0	7.0	83.5	5.9		
34.0	69.1	7.3	74.2	7.7	78.5	6.8	81.9	5.8	84.4	5.2
36.0	67.3	5.9	72.7	7.3	77.0	6.5	80.3	5.7	82.6	5.1
38.0	65.6	4.6	71.2	6.9	75.5	6.3	78.7	5.6	80.8	5.1
40.0	63.8	3.5	69.4	5.8	73.9	6.1	77.0	5.5	78.9	5.0
42.0	62.0	2.5	67.6	4.7	72.3	5.9	75.3	5.4	77.0	5.0
44.0	60.2	1.6	65.6	3.6	70.5	5.4	73.6	5.3	75.1	5.0
46.0			63.7	2.6	68.4	4.3	71.6	5.2	72.9	4.9
48.0			61.7	1.8	66.3	3.3	69.4	4.5	70.6	4.9
50.0					64.2	2.4	67.2	3.5	68.1	4.1
52.0					62.0	1.5	64.8	2.5		
54.0							62.3	1.6		
危険角度 (°)	59		60		60		60		66	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	





10.85m — 35m

# スーパーラフィングジブ 【50mブーム時】

SH性能 50mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.9	21.0	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	76.2	19.3	77.9	21.0	80.1	21.0	81.2	19.8	82.2	18.7
20.0	74.2	15.1	75.8	16.6	78.0	18.5	79.2	18.6	80.1	17.7
22.0	72.0	11.7	73.6	13.0	75.7	14.7	77.1	16.0	78.0	16.7
24.0	69.9	8.8	71.4	10.0	73.5	11.5	74.8	12.7	75.5	13.3
26.0	67.7	6.4	69.2	7.5	71.3	8.8	72.5	9.8	73.1	10.3
28.0					69.0	6.5	70.2	7.4	70.7	7.8
危険角度 (°)	66		68		68		68		69	
標準フック	24t		24t		24t		24t		24t	
フック質量 (t)	0.88		0.88		0.88		0.88		0.88	
巻掛本数	2		2		2		2		2	

SH性能 50mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.4	12.0	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0	72.8	12.0	75.8	12.0	78.5	12.0	80.5	12.0	81.9	12.0
24.0	70.9	9.8	74.2	12.0	76.8	12.0	78.7	12.0	79.9	12.0
26.0	68.9	7.4	72.2	9.6	75.1	11.5	76.9	12.0	77.9	12.0
28.0			70.3	7.4	73.0	9.1	74.8	10.3	75.8	11.0
30.0					70.9	7.0	72.6	8.2	73.5	8.8
32.0							70.4	6.2	71.1	6.8
危険角度 (°)	67		68.5		69		69		69	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 50mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.5	12.0	78.4	12.0	81.8	12.0	84.7	11.3		
24.0	72.9	11.0	76.9	12.0	80.3	12.0	82.9	11.0	84.7	9.9
26.0	71.1	8.7	75.3	11.4	78.6	11.9	81.2	10.7	82.8	9.9
28.0	69.3	6.6	73.5	9.2	76.9	11.2	79.4	10.5	80.9	9.7
30.0			71.6	7.3	74.9	9.2	77.6	10.1	79.0	9.6
32.0			69.6	5.5	73.0	7.5	75.6	8.7	77.1	9.2
34.0					71.0	5.8	73.5	7.1	74.8	7.7
36.0							71.3	5.5	72.4	6.2
38.0									70.0	4.5
危険角度 (°)	67.5		68.5		69		69.5		69.5	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 50mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.3	10.0	79.0	10.0	83.0	9.9				
26.0	72.9	9.7	77.7	10.0	81.5	9.5	84.9	8.4		
28.0	71.2	7.7	76.4	10.0	79.9	9.1	83.3	8.2		
30.0	69.4	5.9	74.5	8.7	78.3	8.8	81.6	8.0	83.7	7.2
32.0			72.7	7.1	76.8	8.5	80.0	7.8	81.8	7.1
34.0			70.8	5.5	75.0	7.5	78.3	7.6	79.9	7.1
36.0					73.0	6.2	76.5	7.5	78.0	7.0
38.0					71.0	4.7	74.4	6.2	75.9	6.9
40.0							72.2	4.8	73.7	5.6
42.0									71.2	4.2
危険角度 (°)	68		69		70		70		70	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 50mブーム + 2m + 30mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0	78.0	8.5	83.3	8.5						
22.0	76.8	8.5	82.1	8.5						
24.0	75.6	8.5	80.9	8.5						
26.0	74.4	8.5	79.7	8.5	84.3	7.8				
28.0	73.2	8.5	78.4	8.5	82.9	7.5				
30.0	71.5	6.9	77.0	8.4	81.4	7.3				
32.0	69.8	5.3	75.6	8.0	80.0	7.0	83.5	5.9		
34.0			73.9	6.8	78.5	6.8	81.9	5.8	84.4	5.2
36.0			72.1	5.4	77.0	6.5	80.3	5.7	82.6	5.1
38.0					75.5	6.3	78.7	5.6	80.8	5.1
40.0					73.6	5.1	77.0	5.5	78.9	5.0
42.0							75.3	5.4	77.0	5.0
44.0							73.2	4.2	75.1	5.0
危険角度 (°)	68.5		70.5		72		72		73	
標準フック	12t		12t		12t		12t		12t	
フック質量 (t)	0.42		0.42		0.42		0.42		0.42	
巻掛本数	1		1		1		1		1	

SH性能 50mブーム + 2m + 35mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)	ブーム角度 (°); 荷重 (ton)
9.0	84.7	7.0								
10.0	84.2	7.0								
11.0	83.7	7.0								
12.0	83.2	7.0								
14.0	82.1	7.0								
16.0	81.1	7.0								
18.0	80.0	7.0								
20.0	78.9	7.0	84.5	4.9						
22.0	77.9	7.0	83.2	4.6						
24.0	76.6	6.6	82.0	4.4						
26.0	75.4	6.1	80.7	4.2						
28.0	74.1	5.7	79.4	4.0	84.3	2.8				
30.0	72.9	5.3	78.1	3.8	82.9	2.7				
32.0	71.6	5.0	76.8	3.6	81.5	2.6				
34.0			75.4	3.4	80.1	2.5	84.3	1.9		
36.0			74.1	3.2	78.7	2.4	82.8	1.8		
38.0			72.7	3.0	77.2	2.3	81.3	1.8	83.8	1.5
40.0					75.8	2.2	79.7	1.7	82.1	1.4
42.0					74.3	2.1	78.1	1.7	80.4	1.4
44.0					72.7	2.0	76.5	1.6	78	



 10.85m — 35m      スーパーラフィングジブ【50mブーム時】

SJ性能 50mブーム + 2m + 10.85mSLジブ

オフセット	5'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.4	21.0	81.1	21.0	83.3	21.0	84.9	21.0		
16.0	77.8	20.1	79.5	21.0	81.7	21.0	83.1	21.0	84.2	19.8
18.0	75.8	15.0	77.5	16.8	79.8	19.1	81.2	19.8	82.2	18.7
20.0	73.8	11.1	75.4	12.6	77.5	14.7	79.0	16.0	78.0	16.8
22.0			73.2	9.3	75.3	11.1	76.7	12.3	77.5	13.0
24.0							74.5	9.4	75.1	9.9
危険角度 (°)	72	72	73.5	73.5	74	74	74	74	74	74
標準フック	24t	24t	24t	24t	24t	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
巻掛本数	2	2	2	2	2	2	2	2	2	2

SJ性能 50mブーム + 2m + 15mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0	77.4	12.0	80.5	12.0	83.4	12.0				
18.0	75.9	12.0	78.9	12.0	81.8	12.0	84.0	12.0		
20.0	74.3	11.8	77.4	12.0	80.2	12.0	82.3	12.0	83.8	12.0
22.0			75.7	11.6	78.5	12.0	80.5	12.0	81.9	12.0
24.0			73.8	8.7	76.7	10.8	78.7	12.0	79.9	12.0
26.0					74.7	8.4	76.6	9.7	77.8	10.5
28.0							74.5	7.5	75.5	8.2
危険角度 (°)	72.5	72.5	73.5	73.5	74	74	74.5	74.5	75	75
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

SJ性能 50mブーム + 2m + 20mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0	77.3	12.0	81.2	12.0	84.8	12.0				
20.0	75.9	12.0	79.8	12.0	83.3	12.0				
22.0	74.2	9.9	78.4	12.0	81.8	12.0	84.7	11.3		
24.0			76.7	10.6	80.3	12.0	82.9	11.0	84.7	9.9
26.0			74.9	8.1	78.4	10.5	81.2	10.7	82.8	9.9
28.0					76.5	8.4	79.3	9.9	80.9	9.7
30.0					74.5	6.5	77.3	8.0	78.9	8.9
32.0							75.2	6.3	76.7	7.1
危険角度 (°)	73	73.5	73.5	73.5	73.5	73.5	74.5	74.5	74.5	74.5
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

SJ性能 50mブーム + 2m + 25mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0	78.2	10.0	83.0	10.0						
20.0	76.9	10.0	81.7	10.0						
22.0	75.6	10.0	80.4	10.0	84.5	10.0				
24.0	74.0	8.3	79.0	10.0	83.0	9.9				
26.0			77.6	9.7	81.5	9.5	84.9	8.4		
28.0			75.8	7.6	79.9	9.1	83.3	8.2		
30.0					78.2	8.2	81.6	8.0	83.7	7.2
32.0					76.3	6.7	80.0	7.8	81.8	7.1
34.0							78.0	6.7	79.9	7.1
36.0							75.9	5.4	77.8	6.3
38.0									75.5	5.0
危険角度 (°)	73	74	74.5	74.5	74.5	74.5	74.5	74.5	74.5	74.5
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

SJ性能 50mブーム + 2m + 30mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0	78.0	8.5	83.3	8.5						
22.0	76.8	8.5	82.1	8.5						
24.0	75.6	8.5	80.9	8.5						
26.0			79.7	8.5	84.3	7.8				
28.0			78.4	8.5	82.9	7.5				
30.0			76.7	7.1	81.4	7.3				
32.0					80.0	7.0	83.5	5.9		
34.0					78.5	6.7	81.9	5.8	84.4	5.2
36.0							80.3	5.7	82.6	5.1
38.0							78.7	5.6	80.8	5.1
40.0									78.9	5.0
危険角度 (°)	74.5	75	77	77	77	77	77	77	77	77
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

SJ性能 50mブーム + 2m + 35mSLジブ

オフセット	0'		15'		30'		45'		60'	
作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
9.0	84.7	7.0								
10.0	84.2	7.0								
11.0	83.7	7.0								
12.0	83.2	7.0								
14.0	82.1	7.0								
16.0	81.1	7.0								
18.0	80.0	7.0								
20.0	78.9	7.0	84.5	4.9						
22.0	77.9	7.0	83.2	4.6						
24.0	76.6	6.6	82.0	4.4						
26.0	75.4	6.1	80.7	4.2						
28.0			79.4	4.0	84.3	2.8				
30.0			78.1	3.8	82.9	2.7				
32.0			76.8	3.6	81.5	2.6				
34.0					80.1	2.5	84.3	1.9		
36.0					78.7	2.4	82.8	1.8		
38.0							81.3	1.8	83.8	1.5
40.0							79.7	1.7	82.1	1.4
42.0							78.1	1.7	80.4	1.4
44.0									78.7	1.4
危険角度 (°)	74.5	75.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5	77.5
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1



# 10.85m — 35m

# スーパーラフingジブ【50mブーム時】

**SK性能 50mブーム+2m+10.85mSLジブ**

オフセット	5'		15'		30'		45'		60'	
	作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.7	21.0								
8.0	83.9	21.0								
9.0	83.2	21.0								
10.0	82.4	21.0	84.2	21.0						
11.0	81.6	21.0	83.4	21.0						
12.0	80.9	21.0	82.7	21.0	84.9	21.0				
14.0	79.2	18.3	81.1	20.7	83.3	21.0	84.9	21.0		
16.0			79.0	14.9	81.4	17.7	83.0	19.6	84.2	19.8
18.0					79.2	12.8	80.7	14.5	81.8	15.5
危険角度 (°)	78	78	78	78	79	79	80	80	80	80
標準フック	24t	24t	24t	24t	24t	24t	24t	24t	24t	24t
フック質量 (t)	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
巻掛本数	2	2	2	2	2	2	2	2	2	2

**SK性能 50mブーム+2m+15mSLジブ**

オフセット	0'		15'		30'		45'		60'	
	作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
6.0	84.8	12.0								
7.0	84.1	12.0								
8.0	83.4	12.0								
9.0	82.6	12.0								
10.0	81.9	12.0								
11.0	81.2	12.0	84.3	12.0						
12.0	80.4	12.0	83.6	12.0						
14.0	78.9	12.0	82.0	12.0						
16.0			80.5	12.0	83.4	12.0				
18.0			78.9	12.0	81.8	12.0	84.0	12.0		
20.0					80.2	12.0	82.3	12.0	83.8	12.0
22.0							80.4	10.6	81.8	11.7
危険角度 (°)	78	78	78	78	79	79	80	80	80	80
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

**SK性能 50mブーム+2m+20mSLジブ**

オフセット	0'		15'		30'		45'		60'	
	作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
7.0	84.6	12.0								
8.0	84.0	12.0								
9.0	83.3	12.0								
10.0	82.7	12.0								
11.0	82.0	12.0								
12.0	81.3	12.0								
14.0	80.0	12.0	84.0	12.0						
16.0	78.6	12.0	82.6	12.0						
18.0			81.2	12.0	84.8	12.0				
20.0			79.7	11.3	83.3	12.0				
22.0					81.7	11.3	84.7	11.3		
24.0					79.8	8.8	82.9	10.6	84.7	9.9
26.0							80.8	8.4	82.7	9.5
危険角度 (°)	78	78	78	78	79	79	81	81	81	81
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

**SK性能 50mブーム+2m+25mSLジブ**

オフセット	0'		15'		30'		45'		60'	
	作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.4	10.0								
9.0	83.8	10.0								
10.0	83.2	10.0								
11.0	82.6	10.0								
12.0	82.0	10.0								
14.0	80.7	10.0								
16.0	79.5	10.0	84.2	10.0						
18.0			83.0	10.0						
20.0			81.7	10.0						
22.0			80.4	10.0	84.5	10.0				
24.0					83.0	9.9				
26.0					81.2	8.4	84.9	8.4		
28.0							83.3	8.2		
30.0							81.3	6.8	83.7	7.2
32.0									81.7	6.4
危険角度 (°)	78.5	79	79.5	79.5	81	81	81	81	81	81
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

**SK性能 50mブーム+2m+30mSLジブ**

オフセット	0'		15'		30'		45'		60'	
	作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
8.0	84.9	8.5								
9.0	84.3	8.5								
10.0	83.8	8.5								
11.0	83.2	8.5								
12.0	82.6	8.5								
14.0	81.5	8.5								
16.0	80.3	8.5								
18.0	79.2	8.5	84.5	8.5						
20.0			83.3	8.5						
22.0			82.1	8.5						
24.0			80.9	8.5						
26.0					84.3	7.8				
28.0					82.9	7.5				
30.0					81.2	6.5				
32.0							83.5	5.9		
34.0							81.9	5.7	84.4	5.2
36.0									82.6	5.1
危険角度 (°)	78.5	79.5	79.5	80	81	81	81	81	81	81
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1

**SK性能 50mブーム+2m+35mSLジブ**

オフセット	0'		15'		30'		45'		60'	
	作業半径 (m)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)	ブーム角度 (°): 荷重 (ton)
9.0	84.7	7.0								
10.0	84.2	7.0								
11.0	83.7	7.0								
12.0	83.2	7.0								
14.0	82.1	7.0								
16.0	81.1	7.0								
18.0	80.0	7.0								
20.0			84.5	4.9						
22.0			83.2	4.6						
24.0			82.0	4.4						
26.0			80.7	4.2						
28.0					84.3	2.8				
30.0					82.9	2.7				
32.0					81.5	2.6				
34.0							84.3	1.9		
36.0							82.8	1.8		
38.0									83.8	1.5
40.0									82.1	1.4
危険角度 (°)	79	79.5	80.5	81.5	81.5	81.5	81.5	81.5	81.5	81.5
標準フック	12t	12t	12t	12t	12t	12t	12t	12t	12t	12t
フック質量 (t)	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42	0.42
巻掛本数	1	1	1	1	1	1	1	1	1	1