



# 10m — 31m

# スーパーラフィングブーム【31.8mブーム時】

SA性能 31.8mブーム+2.3m+10mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 5.0               | 48.0           |                 |                 |                 |                 |
| 6.0               | 48.0           |                 |                 |                 |                 |
| 7.0               | 48.0           |                 |                 |                 |                 |
| 8.0               | 48.0           |                 |                 |                 |                 |
| 9.0               | 48.0           | 47.5            |                 |                 |                 |
| 10.0              | 48.0           | 45.7            |                 |                 |                 |
| 11.0              | 48.0           | 44.0            | 38.0            |                 |                 |
| 12.0              | 48.0           | 42.3            | 37.1            | 33.2            |                 |
| 14.0              | 46.2           | 39.4            | 35.3            | 32.2            | 28.5            |
| 16.0              | 41.9           | 36.9            | 33.8            | 31.4            | 28.5            |
| 18.0              | 38.2           | 34.8            | 32.5            | 30.6            | 28.5            |
| 20.0              | 35.2           | 32.9            | 31.3            | 29.9            | 28.5            |
| 22.0              | 32.5           | 31.2            | 30.3            | 29.0            | 28.5            |
| 24.0              | 30.3           | 29.7            | 29.4            | 28.1            | 28.5            |
| 26.0              | 28.3           | 28.4            | 28.3            | 27.4            |                 |
| 28.0              | 24.9           | 26.0            | 26.1            | 26.0            |                 |
| 30.0              | 21.8           | 22.7            | 23.3            | 23.5            |                 |
| 32.0              | 19.1           | 19.8            | 20.3            | 20.4            |                 |
| 34.0              | 16.7           | 17.3            | 17.6            |                 |                 |
| 36.0              | 14.5           | 15.0            | 15.2            |                 |                 |
| 38.0              | 12.7           | 13.0            |                 |                 |                 |
| 40.0              | 10.3           | 11.1            |                 |                 |                 |
| 危険角度 (°)          | 10             | 15              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SA性能 31.8mブーム+2.3m+23mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           |                 |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 17.8            |                 |                 |                 |
| 20.0              | 18.0           | 16.8            | 13.6            |                 |                 |
| 22.0              | 18.0           | 15.9            | 13.1            |                 |                 |
| 24.0              | 16.5           | 15.1            | 12.6            | 11.0            |                 |
| 26.0              | 15.2           | 14.2            | 12.1            | 10.7            | 9.8             |
| 28.0              | 14.0           | 13.4            | 11.8            | 10.5            | 9.8             |
| 30.0              | 13.0           | 12.7            | 11.4            | 10.3            | 9.8             |
| 32.0              | 12.1           | 12.0            | 11.1            | 10.1            | 9.8             |
| 34.0              | 11.3           | 11.5            | 10.8            | 10.0            | 9.8             |
| 36.0              | 10.5           | 10.9            | 10.6            | 9.9             | 9.8             |
| 38.0              | 9.9            | 10.4            | 10.3            | 9.8             | 9.8             |
| 40.0              | 9.3            | 10.0            | 10.2            | 9.8             |                 |
| 42.0              | 8.8            | 9.6             | 10.0            | 9.8             |                 |
| 44.0              | 8.3            | 9.3             | 9.7             | 9.8             |                 |
| 46.0              | 7.9            | 9.0             | 9.5             |                 |                 |
| 48.0              | 7.5            | 8.7             | 9.4             |                 |                 |
| 50.0              | 7.1            | 8.5             | 9.3             |                 |                 |
| 52.0              | 6.8            | 8.0             |                 |                 |                 |
| 54.0              |                | 4.9             |                 |                 |                 |
| 危険角度 (°)          | 15             | 15              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SA性能 31.8mブーム+2.3m+15mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 6.0               | 18.0           |                 |                 |                 |                 |
| 7.0               | 18.0           |                 |                 |                 |                 |
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           | 18.0            |                 |                 |                 |
| 11.0              | 18.0           | 18.0            |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 16.0              | 18.0           | 18.0            | 18.0            | 18.0            |                 |
| 18.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 20.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 22.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 24.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 26.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 28.0              | 18.0           | 18.0            | 18.0            | 17.8            | 18.0            |
| 30.0              | 18.0           | 18.0            | 18.0            | 17.4            | 18.0            |
| 32.0              | 16.9           | 17.5            | 17.6            | 17.0            |                 |
| 34.0              | 15.9           | 16.8            | 17.0            | 16.8            |                 |
| 36.0              | 15.0           | 16.2            | 16.5            | 16.6            |                 |
| 38.0              | 14.3           | 15.3            | 15.8            |                 |                 |
| 40.0              | 12.8           | 13.4            | 13.8            |                 |                 |
| 42.0              | 11.2           | 11.8            | 12.0            |                 |                 |
| 44.0              | 9.9            | 10.2            |                 |                 |                 |
| 46.0              | 5.5            | 6.3             |                 |                 |                 |
| 危険角度 (°)          | 10             | 15              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SA性能 31.8mブーム+2.3m+27mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 15.0           |                 |                 |                 |                 |
| 9.0               | 15.0           |                 |                 |                 |                 |
| 10.0              | 15.0           |                 |                 |                 |                 |
| 11.0              | 15.0           |                 |                 |                 |                 |
| 12.0              | 15.0           |                 |                 |                 |                 |
| 14.0              | 15.0           |                 |                 |                 |                 |
| 16.0              | 15.0           | 15.0            |                 |                 |                 |
| 18.0              | 15.0           | 14.6            |                 |                 |                 |
| 20.0              | 15.0           | 13.7            |                 |                 |                 |
| 22.0              | 15.0           | 12.9            | 10.0            |                 |                 |
| 24.0              | 15.0           | 12.2            | 10.0            |                 |                 |
| 26.0              | 13.9           | 11.6            | 9.6             | 8.3             |                 |
| 28.0              | 12.8           | 11.0            | 9.3             | 8.1             |                 |
| 30.0              | 11.8           | 10.5            | 9.0             | 7.9             | 7.2             |
| 32.0              | 11.0           | 10.1            | 8.7             | 7.7             | 7.2             |
| 34.0              | 10.2           | 9.7             | 8.4             | 7.6             | 7.2             |
| 36.0              | 9.5            | 9.3             | 8.2             | 7.5             | 7.2             |
| 38.0              | 8.9            | 9.0             | 8.0             | 7.4             | 7.2             |
| 40.0              | 8.4            | 8.7             | 7.8             | 7.3             | 7.2             |
| 42.0              | 7.9            | 8.4             | 7.6             | 7.2             | 7.2             |
| 44.0              | 7.4            | 8.1             | 7.5             | 7.2             |                 |
| 46.0              | 7.0            | 7.8             | 7.4             | 7.2             |                 |
| 48.0              | 6.6            | 7.5             | 7.3             | 7.2             |                 |
| 50.0              | 6.3            | 7.3             | 7.2             |                 |                 |
| 52.0              | 5.9            | 7.0             | 7.2             |                 |                 |
| 54.0              | 5.7            | 6.7             | 7.2             |                 |                 |
| 56.0              | 5.4            | 6.4             |                 |                 |                 |
| 58.0              |                | 4.3             |                 |                 |                 |
| 危険角度 (°)          | 15             | 15              | 30              | 45              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

SA性能 31.8mブーム+2.3m+19mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 20.0              | 18.0           | 18.0            | 18.0            | 16.0            |                 |
| 22.0              | 18.0           | 18.0            | 17.1            | 15.6            | 14.0            |
| 24.0              | 18.0           | 17.6            | 16.4            | 15.1            | 13.8            |
| 26.0              | 17.4           | 16.6            | 15.7            | 14.5            | 13.6            |
| 28.0              | 16.1           | 15.7            | 15.1            | 14.1            | 13.5            |
| 30.0              | 15.0           | 14.9            | 14.6            | 13.7            | 13.4            |
| 32.0              | 14.0           | 14.2            | 14.1            | 13.3            | 13.3            |
| 34.0              | 13.1           | 13.6            | 13.6            | 13.0            | 13.2            |
| 36.0              | 12.3           | 13.0            | 13.2            | 12.8            |                 |
| 38.0              | 11.6           | 12.5            | 12.8            | 12.6            |                 |
| 40.0              | 11.0           | 12.0            | 12.4            | 12.5            |                 |
| 42.0              | 10.4           | 11.7            | 12.2            |                 |                 |
| 44.0              | 9.9            | 11.3            | 12.0            |                 |                 |
| 46.0              | 9.4            | 10.3            | 10.6            |                 |                 |
| 48.0              | 8.6            | 9.0             |                 |                 |                 |
| 50.0              | 4.5            | 5.5             |                 |                 |                 |
| 危険角度 (°)          | 10             | 15              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SA性能 31.8mブーム+2.3m+31mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 9.0               | 12.0           |                 |                 |                 |                 |
| 10.0              | 12.0           |                 |                 |                 |                 |
| 11.0              | 12.0           |                 |                 |                 |                 |
| 12.0              | 12.0           |                 |                 |                 |                 |
| 14.0              | 12.0           |                 |                 |                 |                 |
| 16.0              | 12.0           |                 |                 |                 |                 |
| 18.0              | 12.0           | 12.0            |                 |                 |                 |
| 20.0              | 12.0           | 11.4            |                 |                 |                 |
| 22.0              | 12.0           | 10.7            |                 |                 |                 |
| 24.0              | 12.0           | 10.1            | 8.1             |                 |                 |
| 26.0              | 12.0           | 9.6             | 7.9             |                 |                 |
| 28.0              | 11.5           | 9.1             | 7.5             |                 |                 |
| 30.0              | 10.8           | 8.7             | 7.3             | 6.3             |                 |
| 32.0              | 10.0           | 8.3             | 7.0             | 6.2             |                 |
| 34.0              | 9.3            | 7.9             | 6.8             | 6.0             | 5.4             |
| 36.0              | 8.6            | 7.6             | 6.6             | 5.9             | 5.4             |
| 38.0              | 8.0            | 7.3             | 6.4             | 5.8             | 5.4             |
| 40.0              | 7.5            | 7.0             | 6.2             | 5.7             | 5.4             |
| 42.0              | 7.0            | 6.8             | 6.0             | 5.6             | 5.4             |
| 44.0              | 6.6            | 6.6             | 5.9             | 5.5             | 5.4             |
| 46.0              | 6.2            | 6.4             | 5.8             | 5.4             | 5.4             |
| 48.0              | 5.8            | 6.2             | 5.7             | 5.4             |                 |
| 50.0              | 5.5            | 6.0             | 5.6             | 5.4             |                 |
| 52.0              | 5.2            | 5.9             | 5.5             | 5.4             |                 |
| 54.0              | 4.9            | 5.7             | 5.4             |                 |                 |
| 56.0              | 4.7            | 5.6             | 5.4             |                 |                 |
| 58.0              | 4.4            | 5.4             | 5.4             |                 |                 |
| 60.0              | 4.2            | 5.2             |                 |                 |                 |
| 62.0              |                | 3.8             |                 |                 |                 |
| 危険角度 (°)          | 15             | 15              | 30              | 45              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

# 10m — 31m スーパーラフィングブーム【31.8mブーム時】

SB性能 31.8mブーム+2.3m+10mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 5.0               | 48.0           |                 |                 |                 |                 |
| 6.0               | 48.0           |                 |                 |                 |                 |
| 7.0               | 48.0           |                 |                 |                 |                 |
| 8.0               | 48.0           |                 |                 |                 |                 |
| 9.0               | 48.0           | 47.5            |                 |                 |                 |
| 10.0              | 48.0           | 45.7            |                 |                 |                 |
| 11.0              | 48.0           | 44.0            | 38.0            |                 |                 |
| 12.0              | 48.0           | 42.3            | 37.1            | 33.2            |                 |
| 14.0              | 46.2           | 39.4            | 35.3            | 32.2            | 28.5            |
| 16.0              | 41.9           | 36.9            | 33.8            | 31.4            | 28.5            |
| 18.0              | 36.4           | 34.8            | 32.5            | 30.6            | 28.5            |
| 20.0              | 30.5           | 32.3            | 31.3            | 29.9            | 28.5            |
| 22.0              | 25.7           | 27.0            | 28.1            | 28.8            | 28.5            |
| 24.0              | 21.7           | 22.8            | 23.6            | 24.2            | 24.3            |
| 26.0              | 18.3           | 19.2            | 20.0            | 20.4            |                 |
| 28.0              | 15.4           | 16.3            | 16.9            | 17.2            |                 |
| 30.0              | 13.0           | 13.8            | 14.2            | 14.4            |                 |
| 32.0              | 10.8           | 11.5            | 12.0            | 12.1            |                 |
| 34.0              | 8.9            | 9.5             | 9.8             |                 |                 |
| 36.0              | 7.2            | 7.7             | 7.9             |                 |                 |
| 38.0              | 5.7            | 6.0             |                 |                 |                 |
| 40.0              | 4.2            | 4.3             |                 |                 |                 |
| 危険角度 (°)          | 15             | 15              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SB性能 31.8mブーム+2.3m+23mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           |                 |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 17.8            |                 |                 |                 |
| 20.0              | 18.0           | 16.8            | 13.6            |                 |                 |
| 22.0              | 18.0           | 15.9            | 13.1            |                 |                 |
| 24.0              | 16.5           | 15.1            | 12.6            | 11.0            |                 |
| 26.0              | 15.2           | 14.2            | 12.1            | 10.7            | 9.8             |
| 28.0              | 14.0           | 13.4            | 11.8            | 10.5            | 9.8             |
| 30.0              | 13.0           | 12.7            | 11.4            | 10.3            | 9.8             |
| 32.0              | 12.1           | 12.0            | 11.1            | 10.1            | 9.8             |
| 34.0              | 11.3           | 11.5            | 10.8            | 10.0            | 9.8             |
| 36.0              | 10.5           | 10.9            | 10.6            | 9.9             | 9.8             |
| 38.0              | 9.5            | 10.4            | 10.3            | 9.8             | 9.8             |
| 40.0              | 8.3            | 9.3             | 10.2            | 9.8             |                 |
| 42.0              | 7.1            | 8.1             | 8.9             | 9.3             |                 |
| 44.0              | 5.9            | 7.0             | 7.7             | 8.0             |                 |
| 46.0              | 4.8            | 5.8             | 6.5             |                 |                 |
| 48.0              |                | 4.6             | 5.2             |                 |                 |
| 危険角度 (°)          | 33             | 33              | 35              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SB性能 31.8mブーム+2.3m+15mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 6.0               | 18.0           |                 |                 |                 |                 |
| 7.0               | 18.0           |                 |                 |                 |                 |
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           | 18.0            |                 |                 |                 |
| 11.0              | 18.0           | 18.0            |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 16.0              | 18.0           | 18.0            | 18.0            | 18.0            |                 |
| 18.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 20.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 22.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 24.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 26.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 28.0              | 16.9           | 18.0            | 18.0            | 17.8            | 18.0            |
| 30.0              | 14.5           | 15.7            | 16.6            | 17.3            | 17.4            |
| 32.0              | 12.5           | 13.5            | 14.3            | 14.8            |                 |
| 34.0              | 10.7           | 11.6            | 12.3            | 12.6            |                 |
| 36.0              | 9.0            | 9.9             | 10.5            | 10.7            |                 |
| 38.0              | 7.5            | 8.3             | 8.9             |                 |                 |
| 40.0              | 6.1            | 6.8             | 7.2             |                 |                 |
| 42.0              | 4.8            | 5.3             | 5.6             |                 |                 |
| 危険角度 (°)          | 25             | 28              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SB性能 31.8mブーム+2.3m+27mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 15.0           |                 |                 |                 |                 |
| 9.0               | 15.0           |                 |                 |                 |                 |
| 10.0              | 15.0           |                 |                 |                 |                 |
| 11.0              | 15.0           |                 |                 |                 |                 |
| 12.0              | 15.0           |                 |                 |                 |                 |
| 14.0              | 15.0           |                 |                 |                 |                 |
| 16.0              | 15.0           | 15.0            |                 |                 |                 |
| 18.0              | 15.0           | 14.6            |                 |                 |                 |
| 20.0              | 15.0           | 13.7            |                 |                 |                 |
| 22.0              | 15.0           | 12.9            | 10.0            |                 |                 |
| 24.0              | 15.0           | 12.2            | 10.0            |                 |                 |
| 26.0              | 13.9           | 11.6            | 9.6             | 8.3             |                 |
| 28.0              | 12.8           | 11.0            | 9.3             | 8.1             |                 |
| 30.0              | 11.8           | 10.5            | 9.0             | 7.9             | 7.2             |
| 32.0              | 11.0           | 10.1            | 8.7             | 7.7             | 7.2             |
| 34.0              | 10.2           | 9.7             | 8.4             | 7.6             | 7.2             |
| 36.0              | 9.5            | 9.3             | 8.2             | 7.5             | 7.2             |
| 38.0              | 8.9            | 9.0             | 8.0             | 7.4             | 7.2             |
| 40.0              | 8.4            | 8.7             | 7.8             | 7.3             | 7.2             |
| 42.0              | 7.9            | 8.4             | 7.6             | 7.2             | 7.2             |
| 44.0              | 7.1            | 8.1             | 7.5             | 7.2             |                 |
| 46.0              | 6.0            | 7.1             | 7.4             | 7.2             |                 |
| 48.0              | 4.9            | 6.1             | 6.8             | 7.1             |                 |
| 50.0              | 4.0            | 5.0             | 5.7             |                 |                 |
| 52.0              |                | 4.0             | 4.5             |                 |                 |
| 危険角度 (°)          | 33             | 33              | 35              | 45              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

SB性能 31.8mブーム+2.3m+19mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 20.0              | 18.0           | 18.0            | 18.0            | 16.0            |                 |
| 22.0              | 18.0           | 18.0            | 17.1            | 15.6            | 14.0            |
| 24.0              | 18.0           | 17.6            | 16.4            | 15.1            | 13.8            |
| 26.0              | 17.4           | 16.6            | 15.7            | 14.5            | 13.6            |
| 28.0              | 16.1           | 15.7            | 15.1            | 14.1            | 13.5            |
| 30.0              | 15.0           | 14.9            | 14.6            | 13.7            | 13.4            |
| 32.0              | 13.4           | 14.2            | 14.1            | 13.3            | 13.3            |
| 34.0              | 11.6           | 12.8            | 13.6            | 13.0            | 13.2            |
| 36.0              | 10.1           | 11.1            | 12.0            | 12.5            |                 |
| 38.0              | 8.7            | 9.6             | 10.4            | 10.8            |                 |
| 40.0              | 7.3            | 8.3             | 8.9             | 9.2             |                 |
| 42.0              | 6.1            | 7.0             | 7.6             |                 |                 |
| 44.0              | 4.8            | 5.6             | 6.1             |                 |                 |
| 46.0              |                | 4.4             | 4.6             |                 |                 |
| 危険角度 (°)          | 30             | 30              | 30              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SB性能 31.8mブーム+2.3m+31mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 9.0               | 12.0           |                 |                 |                 |                 |
| 10.0              | 12.0           |                 |                 |                 |                 |
| 11.0              | 12.0           |                 |                 |                 |                 |
| 12.0              | 12.0           |                 |                 |                 |                 |
| 14.0              | 12.0           |                 |                 |                 |                 |
| 16.0              | 12.0           |                 |                 |                 |                 |
| 18.0              | 12.0           | 12.0            |                 |                 |                 |
| 20.0              | 12.0           | 11.4            |                 |                 |                 |
| 22.0              | 12.0           | 10.7            |                 |                 |                 |
| 24.0              | 12.0           | 10.1            | 8.1             |                 |                 |
| 26.0              | 12.0           | 9.6             | 7.9             |                 |                 |
| 28.0              | 11.5           | 9.1             | 7.5             |                 |                 |
| 30.0              | 10.8           | 8.7             | 7.3             | 6.3             |                 |
| 32.0              | 10.0           | 8.3             | 7.0             | 6.2             |                 |
| 34.0              | 9.3            | 7.9             | 6.8             | 6.0             | 5.4             |
| 36.0              | 8.6            | 7.6             | 6.6             | 5.9             | 5.4             |
| 38.0              | 8.0            | 7.3             | 6.4             | 5.8             | 5.4             |
| 40.0              | 7.5            | 7.0             | 6.2             | 5.7             | 5.4             |
| 42.0              | 7.0            | 6.8             | 6.0             | 5.6             | 5.4             |
| 44.0              | 6.6            | 6.6             | 5.9             | 5.5             | 5.4             |
| 46.0              | 6.2            | 6.4             | 5.8             | 5.4             | 5.4             |
| 48.0              | 5.8            | 6.2             | 5.7             | 5.4             |                 |
| 50.0              | 4.8            | 6.0             | 5.6             | 5.4             |                 |
| 52.0              | 4.0            | 5.1             | 5.5             | 5.4             |                 |
| 54.0              |                | 4.1             | 4.9             |                 |                 |
| 56.0              |                | 3.3             | 3.8             |                 |                 |
| 危険角度 (°)          | 33             | 33              | 35              | 45              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |



# 10m — 31m

# スーパーラフィングブーム【31.8mブーム時】

SC性能 31.8mブーム+2.3m+10mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 5.0               | 48.0           |                 |                 |                 |                 |
| 6.0               | 48.0           |                 |                 |                 |                 |
| 7.0               | 48.0           |                 |                 |                 |                 |
| 8.0               | 48.0           |                 |                 |                 |                 |
| 9.0               | 48.0           | 47.5            |                 |                 |                 |
| 10.0              | 48.0           | 45.7            |                 |                 |                 |
| 11.0              | 48.0           | 44.0            | 38.0            |                 |                 |
| 12.0              | 48.0           | 42.3            | 37.1            | 33.2            |                 |
| 14.0              | 41.8           | 39.4            | 35.3            | 32.2            | 28.5            |
| 16.0              | 33.8           | 36.2            | 33.8            | 31.4            | 28.5            |
| 18.0              | 27.5           | 29.7            | 31.5            | 30.6            | 28.5            |
| 20.0              | 22.6           | 24.4            | 25.8            | 26.7            | 27.1            |
| 22.0              | 18.5           | 20.1            | 21.2            | 21.9            | 22.2            |
| 24.0              | 15.1           | 16.4            | 17.3            | 17.9            | 18.0            |
| 26.0              | 12.2           | 13.4            | 14.2            | 14.6            |                 |
| 28.0              | 9.8            | 11.0            | 11.6            | 11.9            |                 |
| 30.0              | 7.7            | 8.9             | 9.2             | 9.4             |                 |
| 32.0              | 5.7            | 6.6             | 7.1             | 7.1             |                 |
| 34.0              |                | 4.5             | 4.9             |                 |                 |
| 危険角度 (°)          | 39             | 39              | 39              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SC性能 31.8mブーム+2.3m+23mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           |                 |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 17.8            |                 |                 |                 |
| 20.0              | 18.0           | 16.8            | 13.6            |                 |                 |
| 22.0              | 18.0           | 15.9            | 13.1            |                 |                 |
| 24.0              | 16.5           | 15.1            | 12.6            | 11.0            |                 |
| 26.0              | 15.2           | 14.2            | 12.1            | 10.7            | 9.8             |
| 28.0              | 13.4           | 13.4            | 11.8            | 10.5            | 9.8             |
| 30.0              | 11.4           | 12.7            | 11.4            | 10.3            | 9.8             |
| 32.0              | 9.7            | 11.3            | 11.1            | 10.1            | 9.8             |
| 34.0              | 8.2            | 9.6             | 10.8            | 10.0            | 9.8             |
| 36.0              | 6.8            | 8.2             | 9.3             | 9.9             | 9.8             |
| 38.0              | 5.3            | 7.0             | 7.9             | 8.7             | 8.9             |
| 40.0              | 4.0            | 5.5             | 6.7             | 7.3             |                 |
| 42.0              |                | 4.2             | 5.3             | 5.9             |                 |
| 44.0              |                |                 |                 | 4.3             |                 |
| 危険角度 (°)          | 43             | 45              | 49              | 49              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SC性能 31.8mブーム+2.3m+15mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 6.0               | 18.0           |                 |                 |                 |                 |
| 7.0               | 18.0           |                 |                 |                 |                 |
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           | 18.0            |                 |                 |                 |
| 11.0              | 18.0           | 18.0            |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 16.0              | 18.0           | 18.0            | 18.0            | 18.0            |                 |
| 18.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 20.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 22.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 24.0              | 16.8           | 18.0            | 18.0            | 18.0            | 18.0            |
| 26.0              | 14.0           | 15.5            | 16.8            | 17.8            | 18.0            |
| 28.0              | 11.6           | 12.9            | 14.1            | 14.8            | 15.2            |
| 30.0              | 9.5            | 10.8            | 11.7            | 12.4            | 12.5            |
| 32.0              | 7.7            | 9.0             | 9.8             | 10.2            |                 |
| 34.0              | 5.9            | 7.2             | 8.0             | 8.4             |                 |
| 36.0              | 4.3            | 5.4             | 6.2             | 6.5             |                 |
| 38.0              |                |                 | 4.4             |                 |                 |
| 危険角度 (°)          | 40             | 43              | 43              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SC性能 31.8mブーム+2.3m+27mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 15.0           |                 |                 |                 |                 |
| 9.0               | 15.0           |                 |                 |                 |                 |
| 10.0              | 15.0           |                 |                 |                 |                 |
| 11.0              | 15.0           |                 |                 |                 |                 |
| 12.0              | 15.0           |                 |                 |                 |                 |
| 14.0              | 15.0           |                 |                 |                 |                 |
| 16.0              | 15.0           | 15.0            |                 |                 |                 |
| 18.0              | 15.0           | 14.6            |                 |                 |                 |
| 20.0              | 15.0           | 13.7            |                 |                 |                 |
| 22.0              | 15.0           | 12.9            | 10.0            |                 |                 |
| 24.0              | 15.0           | 12.2            | 10.0            |                 |                 |
| 26.0              | 13.9           | 11.6            | 9.6             | 8.3             |                 |
| 28.0              | 12.8           | 11.0            | 9.3             | 8.1             |                 |
| 30.0              | 11.8           | 10.5            | 9.0             | 7.9             | 7.2             |
| 32.0              | 10.6           | 10.1            | 8.7             | 7.7             | 7.2             |
| 34.0              | 8.1            | 9.7             | 8.4             | 7.6             | 7.2             |
| 36.0              | 7.8            | 9.3             | 8.2             | 7.5             | 7.2             |
| 38.0              | 6.6            | 8.0             | 8.0             | 7.4             | 7.2             |
| 40.0              | 5.3            | 6.9             | 7.8             | 7.3             | 7.2             |
| 42.0              | 4.1            | 5.7             | 6.8             | 7.2             | 7.2             |
| 44.0              | 3.0            | 4.5             | 5.7             | 6.4             |                 |
| 46.0              |                | 3.4             | 4.4             | 5.1             |                 |
| 48.0              |                |                 |                 | 3.7             |                 |
| 危険角度 (°)          | 43             | 45              | 49              | 49              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

SC性能 31.8mブーム+2.3m+19mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 20.0              | 18.0           | 18.0            | 16.0            |                 |                 |
| 22.0              | 18.0           | 18.0            | 17.1            | 15.6            | 14.0            |
| 24.0              | 17.8           | 17.6            | 16.4            | 15.1            | 13.8            |
| 26.0              | 15.0           | 16.6            | 15.7            | 14.5            | 13.6            |
| 28.0              | 12.6           | 14.3            | 15.1            | 14.1            | 13.5            |
| 30.0              | 10.6           | 12.1            | 13.4            | 13.7            | 13.4            |
| 32.0              | 8.9            | 10.2            | 11.3            | 12.2            | 12.6            |
| 34.0              | 7.2            | 8.6             | 9.6             | 10.3            | 10.5            |
| 36.0              | 5.6            | 7.1             | 8.0             | 8.6             |                 |
| 38.0              | 4.2            | 5.5             | 6.5             | 7.1             |                 |
| 40.0              |                | 4.0             | 4.9             | 5.3             |                 |
| 危険角度 (°)          | 41             | 42              | 45              | 45              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SC性能 31.8mブーム+2.3m+31mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 9.0               | 12.0           |                 |                 |                 |                 |
| 10.0              | 12.0           |                 |                 |                 |                 |
| 11.0              | 12.0           |                 |                 |                 |                 |
| 12.0              | 12.0           |                 |                 |                 |                 |
| 14.0              | 12.0           |                 |                 |                 |                 |
| 16.0              | 12.0           |                 |                 |                 |                 |
| 18.0              | 12.0           | 12.0            |                 |                 |                 |
| 20.0              | 12.0           | 11.4            |                 |                 |                 |
| 22.0              | 12.0           | 10.7            |                 |                 |                 |
| 24.0              | 12.0           | 10.1            | 8.1             |                 |                 |
| 26.0              | 12.0           | 9.6             | 7.9             |                 |                 |
| 28.0              | 11.5           | 9.1             | 7.5             |                 |                 |
| 30.0              | 10.8           | 8.7             | 7.3             | 6.3             |                 |
| 32.0              | 10.0           | 8.3             | 7.0             | 6.2             |                 |
| 34.0              | 9.3            | 7.9             | 6.8             | 6.0             | 5.4             |
| 36.0              | 8.4            | 7.6             | 6.6             | 5.9             | 5.4             |
| 38.0              | 7.3            | 7.3             | 6.4             | 5.8             | 5.4             |
| 40.0              | 6.1            | 7.0             | 6.2             | 5.7             | 5.4             |
| 42.0              | 5.0            | 6.7             | 6.0             | 5.6             | 5.4             |
| 44.0              | 3.9            | 5.6             | 5.9             | 5.5             | 5.4             |
| 46.0              | 2.9            | 4.5             | 5.8             | 5.4             | 5.4             |
| 48.0              |                | 3.5             | 4.7             | 5.4             |                 |
| 50.0              |                |                 | 3.6             | 4.3             |                 |
| 52.0              |                |                 |                 | 3.1             |                 |
| 危険角度 (°)          | 43             | 46              | 49              | 49              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

# 10m — 31m スーパーラフィングブーム【31.8mブーム時】

SD性能 31.8mブーム+2.3m+10mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 5.0               | 48.0           |                 |                 |                 |                 |
| 6.0               | 48.0           |                 |                 |                 |                 |
| 7.0               | 48.0           |                 |                 |                 |                 |
| 8.0               | 48.0           |                 |                 |                 |                 |
| 9.0               | 48.0           | 47.5            |                 |                 |                 |
| 10.0              | 48.0           | 45.7            |                 |                 |                 |
| 11.0              | 48.0           | 44.0            | 38.0            |                 |                 |
| 12.0              | 46.1           | 42.3            | 37.1            | 33.2            |                 |
| 14.0              | 34.2           | 36.8            | 35.3            | 32.2            | 28.5            |
| 16.0              | 26.2           | 28.4            | 30.2            | 31.4            | 28.5            |
| 18.0              | 20.5           | 22.2            | 23.8            | 24.9            | 25.5            |
| 20.0              | 16.1           | 17.6            | 18.9            | 19.8            | 20.2            |
| 22.0              | 12.7           | 14.0            | 15.1            | 15.8            | 16.0            |
| 24.0              | 10.0           | 11.1            | 12.0            | 12.5            | 12.7            |
| 26.0              | 7.4            | 8.7             | 9.4             | 9.9             |                 |
| 28.0              | 5.0            | 6.1             | 7.0             | 7.4             |                 |
| 30.0              |                |                 | 4.6             | 4.8             |                 |
| 危険角度 (°)          | 47             | 50              | 50              | 50              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SD性能 31.8mブーム+2.3m+23mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           |                 |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 17.8            |                 |                 |                 |
| 20.0              | 18.0           | 16.8            | 13.6            |                 |                 |
| 22.0              | 16.1           | 15.9            | 13.1            |                 |                 |
| 24.0              | 13.3           | 15.1            | 12.6            | 11.0            |                 |
| 26.0              | 11.0           | 13.1            | 12.1            | 10.7            | 9.8             |
| 28.0              | 9.1            | 11.0            | 11.8            | 10.5            | 9.8             |
| 30.0              | 7.5            | 9.2             | 10.8            | 10.3            | 9.8             |
| 32.0              | 5.7            | 7.6             | 9.0             | 10.1            | 9.8             |
| 34.0              | 4.1            | 6.2             | 7.5             | 8.5             | 9.1             |
| 36.0              |                | 4.6             | 6.2             | 7.0             | 7.5             |
| 38.0              |                |                 | 4.6             | 5.7             | 6.0             |
| 40.0              |                |                 |                 | 4.0             |                 |
| 危険角度 (°)          | 52             | 54              | 56              | 56              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SD性能 31.8mブーム+2.3m+15mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 6.0               | 18.0           |                 |                 |                 |                 |
| 7.0               | 18.0           |                 |                 |                 |                 |
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           | 18.0            |                 |                 |                 |
| 11.0              | 18.0           | 18.0            |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 16.0              | 18.0           | 18.0            | 18.0            | 18.0            |                 |
| 18.0              | 18.0           | 18.0            | 18.0            | 18.0            | 18.0            |
| 20.0              | 17.7           | 18.0            | 18.0            | 18.0            | 18.0            |
| 22.0              | 14.2           | 16.1            | 17.8            | 18.0            | 18.0            |
| 24.0              | 11.5           | 13.2            | 14.6            | 15.7            | 16.4            |
| 26.0              | 9.2            | 10.7            | 11.9            | 12.9            | 13.4            |
| 28.0              | 7.1            | 8.6             | 9.7             | 10.5            | 10.8            |
| 30.0              | 5.0            | 6.6             | 7.8             | 8.4             | 8.6             |
| 32.0              |                | 4.6             | 5.8             | 6.5             |                 |
| 34.0              |                |                 |                 | 4.4             |                 |
| 危険角度 (°)          | 50             | 51              | 53              | 53              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SD性能 31.8mブーム+2.3m+27mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 15.0           |                 |                 |                 |                 |
| 9.0               | 15.0           |                 |                 |                 |                 |
| 10.0              | 15.0           |                 |                 |                 |                 |
| 11.0              | 15.0           |                 |                 |                 |                 |
| 12.0              | 15.0           |                 |                 |                 |                 |
| 14.0              | 15.0           |                 |                 |                 |                 |
| 16.0              | 15.0           | 15.0            |                 |                 |                 |
| 18.0              | 15.0           | 14.6            |                 |                 |                 |
| 20.0              | 15.0           | 13.7            |                 |                 |                 |
| 22.0              | 15.0           | 12.9            | 10.0            |                 |                 |
| 24.0              | 14.3           | 12.2            | 10.0            |                 |                 |
| 26.0              | 12.0           | 11.6            | 9.6             | 8.3             |                 |
| 28.0              | 10.0           | 11.0            | 9.3             | 8.1             |                 |
| 30.0              | 8.4            | 10.4            | 9.0             | 7.9             | 7.2             |
| 32.0              | 7.0            | 8.8             | 8.7             | 7.7             | 7.2             |
| 34.0              | 5.4            | 7.4             | 8.4             | 7.6             | 7.2             |
| 36.0              | 4.0            | 6.2             | 7.5             | 7.5             | 7.2             |
| 38.0              |                | 4.8             | 6.3             | 7.3             | 7.2             |
| 40.0              |                | 3.5             | 5.1             | 6.1             | 6.5             |
| 42.0              |                |                 | 3.8             | 4.8             | 5.2             |
| 44.0              |                |                 |                 | 3.4             |                 |
| 危険角度 (°)          | 52             | 54              | 56              | 56              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

SD性能 31.8mブーム+2.3m+19mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 18.0           | 18.0            |                 |                 |                 |
| 18.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 20.0              | 18.0           | 18.0            | 18.0            | 16.0            |                 |
| 22.0              | 15.2           | 17.6            | 17.1            | 15.6            | 14.0            |
| 24.0              | 12.5           | 14.5            | 16.4            | 15.1            | 13.8            |
| 26.0              | 10.2           | 12.0            | 13.6            | 14.5            | 13.6            |
| 28.0              | 8.3            | 9.9             | 11.3            | 12.5            | 13.2            |
| 30.0              | 6.3            | 8.1             | 9.4             | 10.4            | 10.9            |
| 32.0              | 4.6            | 6.4             | 7.7             | 8.5             | 8.9             |
| 34.0              |                | 4.7             | 6.1             | 6.9             | 7.1             |
| 36.0              |                |                 | 4.3             | 5.1             |                 |
| 危険角度 (°)          | 51             | 53              | 53              | 55              | 60              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SD性能 31.8mブーム+2.3m+31mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 9.0               | 12.0           |                 |                 |                 |                 |
| 10.0              | 12.0           |                 |                 |                 |                 |
| 11.0              | 12.0           |                 |                 |                 |                 |
| 12.0              | 12.0           |                 |                 |                 |                 |
| 14.0              | 12.0           |                 |                 |                 |                 |
| 16.0              | 12.0           |                 |                 |                 |                 |
| 18.0              | 12.0           | 12.0            |                 |                 |                 |
| 20.0              | 12.0           | 11.4            |                 |                 |                 |
| 22.0              | 12.0           | 10.7            |                 |                 |                 |
| 24.0              | 12.0           | 10.1            | 8.1             |                 |                 |
| 26.0              | 12.0           | 9.6             | 7.9             |                 |                 |
| 28.0              | 10.7           | 9.1             | 7.5             |                 |                 |
| 30.0              | 9.0            | 8.7             | 7.3             | 6.3             |                 |
| 32.0              | 7.6            | 8.3             | 7.0             | 6.2             |                 |
| 34.0              | 6.3            | 7.9             | 6.8             | 6.0             | 5.4             |
| 36.0              | 4.9            | 7.0             | 6.6             | 5.9             | 5.4             |
| 38.0              | 3.7            | 5.9             | 6.4             | 5.8             | 5.4             |
| 40.0              |                | 4.6             | 6.2             | 5.7             | 5.4             |
| 42.0              |                | 3.5             | 5.2             | 5.6             | 5.4             |
| 44.0              |                |                 | 4.0             | 5.2             | 5.4             |
| 46.0              |                |                 | 2.9             | 3.9             | 4.3             |
| 48.0              |                |                 |                 | 2.7             |                 |
| 危険角度 (°)          | 53             | 54              | 56              | 56              | 60              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |



# 10m — 31m

# スーパーラフィングブーム【31.8mブーム時】

SE性能 31.8mブーム+2.3m+10mSLブーム

| オフセット     | 0°       | 15°      | 30°      | 45°      | 60°      |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m)  | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 5.0       | 48.0     |          |          |          |          |
| 6.0       | 48.0     |          |          |          |          |
| 7.0       | 48.0     |          |          |          |          |
| 8.0       | 48.0     |          |          |          |          |
| 9.0       | 48.0     | 47.5     |          |          |          |
| 10.0      | 48.0     | 45.7     |          |          |          |
| 11.0      | 46.1     | 44.0     | 38.0     |          |          |
| 12.0      | 38.9     | 42.3     | 37.1     | 33.2     |          |
| 14.0      | 27.4     | 30.3     | 32.8     | 32.2     | 28.5     |
| 16.0      | 20.0     | 22.3     | 24.3     | 25.8     | 26.8     |
| 18.0      | 14.8     | 16.7     | 18.3     | 19.5     | 20.2     |
| 20.0      | 10.9     | 12.5     | 13.8     | 14.8     | 15.2     |
| 22.0      | 7.6      | 9.3      | 10.4     | 11.1     | 11.4     |
| 24.0      | 4.5      | 6.2      | 7.5      | 8.2      | 8.3      |
| 26.0      |          |          | 4.5      | 5.1      |          |
| 危険角度 (°)  | 54       | 57       | 57       | 57       | 60       |
| フック種類     | 83t      | 83t      | 83t      | 83t      | 83t      |
| フック質量 (t) | 1.35     | 1.35     | 1.35     | 1.35     | 1.35     |
| 掛数        | 4        | 4        | 4        | 4        | 4        |

SE性能 31.8mブーム+2.3m+23mSLブーム

| オフセット     | 0°       | 15°      | 30°      | 45°      | 60°      |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m)  | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 8.0       | 18.0     |          |          |          |          |
| 9.0       | 18.0     |          |          |          |          |
| 10.0      | 18.0     |          |          |          |          |
| 11.0      | 18.0     |          |          |          |          |
| 12.0      | 18.0     |          |          |          |          |
| 14.0      | 18.0     | 18.0     |          |          |          |
| 16.0      | 18.0     | 18.0     |          |          |          |
| 18.0      | 18.0     | 17.8     |          |          |          |
| 20.0      | 14.5     | 16.8     | 13.6     |          |          |
| 22.0      | 11.4     | 14.3     | 13.1     |          |          |
| 24.0      | 9.0      | 11.5     | 12.6     | 11.0     |          |
| 26.0      | 6.9      | 9.3      | 11.3     | 10.7     | 9.8      |
| 28.0      | 4.8      | 7.4      | 9.2      | 10.5     | 9.8      |
| 30.0      |          | 5.6      | 7.4      | 8.8      | 9.8      |
| 32.0      |          |          | 5.9      | 7.1      | 7.8      |
| 34.0      |          |          | 4.1      | 5.6      | 6.2      |
| 36.0      |          |          |          |          | 4.4      |
| 危険角度 (°)  | 60       | 62       | 62       | 65       | 65       |
| フック種類     | 83t      | 83t      | 83t      | 83t      | 83t      |
| フック質量 (t) | 1.35     | 1.35     | 1.35     | 1.35     | 1.35     |
| 掛数        | 4        | 4        | 4        | 4        | 4        |

SE性能 31.8mブーム+2.3m+15mSLブーム

| オフセット     | 0°       | 15°      | 30°      | 45°      | 60°      |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m)  | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 6.0       | 18.0     |          |          |          |          |
| 7.0       | 18.0     |          |          |          |          |
| 8.0       | 18.0     |          |          |          |          |
| 9.0       | 18.0     |          |          |          |          |
| 10.0      | 18.0     | 18.0     |          |          |          |
| 11.0      | 18.0     | 18.0     |          |          |          |
| 12.0      | 18.0     | 18.0     |          |          |          |
| 14.0      | 18.0     | 18.0     | 18.0     |          |          |
| 16.0      | 18.0     | 18.0     | 18.0     | 18.0     |          |
| 18.0      | 16.4     | 18.0     | 18.0     | 18.0     | 18.0     |
| 20.0      | 12.5     | 14.9     | 17.0     | 18.0     | 18.0     |
| 22.0      | 9.5      | 11.5     | 13.3     | 14.7     | 15.6     |
| 24.0      | 6.8      | 8.9      | 10.4     | 11.6     | 12.3     |
| 26.0      |          | 6.4      | 8.0      | 9.0      | 9.5      |
| 28.0      |          | 4.1      | 5.7      | 6.8      | 7.1      |
| 30.0      |          |          |          | 4.4      | 4.6      |
| 危険角度 (°)  | 58       | 58       | 60       | 60       | 60       |
| フック種類     | 83t      | 83t      | 83t      | 83t      | 83t      |
| フック質量 (t) | 1.35     | 1.35     | 1.35     | 1.35     | 1.35     |
| 掛数        | 4        | 4        | 4        | 4        | 4        |

SE性能 31.8mブーム+2.3m+27mSLブーム

| オフセット     | 0°       | 15°      | 30°      | 45°      | 60°      |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m)  | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 8.0       | 15.0     |          |          |          |          |
| 9.0       | 15.0     |          |          |          |          |
| 10.0      | 15.0     |          |          |          |          |
| 11.0      | 15.0     |          |          |          |          |
| 12.0      | 15.0     |          |          |          |          |
| 14.0      | 15.0     |          |          |          |          |
| 16.0      | 15.0     | 15.0     |          |          |          |
| 18.0      | 15.0     | 14.6     |          |          |          |
| 20.0      | 15.0     | 13.7     |          |          |          |
| 22.0      | 12.5     | 12.9     | 10.0     |          |          |
| 24.0      | 10.0     | 12.2     | 10.0     |          |          |
| 26.0      | 8.0      | 10.6     | 9.6      | 8.3      |          |
| 28.0      | 6.2      | 8.6      | 9.3      | 8.1      |          |
| 30.0      | 4.3      | 7.0      | 8.9      | 7.9      | 7.2      |
| 32.0      |          | 5.5      | 7.3      | 7.7      | 7.2      |
| 34.0      |          | 3.9      | 6.0      | 7.3      | 7.2      |
| 36.0      |          |          | 4.5      | 5.9      | 6.6      |
| 38.0      |          |          | 3.0      | 4.5      | 5.2      |
| 40.0      |          |          |          |          | 3.6      |
| 危険角度 (°)  | 60       | 62       | 62       | 65       | 65       |
| フック種類     | 24t      | 24t      | 24t      | 24t      | 24t      |
| フック質量 (t) | 0.88     | 0.88     | 0.88     | 0.88     | 0.88     |
| 掛数        | 2        | 2        | 2        | 2        | 2        |

SE性能 31.8mブーム+2.3m+19mSLブーム

| オフセット     | 0°       | 15°      | 30°      | 45°      | 60°      |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m)  | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 8.0       | 18.0     |          |          |          |          |
| 9.0       | 18.0     |          |          |          |          |
| 10.0      | 18.0     |          |          |          |          |
| 11.0      | 18.0     |          |          |          |          |
| 12.0      | 18.0     | 18.0     |          |          |          |
| 14.0      | 18.0     | 18.0     |          |          |          |
| 16.0      | 18.0     | 18.0     |          |          |          |
| 18.0      | 17.6     | 18.0     | 18.0     |          |          |
| 20.0      | 13.6     | 16.5     | 18.0     | 16.0     |          |
| 22.0      | 10.6     | 13.0     | 15.3     | 15.6     | 14.0     |
| 24.0      | 8.1      | 10.3     | 12.3     | 13.9     | 13.8     |
| 26.0      | 5.7      | 8.1      | 9.8      | 11.2     | 12.1     |
| 28.0      |          | 6.0      | 7.7      | 8.9      | 9.7      |
| 30.0      |          |          | 5.8      | 7.0      | 7.6      |
| 32.0      |          |          |          | 5.1      | 5.6      |
| 危険角度 (°)  | 59       | 61       | 62       | 62       | 63       |
| フック種類     | 83t      | 83t      | 83t      | 83t      | 83t      |
| フック質量 (t) | 1.35     | 1.35     | 1.35     | 1.35     | 1.35     |
| 掛数        | 4        | 4        | 4        | 4        | 4        |

SE性能 31.8mブーム+2.3m+31mSLブーム

| オフセット     | 0°       | 15°      | 30°      | 45°      | 60°      |
|-----------|----------|----------|----------|----------|----------|
| 作業半径 (m)  | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) | 荷重 (ton) |
| 9.0       | 12.0     |          |          |          |          |
| 10.0      | 12.0     |          |          |          |          |
| 11.0      | 12.0     |          |          |          |          |
| 12.0      | 12.0     |          |          |          |          |
| 14.0      | 12.0     |          |          |          |          |
| 16.0      | 12.0     |          |          |          |          |
| 18.0      | 12.0     | 12.0     |          |          |          |
| 20.0      | 12.0     | 11.4     |          |          |          |
| 22.0      | 12.0     | 10.7     |          |          |          |
| 24.0      | 10.7     | 10.1     | 8.1      |          |          |
| 26.0      | 8.7      | 9.6      | 7.9      |          |          |
| 28.0      | 7.0      | 9.1      | 7.5      |          |          |
| 30.0      | 5.3      | 7.9      | 7.3      | 6.3      |          |
| 32.0      | 3.7      | 6.5      | 7.0      | 6.2      |          |
| 34.0      |          | 5.1      | 6.8      | 6.0      | 5.4      |
| 36.0      |          | 3.7      | 5.8      | 5.9      | 5.4      |
| 38.0      |          |          | 4.6      | 5.8      | 5.4      |
| 40.0      |          |          | 3.2      | 4.8      | 5.4      |
| 42.0      |          |          |          | 3.5      | 4.4      |
| 44.0      |          |          |          |          | 2.9      |
| 危険角度 (°)  | 60       | 62       | 63       | 65       | 65       |
| フック種類     | 24t      | 24t      | 24t      | 24t      | 24t      |
| フック質量 (t) | 0.88     | 0.88     | 0.88     | 0.88     | 0.88     |
| 掛数        | 2        | 2        | 2        | 2        | 2        |

# 10m — 31m スーパーラフィングブーム【31.8mブーム時】

SF性能 31.8mブーム+2.3m+10mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 5.0               | 48.0           |                 |                 |                 |                 |
| 6.0               | 48.0           |                 |                 |                 |                 |
| 7.0               | 48.0           |                 |                 |                 |                 |
| 8.0               | 48.0           |                 |                 |                 |                 |
| 9.0               | 48.0           | 47.5            |                 |                 |                 |
| 10.0              | 44.1           | 45.7            |                 |                 |                 |
| 11.0              | 35.4           | 39.5            | 38.0            |                 |                 |
| 12.0              | 28.7           | 32.2            | 35.3            | 33.2            |                 |
| 14.0              | 19.6           | 22.3            | 24.7            | 26.6            | 27.8            |
| 16.0              | 13.7           | 15.9            | 17.7            | 19.2            | 20.1            |
| 18.0              | 9.6            | 11.4            | 12.9            | 14.0            | 14.6            |
| 20.0              |                | 8.0             | 9.2             | 10.1            | 10.6            |
| 22.0              |                |                 | 6.4             | 7.1             | 7.4             |
| 危険角度 (°)          | 63             | 64              | 64              | 64              | 64              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SF性能 31.8mブーム+2.3m+23mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           |                 |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 17.4           | 18.0            |                 |                 |                 |
| 18.0              | 13.1           | 16.7            |                 |                 |                 |
| 20.0              | 9.9            | 13.0            | 13.6            |                 |                 |
| 22.0              | 7.4            | 10.1            | 12.7            |                 |                 |
| 24.0              |                | 7.9             | 10.1            | 11.0            |                 |
| 26.0              |                | 6.0             | 8.0             | 9.7             | 9.8             |
| 28.0              |                |                 | 6.2             | 7.7             | 8.8             |
| 30.0              |                |                 | 4.7             | 6.0             | 6.9             |
| 32.0              |                |                 |                 | 4.5             | 5.3             |
| 危険角度 (°)          | 66             | 67              | 68              | 69              | 70              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SF性能 31.8mブーム+2.3m+15mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 6.0               | 18.0           |                 |                 |                 |                 |
| 7.0               | 18.0           |                 |                 |                 |                 |
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           | 18.0            |                 |                 |                 |
| 11.0              | 18.0           | 18.0            |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            | 18.0            |                 |                 |
| 16.0              | 15.4           | 18.0            | 18.0            | 18.0            |                 |
| 18.0              | 11.2           | 13.7            | 16.1            | 18.0            | 18.0            |
| 20.0              | 8.0            | 10.2            | 12.2            | 13.8            | 14.9            |
| 22.0              |                | 7.5             | 9.2             | 10.5            | 11.4            |
| 24.0              |                |                 | 6.8             | 7.9             | 8.5             |
| 26.0              |                |                 |                 | 5.7             | 6.2             |
| 危険角度 (°)          | 64             | 65              | 66              | 66              | 66              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SF性能 31.8mブーム+2.3m+27mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 15.0           |                 |                 |                 |                 |
| 9.0               | 15.0           |                 |                 |                 |                 |
| 10.0              | 15.0           |                 |                 |                 |                 |
| 11.0              | 15.0           |                 |                 |                 |                 |
| 12.0              | 15.0           |                 |                 |                 |                 |
| 14.0              | 15.0           |                 |                 |                 |                 |
| 16.0              | 15.0           | 15.0            |                 |                 |                 |
| 18.0              | 14.2           | 14.6            |                 |                 |                 |
| 20.0              | 10.9           | 13.7            |                 |                 |                 |
| 22.0              | 8.4            | 11.5            | 10.0            |                 |                 |
| 24.0              | 6.5            | 9.1             | 10.0            |                 |                 |
| 26.0              |                | 7.2             | 9.5             | 8.3             |                 |
| 28.0              |                | 5.7             | 7.7             | 8.1             |                 |
| 30.0              |                |                 | 6.1             | 7.7             | 7.2             |
| 32.0              |                |                 | 4.8             | 6.2             | 7.2             |
| 34.0              |                |                 |                 | 4.9             | 5.7             |
| 36.0              |                |                 |                 | 3.6             | 4.4             |
| 危険角度 (°)          | 66             | 67              | 68              | 69              | 70              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |

SF性能 31.8mブーム+2.3m+19mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 8.0               | 18.0           |                 |                 |                 |                 |
| 9.0               | 18.0           |                 |                 |                 |                 |
| 10.0              | 18.0           |                 |                 |                 |                 |
| 11.0              | 18.0           |                 |                 |                 |                 |
| 12.0              | 18.0           | 18.0            |                 |                 |                 |
| 14.0              | 18.0           | 18.0            |                 |                 |                 |
| 16.0              | 16.5           | 18.0            |                 |                 |                 |
| 18.0              | 12.2           | 15.3            | 18.0            |                 |                 |
| 20.0              | 9.0            | 11.7            | 14.2            | 16.0            |                 |
| 22.0              | 6.6            | 8.9             | 11.1            | 12.9            | 14.0            |
| 24.0              |                | 6.7             | 8.5             | 10.1            | 11.2            |
| 26.0              |                |                 | 6.5             | 7.8             | 8.7             |
| 28.0              |                |                 | 4.8             | 5.9             | 6.6             |
| 30.0              |                |                 |                 | 4.2             | 4.8             |
| 危険角度 (°)          | 65             | 66              | 66              | 67              | 67              |
| フック種類             | 83t            | 83t             | 83t             | 83t             | 83t             |
| フック質量 (t)         | 1.35           | 1.35            | 1.35            | 1.35            | 1.35            |
| 掛数                | 4              | 4               | 4               | 4               | 4               |

SF性能 31.8mブーム+2.3m+31mSLブーム

| オフセット<br>作業半径 (m) | 0°<br>荷重 (ton) | 15°<br>荷重 (ton) | 30°<br>荷重 (ton) | 45°<br>荷重 (ton) | 60°<br>荷重 (ton) |
|-------------------|----------------|-----------------|-----------------|-----------------|-----------------|
| 9.0               | 12.0           |                 |                 |                 |                 |
| 10.0              | 12.0           |                 |                 |                 |                 |
| 11.0              | 12.0           |                 |                 |                 |                 |
| 12.0              | 12.0           |                 |                 |                 |                 |
| 14.0              | 12.0           |                 |                 |                 |                 |
| 16.0              | 12.0           |                 |                 |                 |                 |
| 18.0              | 12.0           | 12.0            |                 |                 |                 |
| 20.0              | 11.6           | 11.4            |                 |                 |                 |
| 22.0              | 9.1            | 10.7            |                 |                 |                 |
| 24.0              | 7.1            | 10.0            | 8.1             |                 |                 |
| 26.0              | 5.5            | 8.1             | 7.9             |                 |                 |
| 28.0              |                | 6.5             | 7.5             |                 |                 |
| 30.0              |                | 5.1             | 7.2             | 6.3             |                 |
| 32.0              |                |                 | 5.8             | 6.2             |                 |
| 34.0              |                |                 | 4.6             | 6.0             | 5.4             |
| 36.0              |                |                 | 3.5             | 4.9             | 5.4             |
| 38.0              |                |                 |                 | 3.9             | 4.7             |
| 40.0              |                |                 |                 |                 | 3.6             |
| 危険角度 (°)          | 66             | 68              | 69              | 70              | 70              |
| フック種類             | 24t            | 24t             | 24t             | 24t             | 24t             |
| フック質量 (t)         | 0.88           | 0.88            | 0.88            | 0.88            | 0.88            |
| 掛数                | 2              | 2               | 2               | 2               | 2               |